

Jeffrey M. Gold, Esq. (pro hac vice)
Morgan, Lewis & Bockius, LLP
101 Park Avenue
New York, New York 10178-0060
Tel: (212) 309-6000
Fax: (212) 309-6001

J. Kevin Fee, Esq. (D.C. Bar No. 494016)
Morgan, Lewis & Bockius, LLP
1111 Pennsylvania Avenue, NW
Washington, D.C. 20004
Tel.: (202) 739-3000
Fax: (202) 739-3001

Scott D. Stimpson, Esq. (pro hac vice)
The Law Office of Scott D. Stimpson
445 Hamilton Avenue -- Suite 1102
White Plains, New York 10601
Tel: (203) 258-8412

Attorneys for Plaintiff and Counter- Defendant Casio
Inc. and Counter-Defendant Casio Computer Co., Ltd.

**UNITED STATES DISTRICT COURT
DISTRICT OF COLUMBIA**

CASIO INC.,

Plaintiff

v.

PAPST LICENSING GMBH & CO. KG

Defendant.

PAPST LICENSING GMBH & CO. KG,
Counter-Plaintiff

v.

**CASIO INC. and CASIO COMPUTER
CO., LTD.**

Counter-Defendants

Case No. 1:06-CV-01751

**Judge: Gladys Kessler
Magistrate Judge: Deborah Robinson**

Next status conference: December 4, 2007

**REPLY MEMORANDUM IN SUPPORT OF CASIO'S MOTION FOR SANCTIONS
FOR NON-COMPLIANCE WITH COURT ORDER**

I. INTERROGATORY 1

A. Accused products

Papst claims (Opp. Mem. at pg. 3) that Casio did not request the identity of the accused products. The interrogatory, however, requested the analysis “for each accused product.”

Papst next claims that “[m]any of the at-issue Casio cameras have been discontinued by Casio and thus, are not available to Papst without further discovery.” *Id.* at 4. But Casio produced manuals for all of its digital cameras on May 21, 2007;¹ there are unaccused models of digital cameras available for purchase and on the Casio website; and Casio advised Papst on May 21 that samples of all cameras were available for its inspection (See Exhibit A, p.5.).

Papst next complains that it “does not yet have the means to verify and confirm infringement of any other cameras.” Opp. Mem. at 4. But Papst had none of this information for the six products it did accuse, and had no problem accusing them of infringement. The reality is that Papst is interpreting these claims so broadly that any digital camera would infringe – a fact that would be apparent if Papst had provided its claim interpretations.

B. The Asserted Claims

Papst asserts that it cannot confirm infringement of any other claims without further information from Casio. The Papst interpretations, had they been provided, would shed interesting light on this argument, too. Even without the Papst interpretations, however, its argument makes little sense for these patents. The other independent claims are substantively very close to claims 1 in both patents and so if Papst could assert claims 1 it could have asserted these other claims. Exhibit B (compare asserted claim 1 with claims 11 and 14) and Exhibit C

¹ Gold Dec. ¶ 3.

(compare asserted claim 1 with claims 17 and 18). As for the dependent claims, Papst points to nothing that could require additional information from Casio.

C. Claim Interpretation

Papst asserts that, because Casio already provided an invalidity analysis, there is nothing wrong with the Papst claim constructions. But these responses were limited due to the failure of Papst to provide its claim constructions, and they so state. Exhibit B to Opp. Mem., page 26. For an interesting comparison, please also see the Casio interpretations at pages 7-24 (the first sentences under each claim element). The lawyers for Papst are experienced patent litigators. They know what it means to interpret patent claims.²

D. How Does Casio Infringe?

Papst claims the “theory” of infringement was not requested. The interrogatory, however, reads: “state in full and complete detail the bases for such charge of infringement. . . .”

As Papst has now represented to this Court that its response is complete (Opp. Mem. at 7), the Court should order that Papst is stuck with its response, and that it may not now assert contributory infringement or inducement of infringement.³

II. INTERROGATORY 2

Papst did not make any effort to comply with the Court Order within the time allowed, and its refusal to do so until Casio was forced to file another motion for sanctions is a another violation of that Order. This conduct is not “moot”; it is disrespect for the Court’s Order.

² See *Papst Licensing GmbH and Co. KG v. Sunonwelath Electric Machine Ind. Co., Ltd.*, No. 03 C 1001, 2004 U.S. Dist. LEXIS 4402, at *8-9, 11 (N.D. Ill. Mar. 18, 2004) (represented by Mr. Schnayer, the court refers to Papst’s proposed claim interpretations: “Papst argues that the Court should define the term ‘drive motor means’ to mean any type of electric motor that...”; and “Papst argues that the Court should construe the claim term in its entirety to mean the fan housing...”) (emphases added). Thus, Papst and its counsel know that statements like those in the Papst supplemental response are not claim interpretations.

³ Under Rule 37(c)(1), a party who fails to disclose information required by Rule 26, or to amend a prior response to discovery under Rule 26, “without substantial justification” for the failure shall be precluded from using the information not disclosed as evidence at trial. Fed. R. Civ. P. 37(c)(1).

III. INTERROGATORY 3

Papst's claim that it has no evidence to support secondary considerations is false. Commercial success, for example, is evidenced by commercial products allegedly covered by the patents.⁴ Counsel for Papst has enough evidence to accuse 39 companies of infringement, and demand that all take licenses, and Papst has now even sued Samsung, Fuji, and Olympus. Papst and its counsel have detailed files on all these companies, with information on the accused cameras, infringement analyses, and more. None of this is mentioned in the Court-ordered response. Papst should be stuck with its decision to not allege any of this as commercial success.

Papst also refuses to provide information on any of the other alleged secondary considerations. Papst asserts failure of others (who failed?), a long standing problem (what problem?), long felt need (what need?), unexpected results (what results and what was unexpected about them?), copying (what copying?), and skepticism of the inventions (who was skeptical?), but there is no detail or support for any of them.

The named inventor (Michael Tasler) signed an Assignment contractually obligating the assignor (his company) to "render such assistance to [Papst] as necessary to . . . enable [Papst] to . . . enforce proper patent protection for the Patent Rights." Exhibit D, ¶3. The inventor also agreed that "[Papst] will, upon its request, be provided promptly with all pertinent facts and documents relating to [the patents-in-suit] as may be known and/or accessible to [the assignor]...." *Id.* ¶5. Surely the inventor was able to identify the long standing problem he allegedly solved, the long felt need, his unexpected results, skepticism, etc., but Papst refused to provide it despite the Court Orders and so should be stuck with its decision.⁵

⁴ See *Ecolchem, Inc. v. Southern Cal. Edison Co.*, 227 F.3d 1361, 1377 (Fed. Cir. 2000); *J.T. Eaton & Co. v. Atlantic Paste & Glue Co.*, 106 F.3d 1563, 1571 (Fed. Cir. 1997).

⁵ This is not the first case where Papst has played games and pretended it does not have access to the inventor. Indeed, the same contractual language was at issue in *Minebea Co., Ltd. v. Papst*, 370 F. Supp. 2d 302, 310

IV. INTERROGATORY 4

The Papst time restriction: Papst states at page 8 of its Opposition that it has provided responsive documents “up until the date the Complaint was filed. . . .” This artificial deadline, we believe, is also resulting in critical information being withheld on this interrogatory. The deadline imposed by Papst is a continued objection, which this Court ordered waived.⁶

Papst’s 33(d) response: Papst provided a 22-page letter, including 18 pages of single-spaced Bates numbers supposedly responding to this interrogatory. Exhibit F. This is not appropriate.⁷ Moreover, information on Papst orally reducing its offers is missing altogether.

As with its response to interrogatory 2, Papst made no effort to identify documents under Rule 33(d) until Casio was forced to file another motion for sanctions. Even if the document identification had been a complete response as ordered, it was untimely.

V. INTERROGATORY 5

Papst and its counsel have access to the patent, the prosecution history, the closest prior art (see their response to interrogatory 2), and the inventor (see discussion of interrogatory 3, above). These are the key sources of evidence to determine the level of ordinary skill in the art.⁸ Papst made no effort to respond to this interrogatory.

(D.D.C. 2005) (court found that since “the inventors are expressly required to testify at the request of Papst by written contracts, the Court cannot but conclude that Papst’s ‘request’ for the voluntary appearance of the inventor witnesses was made with a wink and a nod and that their failure to appear must be attributed to Papst.”).

⁶ Several days ago, we inquired with counsel for Papst as to its unilateral imposition of this deadline and whether they were imposing this time restriction on the interrogatory response for some reason. Despite a follow up inquiry, counsel for Papst has refused to respond. Exhibit E.

⁷ *In re Sulfuric Acid Antitrust Litig.*, 231 F.R.D. 320, 326 (N.D. Ill. 2005) (“[P]laintiffs are entitled to complete disclosure, which cannot be obtained by pouring through a mountain of material.”); *Cambridge Elecs. Corp. v. MGA Elecs., Inc.*, 227 F.R.D. 313, 322-23 (C.D. Cal. 2004).

⁸ *See Environmental Designs, Ltd. v. Union Oil Co.*, 713 F.2d 693, 696 (Fed. Cir. 1983).

VI. INTERROGATORY 6

Papst has access to the inventor. Exhibit D. It is not credible for Papst to claim it could not answer this interrogatory about dates of invention and related information. Papst simply refused to comply with the Court Orders.

III. CONCLUSION

For all the foregoing reasons, we respectfully request that the Court enter our Proposed Order.

Respectfully submitted,

DATED: July 10, 2007

/s/ Scott D. Stimpson
Jeffrey M. Gold, Esq. (pro hac vice)
Morgan, Lewis & Bockius, LLP
101 Park Avenue
New York, New York 10178-0060
Tel: (212) 309-6000
Fax: (212) 309-6001

J. Kevin Fee, Esq. (D.C. Bar No. 494016)
Morgan, Lewis & Bockius, LLP
1111 Pennsylvania Avenue, NW
Washington, D.C. 20004
Tel.: (202) 739-3000
Fax: (202) 739-3001

Scott D. Stimpson, Esq. (pro hac vice)
The Law Office of Scott D. Stimpson
Suite 1102
445 Hamilton Avenue
White Plains, New York 10601
Tel: (203) 258-8412

Attorneys for Plaintiff and Counter- Defendant Casio Inc.
and Counter-Defendant Casio Computer Co., Ltd.

UNITED STATES DISTRICT COURT
FOR THE DISTRICT OF COLUMBIA

-----X	
CASIO INC., 570 Mount Pleasant Avenue, Dover, New Jersey 07801	:
	:
Plaintiff,	: Civil Action No. 1:06 CV 01751
	: Judge: Gladys Kessler
v.	: Magistrate: Deborah Robinson
	: Next status conference: December 4, 2007
	:
	:
PAPST LICENSING GMBH & CO. KG, Bahnhofstrasse 33, 78112 Georgen, Germany	:
	:
Defendant.	:
-----X	
-----X	
PAPST LICENSING GMBH & CO. KG, Bahnhofstrasse 33, 78112 Georgen, Germany	:
	:
Counter-Plaintiff,	: Civil Action No. 1:06 CV 01751
	: Judge: Gladys Kessler
v.	: Magistrate: Deborah Robinson
	: Next status conference: December 4, 2007
	:
	:
CASIO INC. and CASIO COMPUTER CO., LTD.	:
	:
Counter-Defendants	:
-----X	

DECLARATION OF JEFFREY M. GOLD, ESQ.

I, Jeffrey M. Gold, hereby declare as follows:

1. I am a partner at the law firm of Morgan, Lewis & Bockius LLP in the New York Office located at 101 Park Avenue, New York, New York 10178.
2. I have been admitted to practice law in the State of New York since 1997. I am further admitted to practice in the Southern and Eastern Districts of New York, the Federal Circuit Court of Appeals and before the Patent and Trademark Office. I am also currently admitted pro hac vice before this court as part of this action.

3. On May 21, 2007, counsel for Casio produced a DVD containing product manuals for all of Casio's digital camera models in English and Japanese.

4. Attached hereto as Exhibit A, is a true and correct copy of the relevant portions of Counter-defendant Casio Computer Co. Ltd.'s Objections and Responses to Papst Licensing GMBH & Co. KG's First Set of Requests for the Production of Documents and Things to Casio Computer Co., Ltd., served on counsel for Papst Licensing GMBH & Co. KG on May 21, 2007.

5. Attached hereto as Exhibit B is a true and correct copy of United States Patent Number 6,470,399.

6. Attached hereto as Exhibit C is a true and correct copy of United States Patent Number 6,895,449.

7. Attached hereto as Exhibit D is true and correct copy the Assignment regarding the 6,470,399 and 6,895,449 patents executed on March 8, 2006.


8. Attached hereto as Exhibit E is a true and correct copy of Scott Stimpson's July 3 and July 6, 2007 e-mail to Joseph Cwik.

9. Attached hereto as Exhibit F is true and correct copy Joseph Cwik's June 29, 2007 letter to Jeffrey Gold.


I declare under penalty of perjury under the laws of the United States of America that the foregoing is true and correct.

Dated: July 10, 2007

By: _____



Jeffrey M. Gold



UNITED STATES DISTRICT COURT
FOR THE DISTRICT OF COLUMBIA

-----X	:	
CASIO INC.	:	
	:	
Plaintiff,	:	
v.	:	Civil Action No. 1:06 CV 01751
	:	
	:	Judge: Gladys Kessler
PAPST LICENSING GMBH & CO. KG	:	
	:	
Defendant.	:	
-----X	:	
PAPST LICENSING GMBH & CO. KG	:	
	:	
Counter-Plaintiff	:	
v.	:	
	:	
CASIO INC. and	:	
CASIO COMPUTER CO., LTD.	:	
	:	
Counter-Defendants.	:	
-----X	:	

**CASIO COMPUTER CO., LTD.'S OBJECTIONS AND RESPONSES TO
PAPST LICENSING GMBH & CO. KG'S FIRST SET OF REQUESTS FOR THE
PRODUCTION OF DOCUMENTS AND THINGS TO CASIO COMPUTER CO., LTD.**

Casio Computer Co., Ltd. ("Casio Japan") objects to the entirety of these document requests, as they were not served in good faith and clearly were prepared in violation of Federal Rule of Civil Procedure 26(g). The only possible purpose for Papst serving discovery requests of this nature is to increase the expense to Casio Japan in an attempt to force it to settle. Papst is hereby put on notice that Casio Japan intends to seek sanctions for this discovery abuse, and that these document requests will be used as evidence to support Casio Japan's vigorous pursuit of attorney fees and costs in this litigation. Casio Japan will produce some documents to Papst, but in doing so does not in any way agree that any portion of these document requests were proper.

unduly burdensome, and calls for irrelevant information not reasonably calculated to lead to the discovery of admissible evidence.

Metadata: Casio Japan objects to this instruction as overly broad, unduly burdensome, calling for irrelevant information and not reasonably calculated to lead to the discovery of admissible evidence. Casio Japan also objects to the interrogatories buried in this instruction. Casio Japan will not respond to interrogatories that are couched as document requests, and objects to them as overly broad, unduly burdensome, and as calling for irrelevant information not reasonably calculated to lead to the discovery of admissible evidence.

SPECIFIC OBJECTIONS AND RESPONSES TO DOCUMENT REQUESTS

All responses below are expressly subject to General and specific objections.

1. One sample of each and every Casio Digital Camera that has been used, manufactured, sold, offered for sale, licensed or imported into the United States since October 22, 2002.

Objection: Casio Japan objects to this request as overly broad, unduly burdensome, and as calling for irrelevant documents and things that are not reasonably calculated to lead to the discovery of admissible evidence.

Response: Subject to objections, Casio Japan will produce samples, or provide for inspection, all Casio Cameras specifically accused of infringement by Papst, and prior art cameras that Casio Japan will rely upon in this litigation. Samples will only be provided upon advance payment of the camera costs.

2. All documents referring or relating to the research, development, design, redesign, prototype production, testing, licensing, or commercial production of any and all Casio Digital Cameras.

CERTIFICATE OF SERVICE


The undersigned hereby certifies that a copy of the foregoing CASIO COMPUTER CO., LTD.'S OBJECTIONS TO PAPST LICENSING GMBH & CO. KG'S FIRST SET OF DOCUMENT REQUESTS TO CASIO COMPUTER CO. LTD was served on this, the 21st day of May, 2007, upon the attorneys for Papst as follows:

VIA U.S. MAIL and E-MAIL

Jerold B. Schnayer
Joseph E. Cwik
WELSH & KATZ, LTD.
120 South Riverside Plaza • 22nd Floor
Chicago, Illinois 60606

Campbell Killefer (Bar No. 268433)
VENABLE LLP
575 7th Street, N.W.
Washington, D.C. 20004
(202) 344-4000

Attorneys for Defendant/Counter-Plaintiff,
Papst Licensing GmbH & Co. KG



US006470399B1

United States Patent
Tasler

(10) Patent No.: US 6,470,399 B1
(45) Date of Patent: Oct. 22, 2002

(54) FLEXIBLE INTERFACE FOR COMMUNICATION BETWEEN A HOST AND AN ANALOG I/O DEVICE CONNECTED TO THE INTERFACE REGARDLESS THE TYPE OF THE I/O DEVICE

(75) Inventor: Michael Tasler, Würzburg (DE)
(73) Assignee: Labortechnik Tasler GmbH, Wuerzburg (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/331,002
(22) PCT Filed: Mar. 3, 1998
(86) PCT No.: PCT/EP98/01187
§ 371 (c)(1),
(2), (4) Date: Jun. 14, 1999
(87) PCT Pub. No.: WO98/39710
PCT Pub. Date: Sep. 11, 1998

(30) Foreign Application Priority Data
Mar. 4, 1997 (DE) 197 08 755
(51) Int. Cl.⁷ G06F 13/14
(52) U.S. Cl. 710/16; 710/62; 710/63
(58) Field of Search 710/15, 16, 11,
710/12, 62, 63, 64; 703/23, 24, 25

(56) References Cited

U.S. PATENT DOCUMENTS

5,291,611 A	3/1994	Davis et al.	
5,297,124 A *	3/1994	Plotkin et al.	703/25
5,430,855 A *	7/1995	Walsh et al.	703/23
5,444,644 A	8/1995	Divjak	
5,487,154 A	1/1996	Gunji	
5,499,378 A *	3/1996	McNeill et al.	703/24
5,506,692 A	4/1996	Murata	
5,510,774 A	4/1996	Loncle	
5,548,783 A *	8/1996	Jones et al.	710/15
6,012,113 A *	1/2000	Tuckner	710/64

FOREIGN PATENT DOCUMENTS

DE	195 28 889 A1	2/1997
EP	0 436 458 A2	7/1991
EP	0 685 799 A1	12/1995
JP	06301607 A	10/1994
JP	08110883 A	4/1996
WO	WO94/19746	9/1994

OTHER PUBLICATIONS

Steve Martin, "PC-based Data Acquisition in an Industrial Environment," pp. 1-3 (1990).
Payne et al., "High Speed PC-based Data Acquisition Systems," IEEE, pp. 2140-2145 (1995).
National Instruments Corporation, "Dynamic Signal Acquisition and DSP Board for the PC AT," IEEE 488 and VXibus Control, Data Acquisition, and Analysis, pp. 3-118-3-123, (1994).
IBM Corporation, "Communication Method between Devices through FDD Interface," IBM Technical Disclosure Bulletin, vol. 38 (No. 05), p. 245 (May, 1995).

* cited by examiner

Primary Examiner—Thomas Lee


Assistant Examiner—Thuan Du

(74) Attorney, Agent, or Firm—Patton Boggs LLP

(57) ABSTRACT

An interface device (10) provides fast data communication between a host device with input/output interfaces and a data transmit/receive device, wherein the interface device (10) comprises a processor means (13), a memory means (14), a first connecting device (12) for interfacing the host device with the interface device, and a second connecting device (15) for interfacing the interface device (10) with the data transmit/receive device. The interface device (10) is configured by the processor means (13) and the memory means (14) in such a way that, when receiving an inquiry from the host device via the first connecting device (12) as to the type of a device attached to the host device, regardless of the type of the data transmit/receive device, the interface device sends a signal to the host device via the first connecting device (12) which signals to the host device that it is communicating with an input/output device.

15 Claims, 2 Drawing Sheets



U.S. Patent

Oct. 22, 2002

Sheet 1 of 2

US 6,470,399 B1




FIG. 1




FIG. 2

US 6,470,399 B1

1

FLEXIBLE INTERFACE FOR COMMUNICATION BETWEEN A HOST AND AN ANALOG I/O DEVICE CONNECTED TO THE INTERFACE REGARDLESS THE TYPE OF THE I/O DEVICE

FIELD OF THE INVENTION

The present invention relates to the transfer of data and in particular to interface devices for communication between a computer or host device and a data transmit/receive device from which data is to be acquired or with which two-way communication is to take place.

BACKGROUND OF THE INVENTION

Existing data acquisition systems for computers are very limited in their areas of application. Generally such systems can be classified into two groups.

In the first group host devices or computer systems are attached by means of an interface to a device whose data is to be acquired. The interfaces of this group are normally standard interfaces which, with specific driver software, can be used with a variety of host systems. An advantage of such interfaces is that they are largely independent of the host device. However, a disadvantage is that they generally require very sophisticated drivers which are prone to malfunction and which limit data transfer rates between the device connected to the interface and the host device and vice versa. Further, it is often very difficult to implement such interfaces for portable systems and they offer few possibilities for adaptation with the result that such systems offer little flexibility.

The devices from which data is to be acquired cover the entire electrical engineering spectrum. In a typical case, it is assumed that a customer who operates, for example, a diagnostic radiology system in a medical engineering environment reports a fault. A field service technician of the system manufacturer visits the customer and reads system log files generated by the diagnostic radiology system by means a portable computer or laptop for example. If the fault cannot be localized or if the fault is intermittent, it will be necessary for the service technician to read not only an error log file but also data from current operation. It is apparent that in this case fast data transfer and rapid data analysis are necessary.

Another case requiring the use of an interface could be, for example, when an electronic measuring device, e.g. a multimeter, is attached to a computer system to transfer the data measured by the multimeter to the computer. Particularly when long-term measurements or large volumes of data are involved is it necessary for the interface to support a high data transfer rate.

From these randomly chosen examples it can be seen that an interface may be put to totally different uses. It is therefore desirable that an interface be sufficiently flexible to permit attachment of very different electrical or electronic systems to a host device by means of the interface. To prevent operator error, it is also desirable that a service technician is not required to operate different interfaces in different ways for different applications but that, if possible, a universal method of operating the interface be provided for a large number of applications.

To increase the data transfer rates across an interface, the route chosen in the second group of data acquisition systems for the interface devices was to specifically match the

2

interface very closely to individual host systems or computer systems. The advantage of this solution is that high data transfer rates are possible. However, a disadvantage is that the drivers for the interfaces of the second group are very closely matched to a single host system with the result that they generally cannot be used with other host systems or their use is very ineffective. Further, such types of interface have the disadvantage that they must be installed inside the computer casing to achieve maximum data transfer rates as they access the internal host bus system. They are therefore generally not suitable for portable host systems in the form of laptops whose minimum possible size leaves little internal space to plug in an interface card.

DESCRIPTION OF PRIOR ART

A solution to this problem is offered by the interface devices of IOtech (business address: 25971 Cannon Road, Cleveland, Ohio 44146, USA) which are suitable for laptops such as the WaveBook/512 (registered trademark). The interface devices are connected by means of a plug-in card, approximately the size of a credit card, to the PCMCIA interface which is now a standard feature in laptops. The plug-in card converts the PCMCIA interface into an interface known in the art as IEEE 1284. The said plug-in card provides a special printer interface which is enhanced as regards the data transfer rate and delivers a data transfer rate of approximately 2 MBps as compared with a rate of approx. 1 MBps for known printer interfaces. The known interface device generally consists of a driver component, a digital signal processor, a buffer and a hardware module which terminates in a connector to which the device whose data is to be acquired is attached. The driver component is attached directly to the enhanced printer interface thus permitting the known interface device to establish a connection between a computer and the device whose data is to be acquired.

In order to work with the said interface, an interface-specific driver must be installed on the host device so that the host device can communicate with the digital signal processor of the interface card. As described above, the driver must be installed on the host device. If the driver is a driver developed specifically for the host device, a high data transfer rate is achieved but the driver cannot be easily installed on a different host system. However, if the driver is a general driver which is as flexible as possible and which can be used on many host devices, compromises must be accepted with regard to the data transfer rate.

Particularly in an application for multi-tasking systems in which several different tasks such as data acquisition, data display and editing are to be performed quasi-simultaneously, each task is normally assigned a certain priority by the host system. A driver supporting a special task requests the central processing system of the host device for processor resources in order to perform its task. Depending on the particular priority assignment method and on the driver implementation, a particular share of processor resources is assigned to a special task in particular time slots. Conflicts arise if one or more drivers are implemented in such a way that they have the highest priority by default, i.e. they are incompatible, as happens in practice in many applications. It may occur that both drivers are set to highest priority which, in the worst case, can result in a system crash.

EP 0685799 A1 discloses an interface by means of which several peripheral devices can be attached to a bus. An interface is connected between the bus of a host device and various peripheral devices. The interface comprises a finite

US 6,470,399 B1

3

state machine and several branches each of which is assigned to a peripheral device. Each branch comprises a data manager, cycle control, user logic and a buffer. This known interface device provides optimal matching between a host device and a specific peripheral device.

The specialist publication IBM Technical Disclosure Bulletin, Vol. 38, No. 05, page 245; "Communication Method between Devices through FDD Interface" discloses an interface which connects a host device to a peripheral device via a floppy disk drive interface. The interface consists in particular of an address generator, an MFM encoder/decoder, a serial/parallel adapter and a format signal generator. The interface makes it possible to attach not only a floppy disk drive but also a further peripheral device to the FDD host controller of a host device. The host device assumes that a floppy disk drive is always attached to its floppy disk drive controller and communication is initiated if the address is correct. However, this document contains no information as to how communication should be possible if the interface is connected to a multi-purpose interface instead of to a floppy disk drive controller.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an interface device for communication between a host device and a data transmit/receive device whose use is host device-independent and which delivers a high data transfer rate.

In accordance with a first aspect of the present invention, this object is met by an interface device for communication between a host device, which comprises drivers for input/output devices customary in a host device and a multi-purpose interface, and a data transmit/receive device comprising: a processor; a memory; a first connecting device for interfacing the host device with the interface device via the multi-purpose interface of the host device; and a second connecting device for interfacing the interface device with the data transmit/receive device, wherein the interface device is configured by the processor and the memory in such a way that the interface device, when receiving an inquiry from the host device as to the type of a device attached to the multi-purpose interface of the host device, sends a signal, regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, to the host device which signals to the host device that it is an input/output device customary in a host device, whereupon the host device communicates with the interface device by means of the driver for the input/output device customary in a host device.

In accordance with a second aspect of the present invention, this object is met by an interface device for communication between a host device, which comprises a multi-purpose interface and a specific driver for this interface, and a data transmit/receive device comprising: a processor; a memory; a first connecting device for interfacing the host device with the interface device via the multi-purpose interface of the host device; and a second connecting device for interfacing the interface device with the data transmit/receive device, wherein the interface device is configured using the processor and the memory in such a way that the interface device, when receiving an inquiry from the host device as to the type of a device attached at the multi-purpose interface of the host device, sends a signal, regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, to the host device which signals to the host device that it is an input/output device customary in a host device,

4

whereupon the host device communicates with the interface device by means of the specific driver for the multi-purpose interface.

In accordance with a third aspect of the present invention, this object is met by a method of communication between a host device, which comprises drivers for input/output devices customary in a host device and a multi-purpose interface, and a data transmit/receive device via an interface device comprising the steps of interfacing of the host device with a first connecting device of the interface device via the multi-purpose interface of the host device; interfacing of the data transmit/receive device with a second connecting device of the interface device; inquiring by the host device at the interface device as to the type of device to which the multi-purpose interface of the host device is attached; regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, responding to the inquiry from the host device by the interface device in such a way that it is an input/output device customary in a host device, whereupon the host device communicates with the interface device by means of the usual driver for the input/output device.

The present invention is based on the finding that both a high data transfer rate and host device-independent use can be achieved if a driver for an input/output device customary in a host device, normally present in most commercially available host devices, is utilized. Drivers for input/output devices customary in a host device which are found in practically all host devices are, for example, drivers for hard disks, for graphics devices or for printer devices. As however the hard disk interfaces in common host devices which can be, for example, IBM PCs, IBM-compatible PCs, Commodore PCs, Apple computers or even workstations, are the interfaces with the highest data transfer rate, the hard disk driver is utilized in the preferred embodiment of the interface device of the present invention. Drivers for other storage devices such as floppy disk drives, CD-ROM drives or tape drives could also be utilized in order to implement the interface device according to the present invention.

As described in the following, the interface device according to the present invention is to be attached to a host device by means of a multi-purpose interface of the host device which can be implemented, for example, as an SCSI interface or as an enhanced printer interface. Multi-purpose interfaces comprise both an interface card and specific driver software for the interface card. The driver software can be designed so that it can replace the BIOS driver routines. Communication between the host device and the devices attached to the multi-purpose interface then essentially takes place by means of the specific driver software for the multi-purpose interface and no longer primarily by means of BIOS routines of the host device. Recently however drivers for multi-purpose interfaces can also already be integrated in the BIOS system of the host device as, alongside classical input/output interfaces, multi-purpose interfaces are becoming increasingly common in host devices. It is of course also possible to use BIOS routines in parallel with the specific driver software for the multi-purpose interface, if this is desired.

The interface device according to the present invention comprises a processor means, a memory means, a first connecting device for interfacing the host device with the interface device, and a second connecting device for interfacing the interface device with the data transmit/receive device. The interface device is configured by the processor means and the memory means in such a way that the interface device, when receiving an inquiry from the host

US 6,470,399 B1

5

device via the first connecting device as to the type of a device attached to the host device, sends a signal, regardless of the type of the data transmit/receive device, to the host device via the first connecting device which signals to the host device that it is communicating with an input/output device. The interface device according to the present invention therefore simulates, both in terms of hardware and software, the way in which a conventional input/output device functions, preferably that of a hard disk drive. As support for hard disks is implemented as standard in all commercially available host systems, the simulation of a hard disk, for example, can provide host device-independent use. The interface device according to the present invention therefore no longer communicates with the host device or computer by means of a specially designed driver but by means of a program which is present in the BIOS system (Basic Input/Output System) and is normally precisely matched to the specific computer system on which it is installed, or by means of a specific program for the multi-purpose interface. Consequently, the interface device according to the present invention combines the advantages of both groups. On the one hand, communication between the computer and the interface takes place by means of a host device-specific BIOS program or by means of a driver program which is matched to the multi-purpose interface and which could be regarded as a "device-specific driver". On the other hand, the BIOS program or a corresponding multi-purpose interface program which operates one of the common input/output interfaces in host systems is therefore present in all host systems so that the interface device according to the present invention is host device-independent.

BRIEF DESCRIPTION OF THE DRAWINGS

In the following, preferred embodiments of the present invention will be explained in more detail with reference to the drawings enclosed, in which:

FIG. 1 shows a general block diagram of the interface device according to the present invention; and

FIG. 2 shows detailed block diagram of an interface device according to a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

FIG. 1 shows a general block diagram of an interface device 10 according to the present invention. A first connecting device 12 of the interface device 10 can be attached to a host device (not shown) via a host line 11. The first connecting device is attached both to a digital signal processor 13 and to a memory means 14. The digital signal processor 13 and the memory means 14 are also attached to a second connecting device 15 by means of bidirectional communication lines (shown for all lines by means of two directional arrows). The second connecting device can be attached by means of an output line 16 to a data transmit/receive device which is to receive data from the host device or from which data is to be read, i.e. acquired, and transferred to the host device. The data transmit/receive device itself can also communicate actively with the host device via the first and second connecting device, as described in more detail in the following.

Communication between the host system or host device and the interface device is based on known standard access commands as supported by all known operating systems (e.g. DOS, Windows, Unix). Preferably, the interface device

6

according to the present invention simulates a hard disk with a root directory whose entries are "virtual" files which can be created for the most varied functions. When the host device system with which the interface device according to the present invention is connected is booted and a data transmit/receive device is also attached to the interface device 10, usual BIOS routines or multi-purpose interface programs issue an instruction, known by those skilled in the art as the INQUIRY instruction, to the input/output interfaces in the host device. The digital signal processor 13 receives this inquiry instruction via the first connecting device and generates a signal which is sent to the host device (not shown) again via the first connecting device 12 and the host line 11. This signal indicates to the host device that, for example, a hard disk drive is attached at the interface to which the INQUIRY instruction was sent. Optionally, the host device can send an instruction, known by those skilled in the art as "Test Unit Ready", to the interface device to request more precise details regarding the queried device.

Regardless of which data transmit/receive device at the output line 16 is attached to the second connecting device, the digital signal processor 13 informs the host device that it is communicating with a hard disk drive. If the host device receives the response that a drive is present, it then sends a request to the interface device 10 to read the boot sequence which, on actual hard disks, normally resides on the first sectors of the disk. The digital signal processor 13, whose operating system is stored in the memory means 14, responds to this instruction by sending to the host device a virtual boot sequence which, in the case of actual drives, includes the drive type, the starting position and the length of the file allocation table (FAT), the number of sectors, etc., known to those skilled in the art. Once the host device has received this data, it assumes that the interface device 10 according to a preferred embodiment of the present invention is a hard disk drive. In reply to an instruction from the host device to display the directory of the "virtual" hard disk drive simulated by the interface device 10 with respect to the host device, the digital signal processor can respond to the host device in exactly the same way as a conventional hard disk would, namely by reading on request the file allocation table or FAT on a sector specified in the boot sequence, normally the first writable sector, and transferring it to the host device, and subsequently by transferring the directory structure of the virtual hard disk. Further, it is possible that the FAT is not read until immediately prior to reading or storing the data of the "virtual" hard disk and not already at initialization.

In a preferred embodiment of the present invention, the digital signal processor 13, which need not necessarily be implemented as a digital signal processor but may be any other kind of microprocessor, comprises a first and a second command interpreter. The first command interpreter carries out the steps described above whilst the second command interpreter carries out the read/write assignment to specific functions. If the user now wishes to read data from the data transmit/receive device via the line 16, the host device sends a command, for example "read file xy", to the interface device. As described above, the interface device appears to the host device as a hard disk. The second command interpreter of the digital signal processor now interprets the read command of the host processor as a data transfer command, by decoding whether "xy" denotes, for example, a "real-time input" file, a "configuration" file or an executable file, whereby the same begins to transfer data from the data transmit/receive device via the second connecting device to the first connecting device and via the line 11 to the host device.

US 6,470,399 B1

7

Preferably, the volume of data to be acquired by a data transmit/receive device is specified in a configuration file described in the following by the user specifying in the said configuration file that a measurement is to last, for example, five minutes. To the host device the "real-time input" file then appears as a file whose length corresponds to the anticipated volume of data in those five minutes. Those skilled in the art know that communication between a processor and a hard disk consists of the processor transferring to the hard disk the numbers of the blocks or clusters or sectors whose contents it wishes to read. By reference to the FAT the processor knows which information is contained in which block. In this case, communication between the host device and the interface device according to the present invention therefore consists of the very fast transfer of block numbers and preferably of block number ranges because a virtual "real-time input" file will not be fragmented. If the host device now wants to read the "real-time input" file, it transfers a range of block numbers to the interface device, whereupon data commences to be received via the second connecting device and data commences to be sent to the host device via the first connecting device.

In addition to the digital signal processor instruction memory, which comprises the operating system of the digital signal processor and can be implemented as an EPROM or EEPROM, the memory means 14 can have an additional buffer for purposes of synchronizing data transfer from the data transmit/receive device to the interface device 10 and data transfer from the interface device 10 to the host device.

Preferably, the buffer is implemented as a fast random access memory or RAM buffer.

Further, from the host device the user can also create a configuration file, whose entries automatically set and control various functions of the interface device 10, on the interface device 10 which appears to the host device as a hard disk. These settings can be, for example, gain, multiplex or sampling rate settings. By creating and editing a configuration file, normally a text file which is simple to understand with little prior knowledge, users of the interface device 10 are able to perform essentially identical operator actions for almost any data transmit/receive devices which can be attached to the second connecting device via the line 16, thus eliminating a source of error arising from users having to know many different command codes for different applications. In the case of the interface device 10 according to the present invention it is necessary for users to note the conventions of the configuration file once only in order to be able to use the interface device 10 as an interface between a host device and almost any data transmit/receive device.

As a result of the option of storing any files in agreed formats in the memory means 14 of the interface device 10, taking into account the maximum capacity of the memory means, any enhancements or even completely new functions of the interface device 10 can be quickly implemented. Even files executable by the host device, such as batch files or executable files (BAT or EXE files), and also help files can be implemented in the interface device, thus achieving independence of the interface device 10 from any additional software (with the exception of the BIOS routines) of the host device. On the one hand, this avoids licensing and/or registration problems and, on the other hand, installation of certain routines which can be frequently used, for example an FFT routine to examine acquired time-domain data in the frequency domain, is rendered unnecessary as the EXE files are already installed on the interface device 10 and appear in the virtual root directory, by means of which the host device can access all programs stored on the interface device 10.

8

In a preferred embodiment of the present invention in which the interface device 10 simulates a hard disk to the host device, the interface device is automatically detected and readied for operation when the host system is powered up or booted. This corresponds to the plug-and-play standard which is currently finding increasingly widespread use. The user is no longer responsible for installing the interface device 10 on the host device by means of specific drivers which must also be loaded; instead the interface device 10 is automatically readied for operation when the host system is booted.

For persons skilled in the art it is however obvious that the interface device 10 is not necessarily signed on when the computer system is powered up but that a special BIOS routine or a driver for a multi-purpose interface can also be started on the host device during current operation of the computer system in order to sign on or mount the interface device 10 as an additional hard disk. This embodiment is suitable for larger workstation systems which are essentially never powered down as they perform, e.g. mail functions or monitor processes which run continuously, for example, in multi-tasking environments.

In the interface device according to the present invention an enormous advantage is to be gained, as apparent in the embodiment described in the following, in separating the actual hardware required to attach the interface device 10 to the data transmit/receive device from the communication unit, which is implemented by the digital signal processor 13, the memory means 14 and the first connecting device 12, as this allows a plurality of dissimilar device types to be operated in parallel in identical manner. Accordingly, many interface devices 10 can be connected to a host device which then sees many different "virtual" hard disks. In addition, any modification of the specific hardware symbolized by the second connecting device 15 can be implemented essentially without changing the operation of the interface device according to the present invention. Further, an experienced user can intervene at any time on any level of the existing second connecting device by making use of the above mentioned option of creating a configuration file or adding or storing new program sections for the second connecting device.

An important advantage of the interface device 10 of the present invention is that it also permits extremely high data transfer rates by using, for data interchange, the host device's own BIOS routines which are optimized for each host device by the host device manufacturer or BIOS system manufacturer, or by using driver programs which are normally optimized and included by the manufacturers of multi-purpose interfaces. Furthermore, due to the simulation of a virtual mass storage device, the data is managed and made available in such a way that it can be transferred directly to other storage media, e.g. to an actual hard disk of the host device without, as it were, intervention of the host device processor. The only limitation to long-term data transfer at high speed is therefore imposed exclusively by the speed and the size of the mass storage device of the host device. This is the case as the digital signal processor 13 already formats the data read by the data transmit/receive device via the second connecting device 15 into block sizes suitable for a hard disk of the host device, whereby the data transfer speed is limited only by the mechanical latency of the hard disk system of the host device. At this point, it should be noted that normally data flow from a host device must be formatted in blocks to permit writing to a hard disk and subsequent reading from a hard disk, as known by those skilled in the art.

US 6,470,399 B1

9

The said data transfer rate can be increased further by setting up a direct memory access (DMA) or RAM drive in the host system. As those skilled in the art know, the setting up of a RAM drive requires processor resources of the host device, with the result that the advantage of writing the data to a hard disk drive of the host device essentially without the need for processor resources is lost.

As described above, a data buffer can be implemented in the memory means 14 to permit independence in terms of time of the data transmit/receive device attached to the second connecting device from the host device attached to the first connecting device. This guarantees error-free operation of the interface device 10 even for time-critical applications in multi-tasking host systems.

FIG. 2 shows a detailed block diagram of an interface device 10 according to the present invention.

A digital signal processor (DSP) 1300 is, in a manner of speaking, the heart of the interface device 10. The DSP can be any DSP but preferably has a 20-MB on-chip random access memory (RAM). Certain instruction sets, for example, can be stored in the RAM already integrated in the DSP. An 80-MHz clock generator is attached to the DSP 1300 in order to synchronize the DSP. The DSP implements a fast Fourier transformation (FFT) in real time and also optional data compression of the data to be transferred from the data transmit/receive device to the host device in order to achieve greater efficiency and to permit interoperation with host devices which have a smaller memory.

In the preferred embodiment of the interface device 10 shown in FIG. 2, the first connecting device 12 of FIG. 1 contains the following components: an SCSI interface 1220 and a 50-pin SCSI connector 1240 for attachment to an SCSI interface present on most host devices or laptops. The SCSI (small computer system interface) interface 1220 translates the data received via the SCSI connector 1240 into data understood by the DSP 1300, as known by those skilled in the art. Further, the first connecting device 12 comprises an EPP (enhanced parallel port) with a data transfer rate of approx. 1 MBps which delivers a more moderate data transfer rate of 1 MBps by comparison to the data transfer rate of 10 MBps of the SCSI interface. The EPP 1260 is connected to a 25-pin D-shell connector 1280 to permit attachment to a printer interface of a host device for example. Optionally, the first connecting device 12 also comprises a 25-pin connector 1282 which permits the attachment of 8 digital outputs and 8 digital inputs 1284 at a host device.

Preferably, the second connecting device comprises 8 BNC inputs with the calibration relay 1505, a block 1510 with 8 device amplifiers with an overvoltage protection of ± 75 V, this block being connected in turn to 8 sample/hold (S&H) circuits 1515. The calibration relays are relays which permit controlled changeover between a test voltage and a calibration reference voltage. Each sample/hold circuit is connected to a corresponding input of an 8-channel multiplexer 1520 which feeds its output signals via a programmable amplifier 1525 into an analog/digital converter (ADC) with 12 bit and 1.25 MHz 1530 and to the DSP 1300. The ADC 1530 is controlled by means of a 20-bit timer 1535, as known by persons skilled in the art. The programmable amplifier 1525 and the 8-channel multiplexer 1520 are controlled via an amplifier channel selection circuit 1540 which is in turn controlled by the DSP 1300.

The complete interface device 10 is supplied with power by an external AC/DC converter 1800 which delivers a digital supply voltage of ± 5 V and is attached to a DC/DC

10

converter 1810 which can deliver analog supply voltages of ± 5 V and ± 15 V as required for the interface device 10. Further, the DC/DC converter controls a precision voltage reference 1820 which controls the 8 BNC inputs 1505 and the ADC 1530 as well as a digital/analog converter (DAC) 1830 which permits, via an output amplifier block with 4 output amplifiers 1840 and a 9-pin connector 1850, analog output direct from the DSP 1300 to an output device, e.g. printer device or monitor device, which can be attached via the 9-pin connector 1850, thus providing the option of monitoring the data transferred to the host device or also, for example, of viewing an FFT to obtain rapid and comprehensive data analysis without using processor time of the host device.

In FIG. 2 the memory means 14 of FIG. 1 is implemented by an EPROM 1400 which, in a preferred embodiment of the present invention, contains the operating system of the digital signal processor 1300. A random access memory with an access time of 15 ns and a size of 512 KB or optionally 1024 KB 1420 serves as a data buffer to achieve independence in terms of time of the output line 16 from the output lines 11a, 11b and 11c to the data transmit/receive device and to the host device respectively. As described above, in a preferred embodiment of the present invention the digital signal processor 1300 already contains a 20-KB on-chip RAM 1440 which can store certain instruction sets, functions and also smaller application software units.

The connection, symbolized by the line 16, of the interface device 10 to any data transmit/receive device implements, by means of the blocks 1505–1535, an analog input with a sampling rate of 1.25 MHz and quantization of 12 bits. There are 8 channels with an overvoltage protection of ± 75 V. By means of the programmable amplifier 1525 the channels can be programmed independently of each other in voltage ranges up to a maximum of ± 10 V. Unused channels can be grounded internally to reduce channel intermodulation. The block 1515 is implemented as a monolithic high-precision, high-speed sample/hold amplifier for simultaneous sampling of all channels. The precision voltage reference 1820 provides a high-precision, temperature-compensated monolithic energy gap voltage reference for auto-calibration of each channel and each gain. Further, offset fine adjustment for each channel is implemented by the same.

The blocks 1830, 1840 and 1850 implement a direct analog output for the digital signal processor 1300, and the DAC 1830 provides a data transfer rate of 625 kHz and a quantization of 12 bits. The block 1840 comprises 4 channels with a common output latch.

Further, the interface device 10 comprises a digital input/output device implemented by the blocks 1284 and 1282. Here there are 8 digital inputs, 8 digital outputs with a common latch, and the digital port can be attached preferably to a side panel of the interface device 10 so that the port itself can easily be accessed.

The digital signal processor 1300 provides on-board digital data processing. In particular, it is a high-performance DSP with a clock speed of 80 MHz and a 20-bit timer 1535.

As described above, the first connecting device 12 comprises the SCSI interface 1220 with a peak transfer rate of 10 MBps. An optional PCMCIA-to-SCSI adapter permits high-speed communication with laptop computers which are desirable and in widespread use, particularly by mobile service technicians. The EPP 1260 with its associated connector 1280 permits data transfer at a more moderate rate.

As described above, the interface device 10 is supplied with power by means of an external AC/DC adapter which

US 6,470,399 B1

11

has a universal power input (85–264 VAC, 47–63 Hz). Interference suppression complies with the standards EN 55022, curve B and FFC, Class B). Further, it is also in accordance with international safety regulations (TÜV, UL, CSA). The interface device 10 is externally shielded and achieves a value of 55 dB at 30–60 MHz and a value of approximately 40 dB at 1 GHz, and therefore complies with the MILSTD 285-1 standard.

As described above, communication between the host device and the multi-purpose interface can take place not only via drivers for input/output device customary in a host device which reside in the BIOS system of the host device but also via specific interface drivers which, in the case of SCSI interfaces, are known as multi-purpose interface ASPI (advanced SCSI programming interface) drivers. This ASPI driver, which can also be referred to as an ASPI manager, is specific to a special SCSI host adapter, i.e. to a special multi-purpose interface, and is normally included by the manufacturer of the multi-purpose interface. Generally speaking, this multi-purpose interface driver has the task of moving precisely specified SCSI commands from the host system program to the host system SCSI adapter. For this reason, the command set is almost identical to that of the SCSI interface itself. Essentially, only status and reset commands for the host adapter have been added.

The ASPI driver can be used if the hard disk was not already addressable at boot time or if the SCSI-related BIOS routines of the host computer were still disabled. Here too, the steps needed to initialize the interface device, preferably as a virtual hard disk, are similar to the steps taken when initializing at boot time.

In general terms, the ASPI manager comprises two sides. One side is the proprietary, hardware-oriented side. It is responsible for converting all commands into a form required by the corresponding multi-purpose interface. The hardware-oriented side of the ASPI driver is therefore matched to a very specific type of multi-purpose interface or SCSI interface. The other side is known as the user software side. This side is totally independent of the proprietary operating characteristics of the SCSI adapter and is therefore identical for all SCSI interfaces. This permits SCSI programming which is however independent of the individual SCSI adapter types.

In contrast to communication between the host device and the interface device according to the present invention on the basis of a BIOS driver, the use of such an ASPI driver for communication between the host device and the interface device according to the present invention allows various further possibilities of the SCSI multi-purpose interface to be exploited. In the case described above, the interface device which preferably signs on and behaves as a virtual hard disk is detected by the BIOS driver of the host computer at boot time and is configured as a hard disk. This step does not however support active requests sent by the interface device to the host computer. If however the virtual hard disk wishes to write data actively to, for example, a hard disk of the host computer or wishes to initiate communication with the processor of the host computer, the host computer must recognize the request of the virtual hard disk and tolerate a further issuer of instructions on its bus. If the interface device behaves solely like a virtual hard disk, it would always receive and never issue commands. The BIOS has no objections to an additional issuer of commands that actively wishes to place data on the bus of the host device but the BIOS does not support the host device in recognizing corresponding requests of the interface device or in granting the interface device permission to access the bus.

Using the ASPI manager the interface device according to the present invention can now obtain active access to an

12

SCSI hard disk of the host device connected to the same SCSI bus which, in contrast to the interface device, cannot be a virtual but a real SCSI mass storage device or also a further interface device according to the present invention. Thereupon, the interface device according to the present invention can write the desired data to the SCSI hard disk of the host computer totally independently of the host computer or can communicate with the same in some other manner. The interface device according to the present invention therefore initially behaves passively as a virtual hard disk and then, as required and using the driver software for the multi-purpose interface, actively on the same SCSI bus. This means however that the interface device according to the present invention, using a driver software for the multi-purpose interface which comprises the BIOS routines customary in host devices and simultaneously provides the option of active participation, can, regardless of the type of the data transmit/receive device attached to the second connecting device, behave initially as a virtual and at the same time passive hard disk but can, as required, participate actively on the bus so as to be able to initiate communication directly with other SCSI hard disks of the host device by bypassing the processor of the host device.

Using a standard interface of a host device, the interface device according to the present invention permits communication with any host device. By simulating an input/output device to the host device and, in a preferred embodiment, by simulating a virtual mass storage device, the interface device 10 is automatically supported by all known host systems without any additional sophisticated driver software. The simulation of a freely definable file structure on the "virtual" hard disk provides simple operation and expansion options and, through the implementation of any programs, independence from special software implemented on the host device. Help files included on the interface device 10 and plug-and-play support ensure ease of use even in portable, flexible host devices. Despite the very simple user interface, experienced users are free at any time to intervene in the functions of the interface device 10 on system level. The interface device 10 thus provides a universal solution which can cover the entire spectrum of possible data transmit/receive devices.

What is claimed is:

1. An interface device for communication between a host device, which comprises drivers for input/output devices customary in a host device and a multi-purpose interface, and a data transmit/receive device, the data transmit/receive device being arranged for providing analog data, comprising:

- a processor;
- a memory;
- a first connecting device for interfacing the host device with the interface device via the multi-purpose interface of the host device; and
- a second connecting device for interfacing the interface device with the data transmit/receive device, the second connecting device including a sampling circuit for sampling the analog data provided by the data transmit/receive device and an analog-to-digital converter for converting data sampled by the sampling circuit into digital data,

wherein the interface device is configured by the processor and the memory to include a first command interpreter and a second command interpreter,

wherein the first command interpreter is configured in such a way that the command interpreter, when receiving an inquiry from the host device as to a type of a device attached to the multi-purpose interface of the

US 6,470,399 B1

13

host device, sends a signal, regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, to the host device which signals to the host device that it is an input/output device customary in a host device, whereupon the host device communicates with the interface device by means of the driver for the input/output device customary in a host device, and

wherein the second command interpreter is configured to interpret a data request command from the host device to the type of input/output device signaled by the first command interpreter as a data transfer command for initiating a transfer of the digital data to the host device.

2. An interface device according to claim 1, wherein the drivers for input/output drivers customary in a host device comprise a hard disk driver, and the signal indicates to the host device that the host device is communicating with a hard disk.

3. An interface device according to claim 1, wherein the memory means comprises a buffer to buffer data to be transferred between the data transmit/receive device and the host device.

4. An interface device according to claim 1, wherein the multi-purpose interface of the host device is an SCSI interface and the first connecting device also comprises an SCSI interface.

5. An interface device according to claim 1, wherein the processor is a digital signal processor.

6. An interface device according to claim 2, wherein the data to be transferred from the data transmit/receive device to the host device in the interface device is formatted in a suitable format for a hard disk present in the host device.

7. An interface device according to claim 2, which further comprises a root directory and virtual files which are present on the signaled hard disk drive and which can be accessed from the host device.

8. An interface device according to claim 7, wherein the virtual files comprise a configuration file in text format which are stored in the memory means and using which the user can configure the interface device for a specific data transmit/receive device.

9. An interface device according to claim 7, wherein the virtual files comprise batch files or executable files for the microprocessor means which are stored in the interface device in order to perform data processing, independently of the host device, of data received via the second connecting device.

10. An interface device according to claim 7, wherein the virtual files comprise batch files or executable files for the host device which are stored in the interface device.

11. An interface device for communication between a host device, which comprises a multi-purpose interface and a specific driver for this interface, and a data transmit/receive device, the data transmit/receive device being arranged for providing analog data, comprising:

- a processor;
- a memory;
- a first connecting device for interfacing the host device with the interface device via the multi-purpose interface of the host device; and
- a second connecting device for interfacing the interface device with the data transmit/receive device, the second connecting device including a sampling circuit for sampling the analog data provided by the data transmit/receive device and an analog-to-digital converter for converting data sampled by the sampling circuit into digital data,

14

where the interface device is configured using the processor and the memory to include a first command interpreter and a second command interpreter,

wherein the first command interpreter is configured in such a way that the interface device, when receiving an inquiry from the host device as to the type of a device attached at the multi-purpose interface of the host device, sends a signal, regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, to the host device which signals to the host device that it is an input/output device customary in a host device, whereupon the host device communicates with the interface device by means of the specific driver for the multi-purpose interface, and

wherein the second command interpreter is configured to interpret a data request command from the host device to the type of input/output device signaled by the first command interpreter as a data transfer command for initiating a transfer of the digital data to the host device.

12. An interface device according to claim 11, wherein in addition to the first connecting device of the interface device, there is a further input/output device at the multi-purpose interface of the host device, and wherein the interface device can communicate directly with said further input/output device via the specific driver for the multi-purpose interface.

13. An interface device according to claim 11, wherein the multi-purpose interface is an SCSI interface, and wherein the specific driver for the multi-purpose interface is an ASPI manager.

14. A method of communication between a host device, which comprises drivers for input/output devices customary in a host device and a multi-purpose interface, and a data transmit/receive device, the data transmit/receive device being arranged for providing analog data, via an interface device, comprising:

- interfacing of the host device with a first connecting device of the interface device via the multi-purpose interface of the host device;
- interfacing of the data transmit/receive device with a second connecting device of the interface device, the second connecting device including a sampling circuit for sampling the analog data provided by the data transmit/receive device and an analog-to-digital converter for converting data sampled by the sampling circuit into digital data;
- inquiring by the host device at the interface device as to the type of device to which the multi-purpose interface of the host device is attached;
- regardless of the type of the data transmit/receive data attached to the second connecting device of the interface device, responding to the inquiry from the host device by the interface device in such a way that it is an input/output device customary in a host device, whereupon the host device communicates with the interface device by means of the usual driver for the input/output device, and
- interpreting a data request command from the host device to the type of input/output device customary in the host device as a data transfer command for initiating a transfer of the digital data to the host device.

15. A method according to claim 14, wherein the drivers for input/output devices customary in a host device comprise a driver for a storage device and in particular for a hard disk drive.

* * * * *



US006895449B2

(12) **United States Patent**
Tasler

(10) **Patent No.:** **US 6,895,449 B2**
(45) **Date of Patent:** **May 17, 2005**

(54) **FLEXIBLE INTERFACE FOR COMMUNICATION BETWEEN A HOST AND AN ANALOG I/O DEVICE CONNECTED TO THE INTERFACE REGARDLESS THE TYPE OF THE I/O DEVICE**

(75) Inventor: **Michael Tasler, Wuerzburg (DE)**

(73) Assignee: **Labortechnik Tasler GmbH, Wuerzburg (DE)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 369 days.

(21) Appl. No.: **10/219,105**

(22) Filed: **Aug. 15, 2002**

(65) **Prior Publication Data**

US 2002/0199037 A1 Dec. 26, 2002

Related U.S. Application Data

(62) Division of application No. 09/331,002, filed on Jun. 14, 1999.

(30) Foreign Application Priority Data

Mar. 4, 1997 (DE) 197 08 755
Mar. 3, 1998 (EP) PCT/EP98/01187

(51) Int. Cl.⁷ **G06F 13/14**

(52) U.S. Cl. **710/16; 710/8; 710/64; 709/220**

(58) Field of Search 710/8, 16, 64, 710/11, 12, 15, 62, 63; 703/23, 24, 25; 709/220, 222

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,548,783 A * 8/1996 Jones et al. 710/16
5,596,628 A * 1/1997 Klein 379/93.11
5,628,030 A * 5/1997 Tuckner 710/64
6,012,113 A * 1/2000 Tuckner 710/64
6,266,711 B1 * 7/2001 Ishikawa et al. 710/8
6,363,081 B1 * 3/2002 Gase 370/466
6,725,293 B1 * 4/2004 Nakayama et al. 710/36
6,728,844 B2 * 4/2004 Sanada et al. 711/152

* cited by examiner

Primary Examiner—Jeffrey Gaffin


Assistant Examiner—Harold Kim

(74) *Attorney, Agent, or Firm*—Glenn Patent Group; Michael A. Glenn

(57) **ABSTRACT**

An interface device (10) provides fast data communication between a host device with input/output interfaces and a data transmit/receive device, wherein the interface device (10) comprises a processor means (13), a memory means (14), a first connecting device (12) for interfacing the host device with the interface device, and a second connecting device (15) for interfacing the interface device (10) with the data transmit/receive device. The interface device (10) is configured by the processor means (13) and the memory means (14) in such a way that, when receiving an inquiry from the host device via the first connecting device (12) as to the type of a device attached to the host device, regardless of the type of the data transmit/receive device, the interface device sends a signal to the host device via the first connecting device (12) which signals to the host device that it is communicating with an input/output device.

18 Claims, 2 Drawing Sheets



U.S. Patent

May 17, 2005

Sheet 1 of 2

US 6,895,449 B2




FIG. 1

U.S. Patent

May 17, 2005

Sheet 2 of 2

US 6,895,449 B2




FIG.2

US 6,895,449 B2

1

**FLEXIBLE INTERFACE FOR
COMMUNICATION BETWEEN A HOST AND
AN ANALOG I/O DEVICE CONNECTED TO
THE INTERFACE REGARDLESS THE TYPE
OF THE I/O DEVICE**

RELATED APPLICATIONS

This application is a divisional application of copending application Ser. No. 09/331,002 filed Jun. 14, 1999.

DESCRIPTION

The present invention relates to the transfer of data and in particular to interface devices for communication between a computer or host device and a data transmit/receive device from which data is to be acquired or with which two-way communication is to take place.

Existing data acquisition systems for computers are very limited in their areas of application. Generally such systems can be classified into two groups.

In the first group host devices or computer systems are attached by means of an interface to a device whose data is to be acquired. The interfaces of this group are normally standard interfaces which, with specific driver software, can be used with a variety of host systems. An advantage of such interfaces is that they are largely independent of the host device. However, a disadvantage is that they generally require very sophisticated drivers which are prone to malfunction and which limit data transfer rates between the device connected to the interface and the host device and vice versa. Further, it is often very difficult to implement such interfaces for portable systems and they offer few possibilities for adaptation with the result that such systems offer little flexibility.

The devices from which data is to be acquired cover the entire electrical engineering spectrum. In a typical case, it is assumed that a customer who operates, for example, a diagnostic radiology system in a medical engineering environment reports a fault. A field service technician of the system manufacturer visits the customer and reads system log files generated by the diagnostic radiology system by means a portable computer or laptop for example. If the fault cannot be localized or if the fault is intermittent, it will be necessary for the service technician to read not only an error log file but also data from current operation. It is apparent that in this case fast data transfer and rapid data analysis are necessary.

Another case requiring the use of an interface could be, for example, when an electronic measuring device, e.g. a multimeter, is attached to a computer system to transfer the data measured by the multimeter to the computer. Particularly when long-term measurements or large volumes of data are involved it is necessary for the interface to support a high data transfer rate.

From these randomly chosen examples it can be seen that an interface may be put to totally different uses. It is therefore desirable that an interface be sufficiently flexible to permit attachment of very different electrical or electronic systems to a host device by means of the interface. To prevent operator error, it is also desirable that a service technician is not required to operate different interfaces in different ways for different applications but that, if possible, a universal method of operating the interface be provided for a large number of applications.

To increase the data transfer rates across an interface, the route chosen in the second group of data acquisition systems

2

for the interface devices was to specifically match the interface very closely to individual host systems or computer systems. The advantage of this solution is that high data transfer rates are possible. However, a disadvantage is that the drivers for the interfaces of the second group are very closely matched to a single host system with the result that they generally cannot be used with other host systems or their use is very ineffective. Further, such types of interface have the disadvantage that they must be installed inside the computer casing to achieve maximum data transfer rates as they access the internal host bus system. They are therefore generally not suitable for portable host systems in the form of laptops whose minimum possible size leaves little internal space to plug in an interface card.

A solution to this problem is offered by the interface devices of IOTech (business address: 25971 Cannon Road, Cleveland, Ohio 44146, USA) which are suitable for laptops such as the WaveBook/512 (registered trademark). The interface devices are connected by means of a plug-in card, approximately the size of a credit card, to the PCMCIA interface which is now a standard feature in laptops. The plug-in card converts the PCMCIA interface into an interface known in the art as IEEE 1284. The said plug-in card provides a special printer interface which is enhanced as regards the data transfer rate and delivers a data transfer rate of approximately 2 MBps as compared with a rate of approx. 1 MBps for known printer interfaces. The known interface device generally consists of a driver component, a digital signal processor, a buffer and a hardware module which terminates in a connector to which the device whose data is to be acquired is attached. The driver component is attached directly to the enhanced printer interface thus permitting the known interface device to establish a connection between a computer and the device whose data is to be acquired.

In order to work with the said interface, an interface-specific driver must be installed on the host device so that the host device can communicate with the digital signal processor of the interface card. As described above, the driver must be installed on the host device. If the driver is a driver developed specifically for the host device, a high data transfer rate is achieved but the driver cannot be easily installed on a different host system. However, if the driver is a general driver which is as flexible as possible and which can be used on many host devices, compromises must be accepted with regard to the data transfer rate.

Particularly in an application for multi-tasking systems in which several different tasks such as data acquisition, data display and editing are to be performed quasi-simultaneously, each task is normally assigned a certain priority by the host system. A driver supporting a special task requests the central processing system of the host device for processor resources in order to perform its task. Depending on the particular priority assignment method and on the driver implementation, a particular share of processor resources is assigned to a special task in particular time slots. Conflicts arise if one or more drivers are implemented in such a way that they have the highest priority by default, i.e. they are incompatible, as happens in practice in many applications. It may occur that both drivers are set to highest priority which, in the worst case, can result in a system crash.

EP 0685799 A1 discloses an interface by means of which several peripheral devices can be attached to a bus. An interface is connected between the bus of a host device and various peripheral devices. The interface comprises a finite state machine and several branches each of which is assigned to a peripheral device. Each branch comprises a

US 6,895,449 B2

3

data manager, cycle control, user logic and a buffer. This known interface device provides optimal matching between a host device and a specific peripheral device.

The specialist publication IBM Technical Disclosure Bulletin, Vol. 38, No. 05, page 245; "Communication Method between Devices through FDD Interface" discloses an interface which connects a host device to a peripheral device via a floppy disk drive interface. The interface consists in particular of an address generator, an MFM encoder/decoder, a serial/parallel adapter and a format signal generator. The interface makes it possible to attach not only a floppy disk drive but also a further peripheral device to the FDD host controller of a host device. The host device assumes that a floppy disk drive is always attached to its floppy disk drive controller and communication is initiated if the address is correct. However, this document contains no information as to how communication should be possible if the interface is connected to a multi-purpose interface instead of to a floppy disk drive controller.

It is the object of the present invention to provide an interface device for communication between a host device and a data transmit/receive device whose use is host device-independent and which delivers a high data transfer rate.

This object is achieved by an interface device according to claim 1 or 12 and by a method according to claim 15.

The present invention is based on the finding that both a high data transfer rate and host device-independent use can be achieved if a driver for an input/output device customary in a host device, normally present in most commercially available host devices, is utilized. Drivers for input/output devices customary in a host device which are found in practically all host devices are, for example, drivers for hard disks, for graphics devices or for printer devices. As however the hard disk interfaces in common host devices which can be, for example, IBM PCs, IBM-compatible PCs, Commodore PCs, Apple computers or even workstations, are the interfaces with the highest data transfer rate, the hard disk driver is utilized in the preferred embodiment of the interface device of the present invention. Drivers for other storage devices such as floppy disk drives, CD-ROM drives or tape drives could also be utilized in order to implement the interface device according to the present invention.

As described in the following, the interface device according to the present invention is to be attached to a host device by means of a multi-purpose interface of the host device which can be implemented, for example, as an SCSI interface or as an enhanced printer interface. Multi-purpose interfaces comprise both an interface card and specific driver software for the interface card. The driver software can be designed so that it can replace the BIOS driver routines. Communication between the host device and the devices attached to the multi-purpose interface then essentially takes place by means of the specific driver software for the multi-purpose interface and no longer primarily by means of BIOS routines of the host device. Recently however drivers for multi-purpose interfaces can also already be integrated in the BIOS system of the host device as, alongside classical input/output interfaces, multi-purpose interfaces are becoming increasingly common in host devices. It is of course also possible to use BIOS routines in parallel with the specific driver software for the multi-purpose interface, if this is desired.

The interface device according to the present invention comprises a processor means, a memory means, a first connecting device for interfacing the host device with the interface device, and a second connecting device for inter-

4

facing the interface device with the data transmit/receive device. The interface device is configured by the processor means and the memory means in such a way that the interface device, when receiving an inquiry from the host device via the first connecting device as to the type of a device attached to the host device, sends a signal, regardless of the type of the data transmit/receive device, to the host device via the first connecting device which signals to the host device that it is communicating with an input/output device. The interface device according to the present invention therefore simulates, both in terms of hardware and software, the way in which a conventional input/output device functions, preferably that of a hard disk drive. As support for hard disks is implemented as standard in all commercially available host systems, the simulation of a hard disk, for example, can provide host device-independent use. The interface device according to the present invention therefore no longer communicates with the host device or computer by means of a specially designed driver but by means of a program which is present in the BIOS system (Basic Input/Output System) and is normally precisely matched to the specific computer system on which it is installed, or by means of a specific program for the multi-purpose interface. Consequently, the interface device according to the present invention combines the advantages of both groups. On the one hand, communication between the computer and the interface takes place by means of a host device-specific BIOS program or by means of a driver program which is matched to the multi-purpose interface and which could be regarded as a "device-specific driver". On the other hand, the BIOS program or a corresponding multi-purpose interface program which operates one of the common input/output interfaces in host systems is therefore present in all host systems so that the interface device according to the present invention is host device-independent.

In the following, preferred embodiments of the present invention will be explained in more detail with reference to the drawings enclosed, in which:

FIG. 1 shows a general block diagram of the interface device according to the present invention; and

FIG. 2 shows a detailed block diagram of an interface device according to a preferred embodiment of the present invention.

FIG. 1 shows a general block diagram of an interface device 10 according to the present invention. A first connecting device 12 of the interface device 10 can be attached to a host device (not shown) via a host line 11. The first connecting device is attached both to a digital signal processor 13 and to a memory means 14. The digital signal processor 13 and the memory means 14 are also attached to a second connecting device 15 by means of bi-directional communication lines (shown for all lines by means of two directional arrows). The second connecting device can be attached by means of an output line 16 to a data transmit/receive device which is to receive data from the host device or from which data is to be read, i.e. acquired, and transferred to the host device. The data transmit/receive device itself can also communicate actively with the host device via the first and second connecting device, as described in more detail in the following.

Communication between the host system or host device and the interface device is based on known standard access commands as supported by all known operating systems (e.g. DOS, Windows, Unix). Preferably, the interface device according to the present invention simulates a hard disk with

US 6,895,449 B2

5

a root directory whose entries are "virtual" files which can be created for the most varied functions. When the host device system with which the interface device according to the present invention is connected is booted and a data transmit/receive device is also attached to the interface device **10**, usual BIOS routines or multi-purpose interface programs issue an instruction, known by those skilled in the art as the INQUIRY instruction, to the input/output interfaces in the host device. The digital signal processor **13** receives this inquiry instruction via the first connecting device and generates a signal which is sent to the host device (not shown) again via the first connecting device **12** and the host line **11**. This signal indicates to the host device that, for example, a hard disk drive is attached at the interface to which the INQUIRY instruction was sent. Optionally, the host device can send an instruction, known by those skilled in the art as "Test Unit Ready", to the interface device to request more precise details regarding the queried device.

Regardless of which data transmit/receive device at the output line **16** is attached to the second connecting device, the digital signal processor **13** informs the host device that it is communicating with a hard disk drive. If the host device receives the response that a drive is present, it then sends a request to the interface device **10** to read the boot sequence which, on actual hard disks, normally resides on the first sectors of the disk. The digital signal processor **13**, whose operating system is stored in the memory means **14**, responds to this instruction by sending to the host device a virtual boot sequence which, in the case of actual drives, includes the drive type, the starting position and the length of the file allocation table (FAT), the number of sectors, etc., known to those skilled in the art. Once the host device has received this data, it assumes that the interface device **10** according to a preferred embodiment of the present invention is a hard disk drive. In reply to an instruction from the host device to display the directory of the "virtual" hard disk drive simulated by the interface device **10** with respect to the host device, the digital signal processor can respond to the host device in exactly the same way as a conventional hard disk would, namely by reading on request the file allocation table or FAT on a sector specified in the boot sequence, normally the first writable sector, and transferring it to the host device, and subsequently by transferring the directory structure of the virtual hard disk. Further, it is possible that the FAT is not read until immediately prior to reading or storing the data of the "virtual" hard disk and not already at initialization.

In a preferred embodiment of the present invention, the digital signal processor **13**, which need not necessarily be implemented as a digital signal processor but may be any other kind of microprocessor, comprises a first and a second command interpreter. The first command interpreter carries out the steps described above whilst the second command interpreter carries out the read/write assignment to specific functions. If the user now wishes to read data from the data transmit/receive device via the line **16**, the host device sends a command, for example "read file xy", to the interface device. As described above, the interface device appears to the host device as a hard disk. The second command interpreter of the digital signal processor now interprets the read command of the host processor as a data transfer command, by decoding whether "xy" denotes, for example, a "real-time input" file, a "configuration" file or an executable file, whereby the same begins to transfer data from the data transmit/receive device via the second connecting device to the first connecting device and via the line **11** to the host device.

6

Preferably, the volume of data to be acquired by a data transmit/receive device is specified in a configuration file described in the following by the user specifying in the said configuration file that a measurement is to last, for example, five minutes. To the host device the "real-time input" file then appears as a file whose length corresponds to the anticipated volume of data in those five minutes. Those skilled in the art know that communication between a processor and a hard disk consists of the processor transferring to the hard disk the numbers of the blocks or clusters or sectors whose contents it wishes to read. By reference to the FAT the processor knows which information is contained in which block. In this case, communication between the host device and the interface device according to the present invention therefore consists of the very fast transfer of block numbers and preferably of block number ranges because a virtual "real-time input" file will not be fragmented. If the host device now wants to read the "real-time input" file, it transfers a range of block numbers to the interface device, whereupon data commences to be received via the second connecting device and data commences to be sent to the host device via the first connecting device.

In addition to the digital signal processor instruction memory, which comprises the operating system of the digital signal processor and can be implemented as an EPROM or EEPROM, the memory means **14** can have an additional buffer for purposes of synchronizing data transfer from the data transmit/receive device to the interface device **10** and data transfer from the interface device **10** to the host device.

Preferably, the buffer is implemented as a fast random access memory or RAM buffer.

Further, from the host device the user can also create a configuration file, whose entries automatically set and control various functions of the interface device **10**, on the interface device **10** which appears to the host device as a hard disk. These settings can be, for example, gain, multiplex or sampling rate settings. By creating and editing a configuration file, normally a text file which is simple to understand with little prior knowledge, users of the interface device **10** are able to perform essentially identical operator actions for almost any data transmit/receive devices which can be attached to the second connecting device via the line **16**, thus eliminating a source of error arising from users having to know many different command codes for different applications. In the case of the interface device **10** according to the present invention it is necessary for users to note the conventions of the configuration file once only in order to be able to use the interface device **10** as an interface between a host device and almost any data transmit/receive device.

As a result of the option of storing any files in agreed formats in the memory means **14** of the interface device **10**, taking into account the maximum capacity of the memory means, any enhancements or even completely new functions of the interface device **10** can be quickly implemented. Even files executable by the host device, such as batch files or executable files (BAT or EXE files), and also help files can be implemented in the interface device, thus achieving independence of the interface device **10** from any additional software (with the exception of the BIOS routines) of the host device. On the one hand, this avoids licensing and/or registration problems and, on the other hand, installation of certain routines which can be frequently used, for example an FFT routine to examine acquired time-domain data in the frequency domain, is rendered unnecessary as the EXE files are already installed on the interface device **10** and appear in the virtual root directory, by means of which the host device can access all programs stored on the interface device **10**.

US 6,895,449 B2

7

In a preferred embodiment of the present invention in which the interface device 10 simulates a hard disk to the host device, the interface device is automatically detected and readied for operation when the host system is powered up or booted. This corresponds to the plug-and-play standard which is currently finding increasingly widespread use. The user is no longer responsible for installing the interface device 10 on the host device by means of specific drivers which must also be loaded; instead the interface device 10 is automatically readied for operation when the host system is booted.

For persons skilled in the art it is however obvious that the interface device 10 is not necessarily signed on when the computer system is powered up but that a special BIOS routine or a driver for a multi-purpose interface can also be started on the host device during current operation of the computer system in order to sign on or mount the interface device 10 as an additional hard disk. This embodiment is suitable for larger workstation systems which are essentially never powered down as they perform, e.g. mail functions or monitor processes which run continuously, for example, in multi-tasking environments.

In the interface device according to the present invention an enormous advantage is to be gained, as apparent in the embodiment described in the following, in separating the actual hardware required to attach the interface device 10 to the data transmit/receive device from the communication unit, which is implemented by the digital signal processor 13, the memory means 14 and the first connecting device 12, as this allows a plurality of dissimilar device types to be operated in parallel in identical manner. Accordingly, many interface devices 10 can be connected to a host device which then sees many different "virtual" hard disks. In addition, any modification of the specific hardware symbolized by the second connecting device 15 can be implemented essentially without changing the operation of the interface device according to the present invention. Further, an experienced user can intervene at any time on any level of the existing second connecting device by making use of the above mentioned option of creating a configuration file or adding or storing new program sections for the second connecting device.

An important advantage of the interface device 10 of the present invention is that it also permits extremely high data transfer rates by using, for data interchange, the host device's own BIOS routines which are optimized for each host device by the host device manufacturer or BIOS system manufacturer, or by using driver programs which are normally optimized and included by the manufacturers of multi-purpose interfaces. Furthermore, due to the simulation of a virtual mass storage device, the data is managed and made available in such a way that it can be transferred directly to other storage media, e.g. to an actual hard disk of the host device without, as it were, intervention of the host device processor. The only limitation to long-term data transfer at high speed is therefore imposed exclusively by the speed and the size of the mass storage device of the host device. This is the case as the digital signal processor 13 already formats the data read by the data transmit/receive device via the second connecting device 15 into block sizes suitable for a hard disk of the host device, whereby the data transfer speed is limited only by the mechanical latency of the hard disk system of the host device. At this point, it should be noted that normally data flow from a host device must be formatted in blocks to permit writing to a hard disk and subsequent reading from a hard disk, as known by those skilled in the art.

8

The said data transfer rate can be increased further by setting up a direct memory access (DMA) or RAM drive in the host system. As those skilled in the art know, the setting up of a RAM drive requires processor resources of the host device, with the result that the advantage of writing the data to a hard disk drive of the host device essentially without the need for processor resources is lost.

As described above, a data buffer can be implemented in the memory means 14 to permit independence in terms of time of the data transmit/receive device attached to the second connecting device from the host device attached to the first connecting device. This guarantees error-free operation of the interface device 10 even for time-critical applications in multi-tasking host systems.

FIG. 2 shows a detailed block diagram of an interface device 10 according to the present invention.

A digital signal processor (DSP) 1300 is, in a manner of speaking, the heart of the interface device 10. The DSP can be any DSP but preferably has a 20-MB on-chip random access memory (RAM). Certain instruction sets, for example, can be stored in the RAM already integrated in the DSP. An 80-MHz clock generator is attached to the DSP 1300 in order to synchronize the DSP. The DSP implements a fast Fourier transformation (FFT) in real time and also optional data compression of the data to be transferred from the data transmit/receive device to the host device in order to achieve greater efficiency and to permit interoperability with host devices which have a smaller memory.

In the preferred embodiment of the interface device 10 shown in FIG. 2, the first connecting device 12 of FIG. 1 contains the following components: an SCSI interface 1220 and a 50-pin SCSI connector 1240 for attachment to an SCSI interface present on most host devices or laptops. The SCSI (small computer system interface) interface 1220 translates the data received via the SCSI connector 1240 into data understood by the DSP 1300, as known by those skilled in the art. Further, the first connecting device 12 comprises an EPP (enhanced parallel port) with a data transfer rate of approx. 1 MBps which delivers a more moderate data transfer rate of 1 MBps by comparison to the data transfer rate of 10 MBps of the SCSI interface. The EPP 1260 is connected to a 25-pin D-shell connector 1280 to permit attachment to a printer interface of a host device for example. Optionally, the first connecting device 12 also comprises a 25-pin connector 1282 which permits the attachment of 8 digital outputs and 8 digital inputs 1284 at a host device.

Preferably, the second connecting device comprises 8 BNC inputs with the calibration relay 1505, a block 1510 with 8 device amplifiers with an overvoltage protection of ± 75 V, this block being connected in turn to 8 sample/hold (S&H) circuits 1515. The calibration relays are relays which permit controlled changeover between a test voltage and a calibration reference voltage. Each sample/hold circuit is connected to a corresponding input of an 8-channel multiplexer 1520 which feeds its output signals via a programmable amplifier 1525 into an analog/digital converter (ADC) with 12 bit and 1.25 MHz 1530 and to the DSP 1300. The ADC 1530 is controlled by means of a 20-bit timer 1535, as known by persons skilled in the art. The programmable amplifier 1525 and the 8-channel multiplexer 1520 are controlled via an amplifier channel selection circuit 1540 which is in turn controlled by the DSP 1300.

The complete interface device 10 is supplied with power by an external AC/DC converter 1800 which delivers a digital supply voltage of ± 5 V and is attached to a DC/DC

US 6,895,449 B2

9

converter **1810** which can deliver analog supply voltages of ± 5 V and ± 15 V as required for the interface device **10**. Further, the DC/DC converter controls a precision voltage reference **1820** which controls the 8 BNC inputs **1505** and the ADC **1530** as well as a digital/analog converter (DAC) **1830** which permits, via an output amplifier block with 4 output amplifiers **1840** and a 9-pin connector **1850**, analog output direct from the DSP **1300** to an output device, e.g. printer device or monitor device, which can be attached via the 9-pin connector **1850**, thus providing the option of monitoring the data transferred to the host device or also, for example, of viewing an FFT to obtain rapid and comprehensive data analysis without using processor time of the host device.

In FIG. 2 the memory means **14** of FIG. 1 is implemented by an EPROM **1400** which, in a preferred embodiment of the present invention, contains the operating system of the digital signal processor **1300**. A random access memory with an access time of 15 ns and a size of 512 KB or optionally 1024 KB **1420** serves as a data buffer to achieve independence in terms of time of the output line **16** from the output lines **11a**, **11b** and **11c** to the data transmit/receive device and to the host device respectively. As described above, in a preferred embodiment of the present invention the digital signal processor **1300** already contains a 20-KB on-chip RAM **1440** which can store certain instruction sets, functions and also smaller application software units.

The connection, symbolized by the line **16**, of the interface device **10** to any data transmit/receive device implements, by means of the blocks **1505**–**1535**, an analog input with a sampling rate of 1.25 MHz and quantization of 12 bits. There are 8 channels with an overvoltage protection of ± 75 V. By means of the programmable amplifier **1525** the channels can be programmed independently of each other in voltage ranges up to a maximum of ± 10 V. Unused channels can be grounded internally to reduce channel intermodulation. The block **1515** is implemented as a monolithic high-precision, high-speed sample/hold amplifier for simultaneous sampling of all channels. The precision voltage reference **1820** provides a high-precision, temperature-compensated monolithic energy gap voltage reference for auto-calibration of each channel and each gain. Further, offset fine adjustment for each channel is implemented by the same.

The blocks **1830**, **1840** and **1850** implement a direct analog output for the digital signal processor **1300**, and the DAC **1830** provides a data transfer rate of 625 kHz and a quantization of 12 bits. The block **1840** comprises 4 channels with a common output latch.

Further, the interface device **10** comprises a digital input/output device implemented by the blocks **1284** and **1282**. Here there are 8 digital inputs, 8 digital outputs with a common latch, and the digital port can be attached preferably to a side panel of the interface device **10** so that the port itself can easily be accessed.

The digital signal processor **1300** provides on-board digital data processing. In particular, it is a high-performance DSP with a clock speed of 80 MHz and a 20-bit timer **1535**.

As described above, the first connecting device **12** comprises the SCSI interface **1220** with a peak transfer rate of 10 MBps. An optional PCMCIA-to-SCSI adapter permits high-speed communication with laptop computers which are desirable and in widespread use, particularly by mobile service technicians. The EPP **1260** with its associated connector **1280** permits data transfer at a more moderate rate.

As described above, the interface device **10** is supplied with power by means of an external AC/DC adapter which

10

has a universal power input (85–264 VAC, 47–63 Hz). Interference suppression complies with the standards EN 55022, curve B and FFC, Class B). Further, it is also in accordance with international safety regulations (TÜV, UL, CSA). The interface device **10** is externally shielded and achieves a value of 55 dB at 30–60 MHz and a value of approximately 40 dB at 1 GHz, and therefore complies with the MILSTD 285-1 standard.

As described above, communication between the host device and the multi-purpose interface can take place not only via drivers for input/output device customary in a host device which reside in the BIOS system of the host device but also via specific interface drivers which, in the case of SCSI interfaces, are known as multi-purpose interface ASPI (advanced SCSI programming interface) drivers. This ASPI driver, which can also be referred to as an ASPI manager, is specific to a special SCSI host adapter, i.e. to a special multi-purpose interface, and is normally included by the manufacturer of the multi-purpose interface. Generally speaking, this multi-purpose interface driver has the task of moving precisely specified SCSI commands from the host system program to the host system SCSI adapter. For this reason, the command set is almost identical to that of the SCSI interface itself. Essentially, only status and reset commands for the host adapter have been added.

The ASPI driver can be used if the hard disk was not already addressable at boot time or if the SCSI-related BIOS routines of the host computer were still disabled. Here too, the steps needed to initialize the interface device, preferably as a virtual hard disk, are similar to the steps taken when initializing at boot time.

In general terms, the ASPI manager comprises two sides. One side is the proprietary, hardware-oriented side. It is responsible for converting all commands into a form required by the corresponding multi-purpose interface. The hardware-oriented side of the ASPI driver is therefore matched to a very specific type of multi-purpose interface or SCSI interface. The other side is known as the user software side. This side is totally independent of the proprietary operating characteristics of the SCSI adapter and is therefore identical for all SCSI interfaces. This permits SCSI programming which is however independent of the individual SCSI adapter types.

In contrast to communication between the host device and the interface device according to the present invention on the basis of a BIOS driver, the use of such an ASPI driver for communication between the host device and the interface device according to the present invention allows various further possibilities of the SCSI multi-purpose interface to be exploited. In the case described above, the interface device which preferably signs on and behaves as a virtual hard disk is detected by the BIOS driver of the host computer at boot time and is configured as a hard disk. This step does not however support active requests sent by the interface device to the host computer. If however the virtual hard disk wishes to write data actively to, for example, a hard disk of the host computer or wishes to initiate communication with the processor of the host computer, the host computer must recognize the request of the virtual hard disk and tolerate a further issuer of instructions on its bus. If the interface device behaves solely like a virtual hard disk, it would always receive and never issue commands. The BIOS has no objections to an additional issuer of commands that actively wishes to place data on the bus of the host device but the BIOS does not support the host device in recognizing corresponding requests of the interface device or in granting the interface device permission to access the bus.

US 6,895,449 B2

11

Using the ASPI manager the interface device according to the present invention can now obtain active access to an SCSI hard disk of the host device connected to the same SCSI bus which, in contrast to the interface device, cannot be a virtual but a real SCSI mass storage device or also a further interface device according to the present invention. Thereupon, the interface device according to the present invention can write the desired data to the SCSI hard disk of the host computer totally independently of the host computer or can communicate with the same in some other manner. The interface device according to the present invention therefore initially behaves passively as a virtual hard disk and then, as required and using the driver software for the multi-purpose interface, actively on the same SCSI bus. This means however that the interface device according to the present invention, using a driver software for the multi-purpose interface which comprises the BIOS routines customary in host devices and simultaneously provides the option of active participation, can, regardless of the type of the data transmit/receive device attached to the second connecting device, behave initially as a virtual and at the same time passive hard disk but can, as required, participate actively on the bus so as to be able to initiate communication directly with other SCSI hard disks of the host device by bypassing the processor of the host device.

Using a standard interface of a host device, the interface device according to the present invention permits communication with any host device. By simulating an input/output device to the host device and, in a preferred embodiment, by simulating a virtual mass storage device, the interface device 10 is automatically supported by all known host systems without any additional sophisticated driver software. The simulation of a freely definable file structure on the "virtual" hard disk provides simple operation and expansion options and, through the implementation of any programs, independence from special software implemented on the host device. Help files included on the interface device 10 and plug-and-play support ensure ease of use even in portable, flexible host devices. Despite the very simple user interface, experienced users are free at any time to intervene in the functions of the interface device 10 on system level. The interface device 10 thus provides a universal solution which can cover the entire spectrum of possible data transmit/receive devices.

What is claimed is:

1. An interface device for communication between a host device, which comprises drivers for input/output devices customary in a host device and a multi-purpose interface, and a data transmit/receive device comprising the following features:

- a processor;
- a memory;
- a first connecting device for interfacing the host device with the interface device via the multi-purpose interface of the host device; and
- a second connecting device for interfacing the interface device with the data transmit/receive device,

wherein the interface device is configured by the processor and the memory in such a way that the interface device, when receiving an inquiry from the host device as to the type of a device attached to the multi-purpose interface of the host device, sends a signal, regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, to the host device which signals to the host device that it is a storage device customary in a host device,

12

whereupon the host device communicates with the interface device by means of the driver for the storage device customary in a host device, and

wherein the interface device is arranged for simulating a virtual file system to the host, the virtual file system including a directory structure.

2. An interface device in accordance with claim 1, in which the directory structure has a configuration file for setting and controlling functions of the interface device or an executable or a batch file for conducting a routine stored in the memory or a data file used for transferring data from the data transmit/receive device to the host device or a help file for giving help on handling the interface device.

3. An interface device in accordance with claim 2 wherein the configuration file is a text file.

4. An interface device in accordance with claim 2 wherein the executable file includes a Fast Fourier Transform routine for transforming data acquired by the second connecting device into the frequency domain and for examining frequency domain data.

5. An interface device in accordance with claim 2 wherein the executable file includes a data compression routine for compressing data to be transmitted from the data transmit/receive device to the host device.

6. An interface device in accordance with claim 1 wherein, in response to a request from the host to read a boot sequence, the processor is arranged to send a virtual boot sequence to the host.

7. An interface device in accordance with claim 6 wherein the virtual boot sequence includes a starting position and a length of a file allocation table, an indication of a type of the storage device or a number of sectors of the storage device.

8. An interface device in accordance with claim 7 wherein, in response to a request from the host to display a directory of the storage device, a processor is arranged for transferring the file allocation table and the directory structure to the host.

9. An interface device in accordance with claim 1 wherein the file allocation table and the directory structure is transferred to the host in response to a request from the host to read data from or store data to the storage device.

10. An interface device in accordance with claim 1 wherein the directory structure includes a data file for transferring data from the data transmit/receive device to the host device wherein the processor is arranged to interpret a request from the host to read the data file as a request for a data transfer from the data transmit/receive device to the host, so that data is transmitted from the second connecting device to the first connecting device and to the host.

11. An interface device in accordance with claim 10 wherein the directory structure further includes a configuration file for specifying a time period for a measurement by the data transmit/receive device, wherein the interface device is arranged for simulating a length of the data file to the host that corresponds to an anticipated volume of data produced by the data transmit/receive device in the specified time period.

12. An interface device in accordance with claim 1 wherein the file allocation table includes information on numbers of blocks occupied by the data file wherein the interface device is arranged for receiving block numbers or a block number range from the host when the host wants to read the data file, and wherein the interface device is arranged to start a data transfer to the host, when the block numbers or the block number range is received from the host.

13. An interface device in accordance with claim 12 wherein the processor is arranged for formatting the data

US 6,895,449 B2

13

acquired by the second connecting device into blocks having a predetermined size, the predetermined size being suited for the storage device.

14. An interface device in accordance with claim 1 wherein the functions are gain, multiplex or synchronization settings of the second connecting device. 5

15. An interface device in accordance with claim 1 wherein the storage device is a hard disk.

16. An interface device in accordance with claim 1 wherein the memory has a data buffer for permitting independence in terms of time of the data transmit/receive device attachable to the second connecting device from the host device attachable to the first connecting device. 10

17. An interface device for communication between a host device, which comprises a multi-purpose interface and a specific driver for this interface, and a data transmit/receive device comprising the following features: 15

a processor;

a memory;

a first connecting device for interfacing the host device with the interface device via the multi-purpose interface of the host device; and 20

a second connecting device for interfacing the interface device with the data transmit/receive device, 25

where the interface device is configured using the processor and the memory in such a way that the interface device, when receiving an inquiry from the host device as to the type of a device attached at the multi-purpose interface of the host device, sends a signal, regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, to the host device which signals to the host device that it is a storage device customary in a host device, 30

14

whereupon the host device communicates with the interface device by means of the specific driver for the multi-purpose interface, and

wherein the interface device is arranged for simulating a virtual file system to the host, the virtual file system including a file allocation table and a directory structure.

18. A method of communication between a host device, which comprises drivers for input/output devices customary in a host device and a multi-purpose interface, and a data transmit/receive device via an interface device comprising the following steps:

interfacing of the host device with a first connecting device of the interface device via the multi-purpose interface of the host device;

interfacing of the data transmit/receive device with a second connecting device of the interface device;

inquiring by the host device at the interface device as to the type of device to which the multi-purpose interface of the host device is attached;

regardless of the type of the data transmit/receive device attached to the second connecting device of the interface device, responding to the inquiry from the host device by the interface device in such a way that it is a storage device customary in a host device, whereupon the host device communicates with the interface device by means of the usual driver for the storage device, and wherein the interface device is arranged for simulating a virtual file system to the host, the virtual file system including a file allocation table and a directory structure.

* * * * *

EXHIBIT

D

ASSIGNMENT

WHEREAS, LTT Labortechnik Tasler GmbH, is a corporation of Germany, has a P.O. address of Friedrich-Bergius-Ring 15, 97076 Würzburg, Germany, ("Assignor") and is the owner of the entire right, title, and interest in and to: United States Patent No. 6,470,399 B1, United States Patent No. 6,895,449 B2, and United States Patent Application No. 11/078,778 (hereinafter "Patent Rights").

WHEREAS, Papst Licensing GmbH & Co. KG, a German Corporation, having its principal place of business at Bahnhofstrasse 33, 78112 St. Georgen, Germany ("Assignee"), is desirous of acquiring the entire interest in and to the Patent Rights.

NOW, THEREFORE, for good and valuable consideration, the receipt of which is hereby acknowledged, and in consideration of the covenants and obligations hereinafter set forth to be well and truly performed, the parties hereby agree as follows.

1. Assignor hereby, sells, assigns, and transfers to Assignee, its lawful successors and assigns, Assignor's entire right, title and interest in and to the Patent Rights. Assignee hereby shall take, acquire and hold such right, title and interest in and to the Patent Rights.

2. Assignor hereby furthermore sells, assigns, and transfers to Assignee all claims for past, present, and future infringement of the inventions covered by Patent Rights, including without limitation all rights to recover damages and the right to grant releases for past infringement of the Patent Rights.

3. Assignor hereby further covenants and agrees, to render such assistance to Assignee as may be necessary to perfect the title to Patent Rights in said Assignee, its successors and assigns, to enable Assignee to prosecute all divisional, continuation, reexamination, and reissue applications, and to enable Assignee to obtain and enforce proper patent protection for the Patent Rights.

4. Assignor hereby covenants that no assignment, sale, agreement or encumbrance has been or will be made or entered into which would conflict with this assignment and sale.

5. Assignor further covenants that (i) Assignee will, upon its request, be provided promptly with all pertinent facts and documents relating to the Patent Rights as may be known and/or accessible to Assignor, (ii) Assignor shall testify as to the same in any interference or litigation related thereto, and (iii) Assignor shall promptly execute and deliver to Assignee or its legal representative any and all papers, instruments or affidavits required to apply for, obtain, maintain or enforce the Patent Rights and/or any U.S. patent rights evolving therefrom. Assignor shall use his best efforts to cooperate in good faith with Assignee.

LTT Labortechnik Tasler GmbH

By: Karl-Heinz TaslerTitle: General ManagerDate: March 8, 2006


Papst Licensing GmbH & Co. KG

By: Le. ParnTitle: PRESIDENTDate: March 8, 2006

Exhibit A

From: "Scott Stimpson" <stimpsonlaw@gmail.com>
To: "Joseph Cwik" <jecwik@welshkatz.com>
cc: "Jerold Schnayer" <jbschnayer@welshkatz.com>, "Jeffrey Gold" <jgold@morganlewis.com>, "J. Fee" <jkfee@morganlewis.com>, "Kevin He" <khe@morganlewis.com>, "lkrawczyk@morganlewis.com" <lkrawczyk@morganlewis.com>

Date: Friday, July 06, 2007 08:50AM
Subject: Re: Papst opposition to motion for sanctions



Joe:

Please respond to this email, as it is important to our pending motions. Thank you.

Scott

On 7/3/07, **Scott Stimpson** <stimpsonlaw@gmail.com> wrote:

Joe:

Your opposition to our motion regarding interrogatory 4 states that you only produced responsive documents "up until the date the Complaint was filed." Why? Are you limiting your interrogatory answer to that time frame, too?

We do not see in the Papst production any assignments or other agreements with the inventor. Has this been produced?

Thank you.

Scott

--

Scott D. Stimpson
The Law Office of Scott D. Stimpson
Suite 1102
445 Hamilton Avenue
White Plains, NY 10601
email: stimpsonlaw@gmail.com
phone: 203-258-8412

Disclaimer: This email is intended only for the personal use of the recipient(s) named above. This message may be an attorney-client communication and as such privileged and confidential. If you are not an intended recipient, you may not review, copy, or distribute this message. If you have received this communication in error, please notify me immediately by email and delete the original message.

--

Scott D. Stimpson
The Law Office of Scott D. Stimpson
Suite 1102

445 Hamilton Avenue
White Plains, NY 10601
email: stimpsonlaw@gmail.com
phone: 203-258-8412

Disclaimer: This email is intended only for the personal use of the recipient(s) named above. This message may be an attorney-client communication and as such privileged and confidential. If you are not an intended recipient, you may not review, copy, or distribute this message. If you have received this communication in error, please notify me immediately by email and delete the original message.

WELSH & KATZ, LTD.

Attorneys at Law

120 SOUTH RIVERSIDE PLAZA • 22ND FLOOR
CHICAGO, ILLINOIS 60606-3912

TELEPHONE (312) 655-1500
FACSIMILE (312) 655-1501

www.welshkatz.com

June 29, 2007

A. SIDNEY KATZ*
RICHARD L. WOOD*
JEROLD B. SCHNAYER
JOSEPH R. MARCUS
GERALD S. SCHUR
GERALD T. SHEKLETON
JAMES A. SCHEER
DANIEL R. CHERRY
ROBERT B. BREISBLATT
JAMES P. WHITE
R. MARK HALLIGAN
HARTWELL P. MORSE, III
EDWARD P. GAMSON, Ph.D.
KATHLEEN A. RHEINTGEN
THOMAS W. TOLPIN*
RICHARD W. McLAREN, JR.
ELLIOTT C. BANKENDORF
ERIC D. COHEN
JOHN L. AMBROGI
JULIE A. KATZ
JON P. CHRISTENSEN
WALTER J. KAWULA, JR.
LEONARD FRIEDMAN
STEVEN E. FELDMAN
JEFFREY W. SALMON
LOUISE T. WALSH
PAUL M. VARGO, Ph.D.
JOSEPH E. CWIK

J. ARON CARNAHAN
ERIK B. FLOM, Ph.D.
JAMES B. RADEN

RICHARD J. GURAK
DANIEL M. GURFINKEL
MICHELE S. KATZ*
BRIAN J. SODIKOFF
BRETT M. TOLPIN
GEORGE S. PAVLIK
MICHAEL A. KROL, Ph.D.
SHERRY L. ROLLO
CRAIG M. KUCHII
STEPHEN P. BENSON
GREGORY J. SKONY


OF COUNSEL
LAURIE A. HAYNIE
JAMES J. MYRICK
THOMAS R. VIGIL
PHILIP D. SEGREST, JR.**
WALLACE L. OLIVER, Ph.D.
LAURA A. LABEOTS, Ph.D.

DONALD L. WELSH (1925-1998)

* ALSO ADMITTED IN DISTRICT OF COLUMBIA
** ALSO ADMITTED IN ALABAMA

VIA E-MAIL

Jeffrey Gold, Esq.
Morgan Lewis & Bockius, LLP
101 Park Avenue
New York, New York 10178



Re: Casio Inc. v. Papst Licensing, Case No. 1:06 CV 011751 (GK)

Dear Jeffrey:

In response to Casio Inc. Interrogatory No. 2, Papst hereby identifies the following documents pursuant to Rule 33(d):

Beginning Bates No. For Each Document	End Bates No. For Each Document
PAP0001093	PAP0001355
PAP0002914	PAP0002914
PAP0002915	PAP0002919
PAP0002920	PAP0002923
PAP0002924	PAP0002929
PAP0002930	PAP0002934
PAP0002935	PAP0002935
PAP0002936	PAP0002941
PAP0002942	PAP0002960
PAP0002961	PAP0003352
PAP0003353	PAP0003353
PAP0003354	PAP0003367
PAP0003368	PAP0003474
PAP0003475	PAP0003525

Jeffrey Gold

June 29, 2007
Page 2

PAP0003526	PAP0003667
PAP0003668	PAP0003669
PAP0003670	PAP0003670
PAP0003671	PAP0003676
PAP0003677	PAP0003723
PAP0003724	PAP0003724
PAP0003725	PAP0004091
PAP0004092	PAP0004094
PAP0004095	PAP0004098
PAP0004099	PAP0004102
PAP0004103	PAP0004105
PAP0004106	PAP0004108
PAP0004109	PAP0004110
PAP0004111	PAP0004113
PAP0004114	PAP0004114
PAP0004115	PAP0004117
PAP0004118	PAP0004120
PAP0004121	PAP0004124
PAP0004125	PAP0004127
PAP0004128	PAP0004129
PAP0004130	PAP0004131
PAP0004132	PAP0004134
PAP0004135	PAP0004136
PAP0004137	PAP0004142
PAP0005150	PAP0005159
PAP0005160	PAP0005198
PAP0005199	PAP0005209
PAP0005210	PAP0005235
PAP0005236	PAP0005242
PAP0005243	PAP0005263
PAP0005264	PAP0005275
PAP0005276	PAP0005288
PAP0005289	PAP0005296
PAP0005297	PAP0005427
PAP0005428	PAP0005529
PAP0005530	PAP0005537
PAP0005538	PAP0005560
PAP0005561	PAP0005594
PAP0005595	PAP0005621
PAP0005622	PAP0005633
PAP0005634	PAP0005641
PAP0005642	PAP0005665
PAP0005666	PAP0005690
PAP0005691	PAP0005706
PAP0005707	PAP0005718
PAP0005719	PAP0005730
PAP0005731	PAP0005744
PAP0005745	PAP0005758
PAP0005759	PAP0005772
PAP0005773	PAP0005780
PAP0005781	PAP0005804
PAP0005805	PAP0005827
PAP0005828	PAP0005836

Jeffrey Gold

June 29, 2007
Page 3

PAP0005837	PAP0005846
PAP0005847	PAP0005859
PAP0005860	PAP0005882
PAP0005883	PAP0005898
PAP0005899	PAP0005926
PAP0005927	PAP0005942
PAP0005943	PAP0005953
PAP0005954	PAP0005962
PAP0005963	PAP0005988
PAP0005989	PAP0005995
PAP0005996	PAP0006008
PAP0006009	PAP0006036
PAP0006037	PAP0006046
PAP0006047	PAP0006106
PAP0006107	PAP0006115
PAP0006116	PAP0006133
PAP0006134	PAP0006151
PAP0006152	PAP0006164
PAP0006165	PAP0006181
PAP0006182	PAP0006209
PAP0006210	PAP0006219
PAP0006220	PAP0006253
PAP0006254	PAP0006261
PAP0006262	PAP0006274
PAP0006275	PAP0006328
PAP0006329	PAP0006448
PAP0006449	PAP0006459
PAP0006460	PAP0006486
PAP0006487	PAP0006605
PAP0006606	PAP0006621
PAP0006622	PAP0006634
PAP0006635	PAP0006674
PAP0006675	PAP0006724
PAP0006725	PAP0006821
PAP0006822	PAP0006838
PAP0006839	PAP0006855
PAP0006856	PAP0006862
PAP0006863	PAP0006873
PAP0006874	PAP0006885
PAP0006886	PAP0006901
PAP0006902	PAP0006999
PAP0007000	PAP0007021
PAP0007032	PAP0007055
PAP0007066	PAP0007087
PAP0007863	PAP0008130
PAP0008131	PAP0008393
PAP0013821	PAP0013822
PAP0013823	PAP0013824
PAP0013825	PAP0013826
PAP0013827	PAP0013828
PAP0013829	PAP0013830
PAP0013831	PAP0013832
PAP0013833	PAP0013834

Jeffrey Gold

June 29, 2007
Page 4

PAP0013835	PAP0013838
PAP0013839	PAP0013843
PAP0013844	PAP0013847
PAP0013848	PAP0013850
PAP0013851	PAP0013855
PAP0013856	PAP0013873

In response to Casio Inc. Interrogatory No. 4, Papst hereby identifies the following documents pursuant to Rule 33(d):

Beginning Bates No. For Each Document	End Bates No. For Each Document
PAP0000001	PAP0000006
PAP0000007	PAP0000007
PAP0000008	PAP0000008
PAP0000009	PAP0000009
PAP0000010	PAP0000010
PAP0000011	PAP0000011
PAP0000012	PAP0000018
PAP0000019	PAP0000025
PAP0000026	PAP0000027
PAP0000028	PAP0000029
PAP0000030	PAP0000031
PAP0000032	PAP0000033
PAP0000034	PAP0000041
PAP0000042	PAP0000042
PAP0000043	PAP0000043
PAP0000044	PAP0000046
PAP0000047	PAP0000049
PAP0000050	PAP0000054
PAP0000055	PAP0000071
PAP0000072	PAP0000073
PAP0000074	PAP0000075
PAP0000076	PAP0000076
PAP0000077	PAP0000078
PAP0000079	PAP0000081
PAP0000082	PAP0000084
PAP0000085	PAP0000085
PAP0000086	PAP0000087
PAP0000088	PAP0000089
PAP0000090	PAP0000095
PAP0000096	PAP0000098
PAP0000099	PAP0000106
PAP0000107	PAP0000107
PAP0000108	PAP0000117
PAP0000118	PAP0000119
PAP0000120	PAP0000121
PAP0000122	PAP0000124

Jeffrey Gold

June 29, 2007
Page 5

PAP0000125	PAP0000126
PAP0000127	PAP0000127
PAP0000128	PAP0000129
PAP0000130	PAP0000131
PAP0000132	PAP0000132
PAP0000133	PAP0000137
PAP0000138	PAP0000142
PAP0000143	PAP0000155
PAP0000156	PAP0000157
PAP0000158	PAP0000158
PAP0000159	PAP0000160
PAP0000161	PAP0000172
PAP0000173	PAP0000174
PAP0000175	PAP0000175
PAP0000176	PAP0000176
PAP0000177	PAP0000184
PAP0000185	PAP0000189
PAP0000190	PAP0000190
PAP0000191	PAP0000192
PAP0000193	PAP0000197
PAP0000198	PAP0000199
PAP0000200	PAP0000201
PAP0000202	PAP0000203
PAP0000204	PAP0000205
PAP0000206	PAP0000207
PAP0000208	PAP0000216
PAP0000217	PAP0000218
PAP0000219	PAP0000222
PAP0000223	PAP0000224
PAP0000225	PAP0000226
PAP0000227	PAP0000231
PAP0000232	PAP0000232
PAP0000233	PAP0000234
PAP0000235	PAP0000236
PAP0000237	PAP0000238
PAP0000239	PAP0000241
PAP0000242	PAP0000246
PAP0000247	PAP0000252
PAP0000253	PAP0000253
PAP0000254	PAP0000255
PAP0000256	PAP0000257
PAP0000258	PAP0000259
PAP0000260	PAP0000265
PAP0000266	PAP0000269
PAP0000270	PAP0000270
PAP0000271	PAP0000276
PAP0000277	PAP0000278
PAP0000279	PAP0000279
PAP0000280	PAP0000287
PAP0000288	PAP0000288
PAP0000289	PAP0000291
PAP0000292	PAP0000292
PAP0000293	PAP0000294

Jeffrey Gold

June 29, 2007
Page 6

PAP0000295	PAP0000300
PAP0000301	PAP0000302
PAP0000303	PAP0000304
PAP0000305	PAP0000305
PAP0000306	PAP0000307
PAP0000308	PAP0000309
PAP0000310	PAP0000311
PAP0000312	PAP0000313
PAP0000314	PAP0000318
PAP0000319	PAP0000325
PAP0000326	PAP0000330
PAP0000331	PAP0000335
PAP0000336	PAP0000337
PAP0000338	PAP0000339
PAP0000340	PAP0000344
PAP0000345	PAP0000349
PAP0000350	PAP0000354
PAP0000355	PAP0000360
PAP0000361	PAP0000365
PAP0000366	PAP0000366
PAP0000367	PAP0000368
PAP0000369	PAP0000376
PAP0000377	PAP0000379
PAP0000380	PAP0000382
PAP0000383	PAP0000386
PAP0000387	PAP0000400
PAP0000401	PAP0000410
PAP0000411	PAP0000412
PAP0000413	PAP0000416
PAP0000417	PAP0000419
PAP0000420	PAP0000425
PAP0000426	PAP0000427
PAP0000428	PAP0000429
PAP0000430	PAP0000430
PAP0000431	PAP0000436
PAP0000437	PAP0000440
PAP0000441	PAP0000443
PAP0000444	PAP0000446
PAP0000447	PAP0000449
PAP0000450	PAP0000452
PAP0000453	PAP0000456
PAP0000457	PAP0000458
PAP0000459	PAP0000459
PAP0000460	PAP0000465
PAP0000466	PAP0000466
PAP0000467	PAP0000468
PAP0000469	PAP0000471
PAP0000472	PAP0000473
PAP0000474	PAP0000474
PAP0000475	PAP0000476
PAP0000477	PAP0000477
PAP0000478	PAP0000479
PAP0000480	PAP0000485

Jeffrey Gold

June 29, 2007
Page 7

PAP0000486	PAP0000491
PAP0000492	PAP0000493
PAP0000494	PAP0000495
PAP0000496	PAP0000498
PAP0000499	PAP0000500
PAP0000501	PAP0000501
PAP0000502	PAP0000509
PAP0000510	PAP0000511
PAP0000512	PAP0000512
PAP0000513	PAP0000515
PAP0000516	PAP0000518
PAP0000519	PAP0000526
PAP0000527	PAP0000527
PAP0000528	PAP0000531
PAP0000532	PAP0000532
PAP0000533	PAP0000537
PAP0000538	PAP0000541
PAP0000542	PAP0000543
PAP0000544	PAP0000546
PAP0000547	PAP0000563
PAP0000564	PAP0000565
PAP0000566	PAP0000567
PAP0000568	PAP0000586
PAP0000587	PAP0000591
PAP0000592	PAP0000593
PAP0000594	PAP0000596
PAP0000597	PAP0000597
PAP0000598	PAP0000599
PAP0000600	PAP0000605
PAP0000606	PAP0000607
PAP0000608	PAP0000608
PAP0000609	PAP0000610
PAP0000611	PAP0000612
PAP0000613	PAP0000614
PAP0000615	PAP0000615
PAP0000616	PAP0000618
PAP0000619	PAP0000624
PAP0000625	PAP0000626
PAP0000627	PAP0000627
PAP0000628	PAP0000629
PAP0000630	PAP0000639
PAP0000640	PAP0000647
PAP0000648	PAP0000649
PAP0000650	PAP0000651
PAP0000652	PAP0000664
PAP0000665	PAP0000665
PAP0000666	PAP0000668
PAP0000669	PAP0000669
PAP0000670	PAP0000670
PAP0000671	PAP0000672
PAP0000673	PAP0000676
PAP0000677	PAP0000677
PAP0000678	PAP0000678

Jeffrey Gold

June 29, 2007
Page 8

PAP0000679	PAP0000680
PAP0000681	PAP0000681
PAP0000682	PAP0000682
PAP0000683	PAP0000684
PAP0000685	PAP0000693
PAP0000694	PAP0000695
PAP0000696	PAP0000698
PAP0000699	PAP0000702
PAP0000703	PAP0000704
PAP0000705	PAP0000706
PAP0000707	PAP0000709
PAP0000710	PAP0000717
PAP0000718	PAP0000719
PAP0000720	PAP0000721
PAP0000722	PAP0000724
PAP0000725	PAP0000727
PAP0000728	PAP0000728
PAP0000729	PAP0000733
PAP0000734	PAP0000738
PAP0000739	PAP0000744
PAP0000745	PAP0000745
PAP0000746	PAP0000751
PAP0000752	PAP0000753
PAP0000754	PAP0000755
PAP0000756	PAP0000761
PAP0000762	PAP0000762
PAP0000763	PAP0000764
PAP0000765	PAP0000770
PAP0000771	PAP0000776
PAP0000777	PAP0000778
PAP0000779	PAP0000779
PAP0000780	PAP0000780
PAP0000781	PAP0000781
PAP0000782	PAP0000787
PAP0000788	PAP0000789
PAP0000790	PAP0000790
PAP0000791	PAP0000792
PAP0000793	PAP0000800
PAP0000801	PAP0000803
PAP0000804	PAP0000806
PAP0000807	PAP0000808
PAP0000809	PAP0000811
PAP0000812	PAP0000814
PAP0000815	PAP0000816
PAP0000817	PAP0000818
PAP0000819	PAP0000821
PAP0000822	PAP0000822
PAP0000823	PAP0000824
PAP0000825	PAP0000830
PAP0000831	PAP0000835
PAP0000836	PAP0000850
PAP0000851	PAP0000852
PAP0000853	PAP0000854

Jeffrey Gold

June 29, 2007

Page 9

PAP0000855	PAP0000856
PAP0000857	PAP0000857
PAP0000858	PAP0000858
PAP0000859	PAP0000860
PAP0000861	PAP0000866
PAP0000867	PAP0000868
PAP0000869	PAP0000871
PAP0000872	PAP0000877
PAP0000878	PAP0000883
PAP0000884	PAP0000885
PAP0000886	PAP0000886
PAP0000887	PAP0000888
PAP0000889	PAP0000894
PAP0000895	PAP0000910
PAP0000911	PAP0000919
PAP0000920	PAP0000922
PAP0000923	PAP0000923
PAP0000924	PAP0000925
PAP0000926	PAP0000928
PAP0000929	PAP0000929
PAP0000930	PAP0000930
PAP0000931	PAP0000933
PAP0000934	PAP0000942
PAP0000943	PAP0000944
PAP0000945	PAP0000952
PAP0000953	PAP0000961
PAP0000962	PAP0000962
PAP0000963	PAP0000964
PAP0000965	PAP0000966
PAP0000967	PAP0000969
PAP0000970	PAP0000987
PAP0000988	PAP0000989
PAP0000990	PAP0000992
PAP0000993	PAP0000998
PAP0000999	PAP0000999
PAP0001000	PAP0001001
PAP0001002	PAP0001003
PAP0001004	PAP0001009
PAP0001010	PAP0001011
PAP0001012	PAP0001012
PAP0001013	PAP0001021
PAP0001022	PAP0001023
PAP0001024	PAP0001026
PAP0001027	PAP0001029
PAP0001030	PAP0001031
PAP0001032	PAP0001033
PAP0001034	PAP0001035
PAP0001036	PAP0001037
PAP0001038	PAP0001039
PAP0001040	PAP0001040
PAP0001041	PAP0001042
PAP0001043	PAP0001043
PAP0001044	PAP0001045

Jeffrey Gold

June 29, 2007
Page 10

PAP0001046	PAP0001048
PAP0001049	PAP0001053
PAP0001054	PAP0001055
PAP0001056	PAP0001057
PAP0001058	PAP0001062
PAP0001063	PAP0001064
PAP0001065	PAP0001066
PAP0001067	PAP0001072
PAP0001073	PAP0001083
PAP0001084	PAP0001092
PAP0001356	PAP0001358
PAP0001359	PAP0001361
PAP0001362	PAP0001365
PAP0001366	PAP0001366
PAP0001367	PAP0001369
PAP0001370	PAP0001371
PAP0001372	PAP0001374
PAP0001375	PAP0001381
PAP0001382	PAP0001383
PAP0001384	PAP0001385
PAP0001386	PAP0001388
PAP0001389	PAP0001390
PAP0001391	PAP0001392
PAP0001393	PAP0001395
PAP0001396	PAP0001401
PAP0001402	PAP0001406
PAP0001407	PAP0001408
PAP0001409	PAP0001409
PAP0001410	PAP0001410
PAP0001411	PAP0001418
PAP0001419	PAP0001429
PAP0001430	PAP0001431
PAP0001432	PAP0001433
PAP0001434	PAP0001444
PAP0001445	PAP0001446
PAP0001447	PAP0001447
PAP0001448	PAP0001458
PAP0001459	PAP0001459
PAP0001460	PAP0001460
PAP0001461	PAP0001461
PAP0001462	PAP0001464
PAP0001465	PAP0001466
PAP0001467	PAP0001468
PAP0001469	PAP0001471
PAP0001472	PAP0001476
PAP0001477	PAP0001478
PAP0001479	PAP0001480
PAP0001481	PAP0001482
PAP0001483	PAP0001484
PAP0001485	PAP0001486
PAP0001487	PAP0001492
PAP0001493	PAP0001494
PAP0001495	PAP0001497

Jeffrey Gold

June 29, 2007
Page 11

PAP0001498	PAP0001502
PAP0001503	PAP0001506
PAP0001507	PAP0001507
PAP0001508	PAP0001509
PAP0001510	PAP0001512
PAP0001513	PAP0001514
PAP0001515	PAP0001516
PAP0001517	PAP0001521
PAP0001522	PAP0001524
PAP0001525	PAP0001526
PAP0001527	PAP0001527
PAP0001528	PAP0001529
PAP0001530	PAP0001535
PAP0001536	PAP0001537
PAP0001538	PAP0001540
PAP0001541	PAP0001553
PAP0001554	PAP0001621
PAP0001622	PAP0001622
PAP0001623	PAP0001625
PAP0001626	PAP0001626
PAP0001627	PAP0001629
PAP0001630	PAP0001632
PAP0001633	PAP0001637
PAP0001638	PAP0001642
PAP0001643	PAP0001644
PAP0001645	PAP0001649
PAP0001650	PAP0001651
PAP0001652	PAP0001652
PAP0001653	PAP0001657
PAP0001658	PAP0001659
PAP0001660	PAP0001660
PAP0001661	PAP0001665
PAP0001666	PAP0001671
PAP0001672	PAP0001676
PAP0001677	PAP0001684
PAP0001685	PAP0001685
PAP0001686	PAP0001688
PAP0001689	PAP0001693
PAP0001694	PAP0001694
PAP0001695	PAP0001695
PAP0001696	PAP0001699
PAP0001700	PAP0001710
PAP0001711	PAP0001716
PAP0001717	PAP0001718
PAP0001719	PAP0001722
PAP0001723	PAP0001728
PAP0001729	PAP0001729
PAP0001730	PAP0001735
PAP0001736	PAP0001738
PAP0001739	PAP0001740
PAP0001741	PAP0001762
PAP0001763	PAP0001774
PAP0001775	PAP0001776

Jeffrey Gold

June 29, 2007
Page 12

PAP0001777	PAP0001778
PAP0001779	PAP0001788
PAP0001789	PAP0001800
PAP0001801	PAP0001803
PAP0001804	PAP0001808
PAP0001809	PAP0001809
PAP0001810	PAP0001810
PAP0001811	PAP0001814
PAP0001815	PAP0001818
PAP0001819	PAP0001819
PAP0001820	PAP0001820
PAP0001821	PAP0001824
PAP0001825	PAP0001825
PAP0001826	PAP0001826
PAP0001827	PAP0001840
PAP0001841	PAP0001842
PAP0001843	PAP0001843
PAP0001844	PAP0001848
PAP0001849	PAP0001849
PAP0001850	PAP0001851
PAP0001852	PAP0001853
PAP0001854	PAP0001855
PAP0001856	PAP0001857
PAP0001858	PAP0001864
PAP0001865	PAP0001866
PAP0001867	PAP0001868
PAP0001869	PAP0001877
PAP0001878	PAP0001879
PAP0001880	PAP0001881
PAP0001882	PAP0001883
PAP0001884	PAP0001885
PAP0001886	PAP0001893
PAP0001894	PAP0001895
PAP0001896	PAP0001897
PAP0001898	PAP0001904
PAP0001905	PAP0001905
PAP0001906	PAP0001907
PAP0001908	PAP0001917
PAP0001918	PAP0001918
PAP0001919	PAP0001921
PAP0001922	PAP0001925
PAP0001926	PAP0001928
PAP0001929	PAP0001929
PAP0001930	PAP0001933
PAP0001934	PAP0001939
PAP0001940	PAP0001941
PAP0001942	PAP0001942
PAP0001943	PAP0001944
PAP0001945	PAP0001946
PAP0001947	PAP0001948
PAP0001949	PAP0001950
PAP0001951	PAP0001959
PAP0001960	PAP0001961

Jeffrey Gold

June 29, 2007
Page 13

PAP0001962	PAP0001962
PAP0001963	PAP0001969
PAP0001970	PAP0001976
PAP0001977	PAP0001987
PAP0001988	PAP0001989
PAP0001990	PAP0001990
PAP0001991	PAP0002000
PAP0002001	PAP0002010
PAP0002014	PAP0002015
PAP0002016	PAP0002016
PAP0002017	PAP0002036
PAP0002037	PAP0002044
PAP0002045	PAP0002046
PAP0002047	PAP0002048
PAP0002049	PAP0002051
PAP0002052	PAP0002062
PAP0002063	PAP0002064
PAP0002065	PAP0002065
PAP0002066	PAP0002071
PAP0002072	PAP0002083
PAP0002084	PAP0002084
PAP0002085	PAP0002089
PAP0002090	PAP0002094
PAP0002095	PAP0002095
PAP0002096	PAP0002098
PAP0002099	PAP0002103
PAP0002104	PAP0002105
PAP0002106	PAP0002107
PAP0002108	PAP0002118
PAP0002119	PAP0002120
PAP0002121	PAP0002121
PAP0002122	PAP0002127
PAP0002128	PAP0002128
PAP0002129	PAP0002129
PAP0002130	PAP0002130
PAP0002131	PAP0002134
PAP0002135	PAP0002141
PAP0002142	PAP0002143
PAP0002144	PAP0002144
PAP0002145	PAP0002145
PAP0002146	PAP0002151
PAP0002152	PAP0002152
PAP0002153	PAP0002153
PAP0002154	PAP0002162
PAP0002163	PAP0002175
PAP0002176	PAP0002181
PAP0002182	PAP0002183
PAP0002184	PAP0002184
PAP0002185	PAP0002186
PAP0002187	PAP0002194
PAP0002195	PAP0002206
PAP0002207	PAP0002218
PAP0002219	PAP0002220

Jeffrey Gold

June 29, 2007
Page 14

PAP0002221	PAP0002221
PAP0002222	PAP0002223
PAP0002224	PAP0002224
PAP0002225	PAP0002237
PAP0002238	PAP0002239
PAP0002240	PAP0002240
PAP0002241	PAP0002249
PAP0002250	PAP0002260
PAP0002261	PAP0002263
PAP0002264	PAP0002264
PAP0002265	PAP0002273
PAP0002274	PAP0002275
PAP0002276	PAP0002279
PAP0002280	PAP0002281
PAP0002282	PAP0002293
PAP0002294	PAP0002294
PAP0002295	PAP0002296
PAP0002297	PAP0002297
PAP0002298	PAP0002302
PAP0002303	PAP0002304
PAP0002305	PAP0002314
PAP0002315	PAP0002315
PAP0002316	PAP0002318
PAP0002319	PAP0002321
PAP0002322	PAP0002322
PAP0002323	PAP0002324
PAP0002325	PAP0002326
PAP0002327	PAP0002334
PAP0002335	PAP0002337
PAP0002338	PAP0002338
PAP0002339	PAP0002339
PAP0002340	PAP0002342
PAP0002343	PAP0002345
PAP0002346	PAP0002348
PAP0002349	PAP0002353
PAP0002354	PAP0002354
PAP0002355	PAP0002356
PAP0002357	PAP0002357
PAP0002358	PAP0002365
PAP0002366	PAP0002368
PAP0002369	PAP0002369
PAP0002370	PAP0002370
PAP0002371	PAP0002372
PAP0002373	PAP0002378
PAP0018684	PAP0018690
PAP0018691	PAP0018694
PAP0018695	PAP0018700
PAP0018701	PAP0018701
PAP0018702	PAP0018703
PAP0018704	PAP0018705
PAP0018706	PAP0018736
PAP0018737	PAP0018745
PAP0018746	PAP0018749

Jeffrey Gold

June 29, 2007
Page 15

PAP0018752	PAP0018753
PAP0018754	PAP0018757
PAP0018758	PAP0018760
PAP0018761	PAP0018761
PAP0018762	PAP0018765
PAP0018766	PAP0018769
PAP0018774	PAP0018775
PAP0018776	PAP0018776
PAP0018777	PAP0018780
PAP0018781	PAP0018781
PAP0018782	PAP0018786
PAP0018787	PAP0018789
PAP0018790	PAP0018796
PAP0018797	PAP0018800
PAP0018801	PAP0018804
PAP0018805	PAP0018809
PAP0018810	PAP0018811
PAP0018812	PAP0018825
PAP0018826	PAP0018827
PAP0018828	PAP0018829
PAP0018830	PAP0018831
PAP0018832	PAP0018835
PAP0018836	PAP0018839
PAP0018842	PAP0018864
PAP0018865	PAP0018866
PAP0018867	PAP0018869
PAP0018870	PAP0018872
PAP0018873	PAP0018875
PAP0018876	PAP0018877
PAP0018878	PAP0018884
PAP0018885	PAP0018886
PAP0018887	PAP0018889
PAP0018890	PAP0018891
PAP0018892	PAP0018899
PAP0018900	PAP0018905
PAP0018906	PAP0018910
PAP0018911	PAP0018913
PAP0018914	PAP0018918
PAP0018919	PAP0018921
PAP0018922	PAP0018925
PAP0018926	PAP0018929
PAP0018930	PAP0018933
PAP0018934	PAP0018936
PAP0018937	PAP0018940
PAP0018941	PAP0018943
PAP0018944	PAP0018948
PAP0018949	PAP0018951
PAP0018952	PAP0018954
PAP0018955	PAP0018956
PAP0018957	PAP0018957
PAP0018958	PAP0018959
PAP0018960	PAP0018960
PAP0018961	PAP0018962

Jeffrey Gold

June 29, 2007
Page 16

PAP0018963	PAP0018964
PAP0018965	PAP0018965
PAP0018966	PAP0018970
PAP0018972	PAP0018973
PAP0018974	PAP0018977
PAP0018978	PAP0018980
PAP0018981	PAP0018982
PAP0018983	PAP0018984
PAP0018985	PAP0018988
PAP0018989	PAP0018990
PAP0018991	PAP0018993
PAP0018994	PAP0018998
PAP0018999	PAP0019001
PAP0019002	PAP0019013
PAP0019014	PAP0019019
PAP0019020	PAP0019023
PAP0019024	PAP0019025
PAP0019026	PAP0019026
PAP0019027	PAP0019031
PAP0019032	PAP0019033
PAP0019034	PAP0019035
PAP0019036	PAP0019037
PAP0019038	PAP0019039
PAP0019040	PAP0019041
PAP0019042	PAP0019043
PAP0019044	PAP0019046
PAP0019072	PAP0019074
PAP0019075	PAP0019077
PAP0019082	PAP0019083
PAP0019084	PAP0019088
PAP0019089	PAP0019090
PAP0019091	PAP0019092
PAP0019093	PAP0019095
PAP0019096	PAP0019097
PAP0019098	PAP0019099
PAP0019100	PAP0019101
PAP0019102	PAP0019103
PAP0019104	PAP0019105
PAP0019106	PAP0019109
PAP0019110	PAP0019116
PAP0019117	PAP0019124
PAP0019125	PAP0019129
PAP0019130	PAP0019131
PAP0019132	PAP0019145
PAP0019146	PAP0019147
PAP0019148	PAP0019148
PAP0019149	PAP0019155
PAP0019156	PAP0019158
PAP0019159	PAP0019162
PAP0019168	PAP0019171
PAP0019172	PAP0019200
PAP0019201	PAP0019208
PAP0019209	PAP0019210

Jeffrey Gold

June 29, 2007

Page 17

PAP0019211	PAP0019212
PAP0019213	PAP0019216
PAP0019217	PAP0019219
PAP0019220	PAP0019220
PAP0019221	PAP0019222
PAP0019223	PAP0019225
PAP0019226	PAP0019229
PAP0019230	PAP0019236
PAP0019237	PAP0019238
PAP0019239	PAP0019245
PAP0019246	PAP0019258
PAP0019259	PAP0019260
PAP0019261	PAP0019272
PAP0019273	PAP0019274
PAP0019275	PAP0019276
PAP0019277	PAP0019280
PAP0019281	PAP0019285
PAP0019286	PAP0019313
PAP0019314	PAP0019315
PAP0019316	PAP0019317
PAP0019318	PAP0019330
PAP0019331	PAP0019339
PAP0019340	PAP0019341
PAP0019342	PAP0019343
PAP0019344	PAP0019346
PAP0019347	PAP0019355
PAP0019356	PAP0019357
PAP0019358	PAP0019362
PAP0019363	PAP0019367
PAP0019368	PAP0019369
PAP0019370	PAP0019373
PAP0019374	PAP0019375
PAP0019376	PAP0019379
PAP0019380	PAP0019381
PAP0019382	PAP0019384
PAP0019385	PAP0019389
PAP0019390	PAP0019391
PAP0019392	PAP0019393
PAP0019394	PAP0019395
PAP0019396	PAP0019397
PAP0019398	PAP0019401
PAP0019402	PAP0019405
PAP0019419	PAP0019426
PAP0019427	PAP0019429
PAP0019430	PAP0019432
PAP0019433	PAP0019436
PAP0019439	PAP0019441
PAP0019442	PAP0019444
PAP0019445	PAP0019446
PAP0019447	PAP0019449
PAP0019450	PAP0019453
PAP0019454	PAP0019466
PAP0019467	PAP0019467

Jeffrey Gold

June 29, 2007
Page 18

PAP0019468	PAP0019469
PAP0019470	PAP0019476
PAP0019477	PAP0019477
PAP0019478	PAP0019480
PAP0019481	PAP0019482
PAP0019483	PAP0019487
PAP0019488	PAP0019493
PAP0019494	PAP0019502
PAP0019503	PAP0019508
PAP0019509	PAP0019511
PAP0019512	PAP0019515
PAP0019516	PAP0019519
PAP0019520	PAP0019521
PAP0019522	PAP0019522
PAP0019523	PAP0019524
PAP0019525	PAP0019527
PAP0019528	PAP0019531
PAP0019532	PAP0019534
PAP0019535	PAP0019539
PAP0019540	PAP0019541
PAP0019542	PAP0019542
PAP0019543	PAP0019548
PAP0019549	PAP0019562
PAP0019563	PAP0019569
PAP0019570	PAP0019573
PAP0019576	PAP0019577
PAP0019578	PAP0019578
PAP0019579	PAP0019584
PAP0019585	PAP0019587
PAP0019588	PAP0019591
PAP0019592	PAP0019595
PAP0020532	PAP0020534
PAP0020535	PAP0020537
PAP0020538	PAP0020539
PAP0020540	PAP0020542
PAP0020543	PAP0020544
PAP0020545	PAP0020546
PAP0020547	PAP0020556
PAP0020557	PAP0020566
PAP0020567	PAP0020570
PAP0020571	PAP0020575
PAP0020576	PAP0020586
PAP0020587	PAP0020589
PAP0020590	PAP0020591
PAP0020592	PAP0020592
PAP0020593	PAP0020595
PAP0020596	PAP0020599
PAP0020600	PAP0020602
PAP0020603	PAP0020606
PAP0020607	PAP0020608
PAP0020609	PAP0020615
PAP0020616	PAP0020621
PAP0020622	PAP0020624

Jeffrey Gold

June 29, 2007

Page 19

PAP0020625	PAP0020627
PAP0020628	PAP0020629
PAP0020630	PAP0020631
PAP0020632	PAP0020634
PAP0020635	PAP0020638
PAP0020641	PAP0020642
PAP0020643	PAP0020643
PAP0020644	PAP0020654
PAP0020655	PAP0020656
PAP0020657	PAP0020658
PAP0020659	PAP0020660
PAP0020661	PAP0020662
PAP0020663	PAP0020663
PAP0020664	PAP0020672
PAP0020673	PAP0020674
PAP0020675	PAP0020681
PAP0020682	PAP0020688
PAP0020689	PAP0020693
PAP0020694	PAP0020700
PAP0020701	PAP0020709
PAP0020710	PAP0020711
PAP0020712	PAP0020715
PAP0020716	PAP0020718
PAP0020719	PAP0020726
PAP0020727	PAP0020728
PAP0020729	PAP0020732
PAP0020735	PAP0020737
PAP0020738	PAP0020746
PAP0020747	PAP0020748
PAP0020749	PAP0020750
PAP0020751	PAP0020752
PAP0020753	PAP0020756
PAP0020762	PAP0020766
PAP0020767	PAP0020794
PAP0020795	PAP0020797
PAP0020798	PAP0020799
PAP0020800	PAP0020801
PAP0020803	PAP0020804
PAP0020805	PAP0020806
PAP0020807	PAP0020835
PAP0020836	PAP0020847
PAP0020848	PAP0020849
PAP0020850	PAP0020850
PAP0020851	PAP0020852
PAP0020853	PAP0020853
PAP0020854	PAP0020855
PAP0020856	PAP0020862
PAP0020863	PAP0020865
PAP0020866	PAP0020867
PAP0020868	PAP0020871
PAP0020872	PAP0020873
PAP0020874	PAP0020875
PAP0020876	PAP0020876

Jeffrey Gold

June 29, 2007

Page 20

PAP0020877	PAP0020881
PAP0020882	PAP0020882
PAP0020883	PAP0020884
PAP0020885	PAP0020886
PAP0020887	PAP0020888
PAP0020889	PAP0020890
PAP0020891	PAP0020891
PAP0020892	PAP0020893
PAP0020894	PAP0020894
PAP0020895	PAP0020899
PAP0020900	PAP0020907
PAP0020908	PAP0020916
PAP0020917	PAP0020921
PAP0020922	PAP0020926
PAP0020927	PAP0020927
PAP0020928	PAP0020932
PAP0020933	PAP0020933
PAP0020934	PAP0020935
PAP0020936	PAP0020937
PAP0020938	PAP0020938
PAP0020939	PAP0020940
PAP0020941	PAP0020942
PAP0020943	PAP0020944
PAP0020945	PAP0020946
PAP0020947	PAP0020949
PAP0020950	PAP0020951
PAP0020952	PAP0020958
PAP0020959	PAP0020974
PAP0020975	PAP0021002
PAP0021003	PAP0021003
PAP0021004	PAP0021006
PAP0021007	PAP0021011
PAP0021012	PAP0021012
PAP0021013	PAP0021014
PAP0021015	PAP0021016
PAP0021017	PAP0021018
PAP0021019	PAP0021031
PAP0021032	PAP0021032
PAP0021033	PAP0021034
PAP0021035	PAP0021047
PAP0021048	PAP0021050
PAP0021051	PAP0021052
PAP0021053	PAP0021053
PAP0021054	PAP0021055
PAP0021056	PAP0021057
PAP0021058	PAP0021058
PAP0021059	PAP0021064
PAP0021065	PAP0021068
PAP0021069	PAP0021073
PAP0021074	PAP0021075
PAP0021078	PAP0021080
PAP0021081	PAP0021081
PAP0021082	PAP0021083

Jeffrey Gold

June 29, 2007

Page 21


PAP0021084	PAP0021087
PAP0021088	PAP0021092
PAP0021093	PAP0021101
PAP0021102	PAP0021102
PAP0021103	PAP0021104
PAP0021105	PAP0021106
PAP0021107	PAP0021108
PAP0021109	PAP0021112
PAP0021113	PAP0021114
PAP0021115	PAP0021119
PAP0021128	PAP0021130
PAP0021131	PAP0021133
PAP0021134	PAP0021161
PAP0021162	PAP0021163
PAP0021164	PAP0021167
PAP0021168	PAP0021173
PAP0021174	PAP0021175
PAP0021176	PAP0021176
PAP0021177	PAP0021180
PAP0021190	PAP0021191
PAP0021192	PAP0021195
PAP0021196	PAP0021200
PAP0021201	PAP0021202
PAP0021203	PAP0021208
PAP0021209	PAP0021210
PAP0021211	PAP0021211
PAP0021212	PAP0021215
PAP0021216	PAP0021216
PAP0021217	PAP0021218
PAP0021219	PAP0021222
PAP0021223	PAP0021223
PAP0021224	PAP0021225
PAP0021226	PAP0021228
PAP0021229	PAP0021232
PAP0021233	PAP0021239
PAP0021240	PAP0021240
PAP0021241	PAP0021244
PAP0021246	PAP0021247
PAP0021248	PAP0021250
PAP0021251	PAP0021252
PAP0021254	PAP0021255
PAP0021256	PAP0021262
PAP0021263	PAP0021269
PAP0021270	PAP0021337
PAP0021338	PAP0021347
PAP0021348	PAP0021348
PAP0021349	PAP0021350
PAP0021351	PAP0021352
PAP0021353	PAP0021353
PAP0021354	PAP0021356
PAP0021357	PAP0021357
PAP0021358	PAP0021358
PAP0021359	PAP0021360

Jeffrey Gold

June 29, 2007
Page 22

PAP0021361 PAP0021362
PAP0021363 PAP0021368

By:



Joseph E. Cwik

JEC/pm

cc: Jerold B. Schnayer
Campbell Killefer