EXHIBIT D

US006339830B1

(12) **United States Patent**
See et al.

(10) **Patent No.: US 6,339,830 B1**
(45) **Date of Patent: *Jan. 15, 2002**

(54) **DETERMINISTIC USER AUTHENTICATION SERVICE FOR COMMUNICATION NETWORK**

(75) Inventors: **Michael E. See**, Chapel Hill, NC (US); **John W. Bailey**, Agoura Hills, CA (US); **Charles L. Panza**, Park City, UT (US); **Yuri Pikover**; **Geoffrey C. Stone**, both of Malibu, CA (US)

(73) Assignee: **Alcatel Internetworking, Inc.**, Calabasas, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/525,506**

(22) Filed: **Mar. 15, 2000**

Related U.S. Application Data

(63) Continuation of application No. 08/874,754, filed on Jun. 13, 1997, now Pat. No. 6,070,243.

(51) **Int. Cl.**[7] **G06F 11/00**
(52) **U.S. Cl.** **713/202**; 380/3
(58) **Field of Search** 713/202, 201, 713/200; 380/3, 4, 29, 30, 23, 25; 370/60, 94; 340/825.31, 825.34

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,896,319	A	*	1/1990	Lidinsky et al.	370/60
4,922,486	A		5/1990	Lidinsky	
4,962,449	A	*	10/1990	Schlesinger	364/200
5,191,613	A	*	3/1993	Graziano et al.	380/25
5,249,230	A	*	9/1993	Mihm, Jr.	380/23
5,272,754	A	*	12/1993	Boerbert	380/25
5,311,593	A	*	5/1994	Carmi	380/23
5,343,529	A	*	8/1994	Goldfine et al.	380/23
5,414,844	A	*	5/1995	Wang	395/650
5,469,576	A	*	11/1995	Dauerer et al.	395/186
5,499,297	A	*	3/1996	Boebert	380/23
5,502,766	A	*	3/1996	Boebert et al.	380/25
5,564,016	A	*	10/1996	Korenshtein	395/186
5,657,388	A	*	8/1997	Weiss	380/23

(List continued on next page.)

OTHER PUBLICATIONS

Claassen et al., "Secure communication procedure for ISDN", IEEE Trans. on computers, pp. 165–170, Jun. 1988.*
Eric Benhanmou, "Integrating Bridges and Routers in a large internetwork", IEEE Network, pp. 65–71, Jan. 1988.*
Weaver, et al., "A real–time Monitor for token ring Networks", IEEE Trans. on computers, pp. 0794–0798, May 1989.*


(List continued on next page.)

Primary Examiner—Nadeem Iqbal
(74) *Attorney, Agent, or Firm*—Scot A. Reader, Esq.

(57) **ABSTRACT**

A user authentication service for a communication network authenticates local users before granting them access to personalized sets of network resources. Authentication agents on intelligent edge devices present users of associated end systems with log-in challenges. Information supplied by the users is forwarded to an authentication server for verification. If successfully verified, the authentication server returns to the agents authorized connectivity information and time restrictions for the particular authenticated users. The agents use the information to establish rules for filtering and forwarding network traffic originating from or destined for particular authenticated users during authorized time periods. An enhanced authentication server may be engaged if additional security is desired. The authorized connectivity information preferably includes identifiers of one or more virtual local area networks active in the network. Log-in attempts are recorded so that the identity and whereabouts of network users may be monitored from a network management station.

40 Claims, 8 Drawing Sheets



U.S. PATENT DOCUMENTS

5,671,354	A	*	9/1997	Ito et al.	395/187.01
5,678,004	A	*	10/1997	Thaweethai	595/187.01
5,684,951	A	*	11/1997	Goldman et al.	395/188.01
5,696,898	A	*	12/1997	Baker et al.	395/187.01
5,721,780	A	*	2/1998	Ensor et al.	380/25
5,761,309	A	*	6/1998	Ohashi et al.	380/25
5,774,525	A	*	6/1998	Kanevsky et al.	379/88
5,774,551	A	*	6/1998	Wu et al.	380/25
5,774,650	A	*	6/1998	Chapman et al.	395/186
5,778,065	A	*	7/1998	Hauser et al.	380/21
5,784,566	A	*	7/1998	Viavant et al.	395/200.59
5,796,942	A	*	8/1998	Esbensen	395/187.01
5,852,714	A	*	12/1998	Tseng et al.	395/187.01
6,055,638	A	*	4/2000	Pascal et al.	713/201
6,061,790	A	*	5/2000	Bodnar	713/171
6,070,240	A	*	5/2000	Xydis	713/200
6,070,243	A	*	5/2000	See et al.	713/201

OTHER PUBLICATIONS

Ramesh, Karri, "A security Imbedded authentication protocol", IEEE Trans. on computers, pp. 1105–1109, Jun. 1988.*

Cole et al., "An architecture for a mobile OSI mail access system", IEEE Journal on selected Areas in communications, vol. 7, No. 2, pp. 249–256, Feb. 1989.*

Nakao et al., "Proposal on a secure communications service element in the OSI application Layer", IEEE Journal on selected areas on communications, vol. 7, No. 4, pp. 505–516, May 1989.*

Ciminiera et al., "Authentication mechanism in microprocessor–based local area networks", IEEE Trans. on software Engineering, col. 15, No. 5, pp. 654–658, May 1989.*

Lu et al., "Secure communication in internet environments: A hierarchical key management Scheme for end–to–end encryption", IEEE Trans. on communications, vol. 37, No. 10, pp. 1014–1023, Oct. 1989.*

Ascend Max/Pipeline Software Version 4.5 Dictionary Definitions, Oct. 18, 1996.

Livingston Enterprises, Inc., "Remote Authentication Dial In User Service (RADIUS) Ascend Difinitions," Jul. 25, 1995.

Rigney, C., "RADIUS Accounting," IETF RFC 1035, Jan. 1996, http://www.ietf.org/rfc/rfc2059.txt?number=2059.

Rigney, C., "Remote Authentication Dial In User Service (RADIUS)," IETF RFC 2058, Network Working Group Internet, Jan. 1997, http://www.ietf.org/rfc/rfc2058.txt?number=2058.


Hamzeh, K., "Ascend Tunnel Management Protocol—ATMP," IETF RFC 2107, Network Working Group Internet, Feb. 1997, ftp://ftp.isi.edu/in–notes/rfc2107.txt.

Rigney, C., "Remote Authentication Dial In User Service (RADIUS)," IETF RFC 2138, Apr. 1997, http://www.ietf.org/rfc/rfc2138.txt?number=2138.

Rigney, C., "RADIUS Accounting," IETF RFC 2139, Apr. 1997, http://www.ietf.org/rfc/rfc2139.txt?number=2139.

* cited by examiner

Figure 1


1
NETWORK MANAGEMENT STATION
20
BACKBONE NETWORK
30
10
INTELLIGENT EDGE DEVICE
15
INTELLIGENT EDGE DEVICE
40
45
60
65
50
55




Figure 2




Figure 3A




Figure 3B

Figure 4





Figure 5






Figure 6



7
EHHANCED AUTH. SERVER
770
NETWORK MANAGEMENT STATION
720
BACKBONE NETWORK
730
INTELLIGENT EDGE DEVICE
710
INTELLIGENT EDGE DEVICE
715
740
745
760
765
750
755

Figure 7



800
ID STOR
540
ENH ID VER
830
ID VER
530
ENH RSRC AUTH
820
CNCT EST
520
ENH CNCT EST
810
RSRC AUTH
510
NET MNTR
550

Figure 8




INITIALIZE DEVICE
905
BOOT-UP SYSTEM
910
TRANSMIT USER ID
915
IS USER ID RECOGNIZED?
N
Y
920
HAS MAX NUMBER OF LOG-IN ATTEMPTS BEEN MADE?
945
950
955
935
IS USER TIME-AUTHORIZED?
N
Y
925
940
TRANSMIT LIST
930

Figure 9

Figure 10


INITIALIZE DEVICE
BOOT-UP SYSTEM
TRANSMIT USER ID
IS USER ID RECOGNIZED?
N
HAS MAX NUMBER OF LOG-IN ATTEMPTS BEEN MADE?
N
Y
Y
IS USER TIME-AUTHORIZED?
N
1025
Y
1005
1015
N
IS ENHANCED METHOD INDICATED?
Y
TRANSMIT ENH. USER ID
IS ENHANCED USER ID RECOGNIZED?
1010
N
Y
TRANSMIT LIST
1020
1030

DETERMINISTIC USER AUTHENTICATION SERVICE FOR COMMUNICATION NETWORK

CROSS REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. patent application Ser. No. 08/874,754 filed on Jun. 13, 1997, now U.S. Pat. No. 6,070,243.

FIELD OF THE INVENTION

The present invention relates to regulating connectivity to and communicability within communication networks. More specifically, the present invention relates to authenticating and establishing personalized network communicability for local users of institutional communication networks.

BACKGROUND OF THE INVENTION

Institutions are relying increasingly on their data communication network infrastructures for efficient communication and data transfer. With this increasing reliance on network computing has arisen a significant need for mechanisms to regulate connectivity to and communicability within such networks. This need has been partially filled by internet protocol (IP) firewalls. IP firewalls typically restrict access to fixed sets of network resources by applying a set of protocol level filters on a packet-by-packet basis or by requiring prospective users to become authenticated before gaining access to the resources. Authentication has generally required users to supply certain signature information, such as a password. While this requirement of signature information has reduced the risk of unauthorized access to firewall-protected resources, firewalls have proven an imperfect and inflexible regulatory solution. Because firewalls are protocol-specific, firewalls have not provided a means for regulating network connectivity in a multi-protocol environment. Moreover, because firewalls regulate access to particular network resources, they have failed to provide a means for regulating access to sets of network resources which can vary as a function of user identity.

Protocol-independent mechanisms have also been deployed for authenticating users of the resources of institutional networks. However, such authentication mechanisms are only known to have been deployed to challenge remote users attempting to log-in over dial-up phone lines. Such mechanisms are not known to regulate the network access of local users logging-in over a LAN interfaces, such as Ethernet or Token Ring interfaces. Moreover, such mechanisms have, like firewalls, provided an inflexible solution which is unable to regulate access to customized or personalized sets of resources within the network based on user identity.

The flexibility limitations of the foregoing log-in challenge mechanisms have been partially overcome by independently implementing virtual local area networks (VLANs) within institutional networks. VLANs are sub-networks which typically include a plurality of network devices, such as servers, workstations and PCs, that together form a logical work group within a larger network. Because VLAN membership is assigned based on policies rather than physical location in the network, network bandwidth has been conserved and network security enhanced by assigning VLAN membership based on considerations of efficiency and need and restricting the flow of network traffic across VLAN boundaries.

While significant security and efficiency gains have been realized by policy-based VLANs, the solution they have offered is far from complete. VLAN membership has generally been assigned to end systems without reference to the identity of the users of such systems. In the current technology, for instance, VLAN membership is typically assigned by comparing network traffic with a configured set of rules which classify the traffic, and by inference the system which originated the traffic, into one or more VLANs. The identity of the user who sent the traffic is not considered in the assignment process. The failure to consider user identity leaves some network security issues unaddressed. Particularly, a person not authorized to use the resources of a VLAN may be able to gain access to its resources by transmitting data packets which the configured rules will classify into the VLAN, either by communicating over a member end system or by spoofing the required identifiers. Known VLAN assignment methods have also failed to contemplate providing conditional access to users based on the day of the week, the time of day, the length of access or a combination of such factors. Furthermore, current networking equipment and policy-based VLANs in particular have not offered collateral functionality, such as the ability to dynamically track where local users are connected to the network. Such a tracking mechanism would greatly simplify tasks such as network troubleshooting by allowing the network location of a user requesting technical support to be easily determined.

Accordingly, there is a need for comprehensive services for regulating communicability in institutional networks which are not subject to the inflexibility of conventional user log-in mechanisms or the lack of consideration for user identity of conventional VLAN assignment techniques. There is also a need for services which authenticate local users of institutional networks before establishing network communicability. There is a further need for user authentication services which provide collateral functionality, such as the ability to dynamically track the whereabouts of network users.

SUMMARY OF THE INVENTION

In accordance with its basic feature, the present invention combines the user-specific advantages of log-in challenges and the flexibility of VLANs into a deterministic user-based authentication and tracking service for local users of institutional communication networks.

It is therefore one object of the present invention to provide a service which authenticates local users before establishing network communicability.

It is another object of the present invention to provide a service which assigns and regulates user access to personalized sets of network resources.

It is another object of the present invention to provide a service which grants user access to personalized sets of network resources upon verifying signature information.

It is another object of the present invention to provide a service which conditions user access to personalized sets of network resources on one or more time-dependent variables.

It is another object of the present invention to provide a service which tracks user identity and network location.

These and other objects of the present invention are accomplished by a service which requires that local users be authenticated before gaining access to personalized sets of network resources. User identification information, time restrictions and authorized lists of resources for particular users are entered and stored in the network. Prior to

authentication, packets from an end system being used by a prospective user of network resources are transmitted to an authentication agent operative on an intelligent edge device associated with the system. The agent relays log-in responses received from the system to a basic authentication server in the network for verification of the user. Verification is made by comparing log-in responses with the user identification information stored in the network and determining whether time restrictions associated with the user identification information are applicable. If the basic authentication server is able to verify from the log-in response that the user is an authorized user of network resources, and that the user is authorized to use the network resources at the time of the log-in attempt, the basic authentication server transmits to the agent the list of network resources for which the user is authorized, along with any time restrictions. The agent forwards the list of authorized network resources and time restrictions for storage and use on the edge device. The edge device uses the authorized list of resources and time restrictions to establish network communicability rules for the user. Preferably, the authorized list of network resources is a list of one or more VLANs.

If the basic authentication server is unable to verify from the log-in response that the user is an authorized user of network resources and authorized to use network resources at the time of the log-in attempt, the basic authentication server communicates that information to the agent. Packets from the user continue to be directed to the agent or, alternatively, are dropped. Preferably, the number of log-in attempts users are granted before packets are dropped is configurable.

In another aspect of the invention, the basic authentication server records information relating to the identity and network location of users learned from log-in attempts. The information is accessible by a network administrator tracking network activity from a network management station.

In another aspect of the invention, when the basic authentication server successfully verifies that the user is an authorized user of network resources, and that the user is authorized to use the network resources at the time of the log-in attempt, the basic authentication server, in lieu of transmitting to the agent the list of authorized network resources and time restrictions, initiates an enhanced authentication method for the user. The enhanced authentication method is preferably conducted by an enhanced authentication server within the network.

In another aspect of the invention, when an authenticated user logs-off the network, or fails to transmit packets for a predetermined time, or if the system being used by the authenticated user is disconnected from the network, or if the authorized communicability period expires, or if the basic authentication server or other management entity instructs the agent to abolish the authenticated user's network communicability, the authenticated user's network communicability is deactivated.

The present invention can be better understood by reference to the following detailed description, taken in conjunction with the accompanying drawings which are briefly described below. Of course, the actual scope of the invention is defined by the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is a schematic of a network in which a preferred embodiment of the present invention is operative;

FIG. **2** is a schematic of an intelligent edge device operative in the network according to FIG. **1**;

FIG. **3A** is a schematic of a network management station operative in the network according to FIG. **1**;

FIG. **3B** is a schematic of a end system operative in the network according to FIG. **1**;

FIG. **4** is a functional diagram of an authentication agent operative in the network according to FIG. **1**;

FIG. **5** is a functional diagram of a basic authentication server operative in the network according to FIG. **1**;

FIG. **6** is a functional diagram of an authentication client operative in the network according to FIG. **1**;

FIG. **7** is a schematic of an LAN in which a more preferred embodiment of the present invention is operative;

FIG. **8** is a functional diagram of a basic authentication server operative in the network according to FIG. **7**;

FIG. **9** is a flow diagram of a preferred method for authenticating users within network **1**; and

FIG. **10** is a flow diagram of a preferred method for authenticating users within network **7**.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIG. **1**, a network **1** operating in accordance with a preferred embodiment of the present invention is shown. Network **1** includes intelligent edge devices **10**, **15** and a network management station **20** interconnected over a backbone network **30**, such as an asynchronous transfer mode (ATM) or fiber distributed data interface (FDDI) network. Devices **10**, **15** and station **20** are interconnected using cables, which may be fiber optic, unshielded twisted pair, or other form. Devices **10**, **15** are associated with end systems **40**, **50**, **60**, and **45**, **55**, **65**, respectively, which are operative in local area network (LAN) communication media, such as Ethernet or Token Ring. It will be appreciated that Ethernet as used herein is not limited to 10 megabit Ethernet, but includes other Ethernet varieties, such as Fast Ethernet and Gigabit Ethernet. Systems **40**, **50**, **60** and **45**, **55**, **65** may be workstations, PCs, or other systems having a user interface. Although the illustrated network **1** is shown to include two edge devices each associated with multiple end systems, it will be appreciated that a network operating in accordance with the present invention may include one or more edge devices interconnected across a backbone network, and that each edge device may be associated with one or more end systems or servers. It will also be appreciated that, in networks operating in accordance with the present invention, every edge device preferably has common operational capabilities.

Turning to FIG. **2**, device **10** is shown in greater detail. Device **10** is preferably representative of devices **10**, **15**. Device **10** includes a management processor module **210**, backbone module **220** and authentication modules **240**, **250**, **260** interconnected over a switching link **230**. Modules **220**, **240**, **250**, **260** are preferably implemented using custom logic, e.g., application specific integrated circuits (ASICs), while management processor module **210** is preferably software-implemented. Authentication modules **240**, **250**, **260** each include a LAN interface interconnecting systems **40**, **50**, **60**, respectively, and switching link **230**. In contradistinction to hubs which indiscriminately forward packets in unmodified form to all associated end systems, device **10** includes means on each of modules **220**, **240**, **250**, **260** for interpreting, modifying, filtering and forwarding packets. Preferably, modules **220**, **240**, **250**, **260** are also operative to perform necessary LAN media translations so that device **10** is able to support end stations operating using disparate

LAN media. Thus, for example, system **40** utilizing an Ethernet communication protocol may communicate through device **10** with system **50** utilizing Token Ring. LAN switches marketed by the assignee hereof under the federally registered trademarks OmniSwitch® and PizzaSwitch®, implemented with appropriate switching modules available from the assignee, may advantageously be implemented as devices **10, 15** in the performance of the above-described functionality.

Turning to FIG. 3A, a schematic diagram of network management station **20** is shown. Preferably, station **20** includes a user interface **310**, a software-implemented basic authentication server **320** and user records **330**. Although server **320** and user records **330** are shown operative on station **20**, server **320** and user records **330**, or either one, may be operative on another device in network **1** accessible by station **20**. Although network **1** is illustrated to include a single basic authentication server **320**, a network operating in accordance with the present invention may include one or more basic authentication servers. Server **320** is preferably configured with an address of each of devices **10, 15** and an associated authentication key for the authentication agent active on each of devices **10, 15**. The addresses are preferably IP addresses.

Turning to FIG. 3B, a schematic diagram of system **40** is shown. System **40** is representative of systems **40, 50, 60** and **45, 55, 65**. System **40** has a user interface **350** and an authentication client **360**. Authentication client **360** is software used during the authentication process. This is preferably a software application installed on system **40** but may also take the form of a standard software application such as Telnet. Client **360** is configured with an address of an authentication agent on associated device **10**, which may be an IP address or a reserved media access control (MAC) address.

An authentication agent is deployed on each of devices **10, 15**. Turning to FIG. **4**, a functional diagram of an authentication agent **400** residing on device **10** is shown. Agent **400** is preferably a software module implemented by management processor module **210**. Agent **400** is configured with an address of device **10**, an address of basic server **320** and an authentication key for server **320**. The configured addresses are preferably IP addresses.

Agent **400** includes CNCT EST means **410**. Means **410** serves, upon initialization of device **10**, to establish a secure connection with server **320**. Means **410** requests a connection to server **320** using the known address of server **320** and acknowledges a response from server **320** to such a request. Means **410** also transmits and receives information from and to server **320** sufficient to allow agent **400** and server **320** to authenticate one another. Preferably, mutual authentication is accomplished through exchange of authentication keys configured on agent **400** and server **320**. Means **410** may encrypt information and decipher encrypted information transmitted during the secure connection establishment process. TCP/IP based flows between agent **400** and server **320** are contemplated. Although network **1** is shown to include only one basic server **320**, it will be appreciated that a network may include more than one basic server. If an agent is configured with the address of more than one basic server in the network, and an attempt to establish a secure connection with a particular server fails, the agent may implement the foregoing process using the known address of another basic server until a secure connection is established.

Agent **400** also includes ID REQ means **420**. Means **420** serves to obtain log-in responses from users of associated systems **40, 50, 60** by communicating with authentication clients operative on systems **40, 50, 60**. Means **420** acknowledges requests received from clients to establish an authentication session. Means **420** responds to the requests by transmitting a log-in prompt to the requesting one of clients. IP-based flows using an application, such as Telnet, or MAC-based flows between agent **400** and clients are contemplated. Flows are initiated by clients using a reserved MAC address or IP address of agent **400** configured on clients.

Agent **400** also includes ID RLY means **430**. Means **430** serves to relay to server **320** for verification log-in responses received from users in response to log-in prompts. Means **430** associates the known address of device **10**, the identifier of the authentication module (i.e., **240, 250** or **260**) associated with the one of systems **40, 50, 60** being used by a user and the log-in response. Means **430** transmits the associated authentication information to server **320** for verification.

Agent **400** also includes VER RLY means **440**. Means **440** serves to relay user status information received from server **320** to users. Means **440** transmits user status information to the one of systems **40, 50, 60** being used by a user. User status information preferably includes a log-in valid or log-in invalid message, depending on whether server **320** was able to successfully verify the log-in response. IP-based flows using an application such as Telnet or MAC-based flows are contemplated for transmission of user status information between agent **400** and clients.

Agent **400** also includes SESS TERM means **450**. Means **450** serves to terminate an authentication session if a user has failed to be authenticated after a configurable number of failed log-in attempts. Means **450** transmits to the client associated with the one of systems **40, 50, 60** being used by the user an authentication session termination message after a configurable number of log-in failures. Means **450** also terminates the authentication session with the one of clients.

Agent **400** also includes RSRC RLY means **460**. Means **460** serves to forward for storage and use on device **10** authorized communicability information received from server **320** for authenticated users of systems **40, 50, 60**. Authorized communicability information may advantageously be transmitted by server **320** to agent **400** in the same data packet as user status information. Authorized communicability information includes, for the particular one of the systems **40, 50, 60**, a list of authorized network resources. Authorized communicability information may also include time restrictions, if any. Time restrictions preferably define times during which the particular user is authorized to use the network resources, such as the day of the week, the time of day, and the length of permitted access. The list of authorized network resources is preferably a list of VLAN identifiers. Authorized communicability information is preferably forwarded by agent **400** to management processor module **210** along with the authentication module identifier. Management processor module **210** preferably associates the authorized connectivity information with a known address of the one of the systems **40, 50, 60** being used by the authenticated user and stores the pair in device records. The address is preferably a MAC address.

Device records are advantageously used on device **10** to make filtering and forwarding decisions on packets received from and destined for authenticated users. Packets transmitted by an unauthenticated one of systems **40, 50, 60**, unless addressed to authentication agent **400**, are dropped by the receiving one of modules **240, 250, 260**. Packets addressed to an unauthenticated one of systems **40, 50, 60** are also

dropped. Packets transmitted by one of authenticated systems **40, 50, 60** addressed to another authenticated one of systems **40, 50, 60** are selectively forwarded according to the following rules:

1. If the destination address is the address of another one of systems **40, 50, 60** associated with device **10,** resort is made to device records on device **10** to verify that the source and destination systems share a common VLAN. If a VLAN is shared, the packet is forwarded to the destination system. If a VLAN is not shared, the packet is dropped.
2. If the destination address is not the address of another one of systems **40, 50, 60** associated with device **10,** resort is made to device records on device **10** to retrieve the VLAN identifiers associated with the source system. The VLAN identifiers are appended to the packet and the packet is transmitted by backbone module **220** on backbone network **30.** When the packet arrives on the edge device (e.g., **15**) associated with the destination system (e.g., **45**), resort is made to device records on the edge device to verify that the source and destination systems share a common VLAN. If a VLAN is shared, the packet is forwarded to the destination system. If a VLAN is not shared, the packet is dropped. Packets addressed to unauthenticated systems in network **1** continue to be dropped. The foregoing rules may be implemented using various known protocols. It will be appreciated that any addressable core, edge, or end devices, stations and systems in network **1** which are not subject to authentication requirements may be treated as authenticated systems for purposes of transmitting and receiving packets under the foregoing rules.

Agent **400** also includes ID TERM means **470.** Means **470** serves, upon receipt of log-off commands from authenticated users, or upon expiration of the authorized communicability period, or when one of authenticated systems **40, 50, 60** is physically disconnected from network **1,** or when one of authenticated systems **40, 50, 60** fails to send traffic for a prescribed length of time, or upon receipt of instruction from server **320,** to deactivate the established network communicability. Means **460** forwards to management processor module **210** a request to remove from device records the address-authorized communicability information entry for the user whose connectivity is to be deactivated. Upon receipt of such a request, management processor module **210** preferably removes the entry from device records and the authenticated one of systems **40, 50, 60** reverts to the unauthenticated state.

Turning to FIG. **5,** a functional diagram of basic authentication server **320** is shown. Server **320** includes RSRC AUTH means **510.** Means **510** serves to enable network administrators to define, on an individualized basis, authorized communicability information for users of the network **1.** Means **510** enables a network administrator to input user-specific entries. Means **510** supplies a textual or graphical display to user interface **310** operative to accept user-specific entries. Means **510** stores each user-specific entry as a related pair in user records **330.** Each user-specific entry preferably includes user identifier information and a list of authorized network resources. User-specific entries may also include time restrictions for the particular user. User identification information preferably includes signature information for the user, such as a password. Means **510** also enables a network administrator to input device-specific entries. Device-specific entries preferably includes, for each edge device in network **1** having an authentication agent, a device address and an authentication key. Device addresses are preferably IP addresses. Means **510** stores each device-specific entry as a related pair in network management records (not shown). Each device address is preferably uniquely assigned to a particular edge device operative within network **1.**

Server **320** also includes CNCT EST means **520.** Means **520** serves, upon receipt of a request from an authentication agent, to establish a secure connection with the agent. Means **520** acknowledges receipt from the agent of a request to establish a secure connections and to respond to the request. Means **520** also transmits and receives information sufficient to allow the agent and server **320** to authenticate one another. Preferably, authentication is established through exchange of authentication keys. Means **520** may encrypt information and decipher encrypted information transmitted during the secure connection establishment process. TCP/IP based flows between the agent and server **320** are contemplated.

Server **320** also includes ID VER means **530.** Means **530** serves to subject to a verification process authentication information received from users via agent **400.** Means **530,** upon receipt of authentication information from agent **400,** determines if the log-in response matches the user identification information associated with a user-specific entry in user records **330.** If a match is found, and there are time restrictions associated with the user-specific entry, means **530** determines from the time restrictions if the user is authorized to use network **1** at the particular time. If the user is time-authorized or there are no time restrictions, means **530** generates authorized communicability information. Means **530** retrieves the list of authorized network resources associated with the matching user identification information in the generation of authorized communicability information. Authorized communicability information may also include any time restrictions. Means **530** also generates user status information. User status information is information sufficient to communicate to agent **400** whether user identification information was successfully verified. User status information is preferably either a log-in valid or log-in invalid message. Means **530** transmits authorized information and user status information to agent **400.** Preferably, authorized communicability information and user status information are transmitted as part of the same data packet. If no match for user identification information is found, or if the user is not time-authorized, means **530** generates and transmits to agent **400** user status information, preferably in the form of a log-in invalid message, but does not generate or transmit authorized communicability information. Although the above described means operative on server **320** are described to be interoperative in conjunction with agent **400,** it will be appreciated that the means are fully interoperative with other authentication agents residing on edge devices in network **1.**

Server **320** also includes ID STOR means **540.** Means **540** serves to forward for storage and use by a network administrator user tracking information. User tracking information is preferably retained for all log-in attempts made by prospective users, whether successful or unsuccessful. User tracking information may include, for each login attempt, any information learned from one or more of the following: user identification information, authentication information, user status information, authorized communicability information. User tracking information also may include the time of day the log-in attempt was made. The time of day may be kept on and obtained from server **320.** Server **320** preferably associates the user tracking information and stores the

information as an entry in a network activity database (not shown) that is accessible by or resides on station **20**. Network activity database entries are accessible by a network administrator using interface **310**.

Server **320** also includes NET MNTR means **550**. Means **550** serves to enable a network administrator to access and use user tracking information. Means **550** supplies a textual or graphical display to interface **310** operative to display user tracking information. Means **550** also enables a network administrator to generate user tracking information reports consisting of related information from one or more user tracking information entries.

Turning to FIG. **6**, a functional diagram of client **360** is shown. Client **360** is representative of clients residing on systems **40**, **50**, **60** and **45**, **55**, **65**. Client **360** includes ID INIT means **610**. Means **610** serves, when system **40** is booted-up by a user, to request and establish an authentication session with agent **400**. Alternatively, means **610** can be activated by a direct action of the user of system **40**. Means **610** transmits to agent **400** a request to establish an authentication session using a known address of agent **400**. Client **360** preferably transmits requests periodically until agent **400** responds. A MAC-based flow is contemplated. Alternatively, an IP-based flow using an application such as Telnet may be used.

Client **360** also includes ID RPLY means **620**. Means **620** serves to enable users to reply to log-in prompts received from agent **400**. Means **620** supplies a textual or graphical display to a user interface of system **40** operative to accept log-in responses. Means **620** also transmits log-in responses to agent **400**.

Client **360** also includes VER DSPL means **630**. Means **630** serves to convey to users whether log-in attempts were successful or unsuccessful. Means **630** supplies a textual or graphical display to a user interface of system **40** operative to display user status information, preferably a log-in valid message or a log-in invalid message, received from agent **400**.

Client **360** further includes ID OFF means **640**. Means **640** serves to initiate the log-off process by which authenticated users log-off the network **1**. Means **640** supplies a textual or graphical display to user interface **350** operative to accept log-off commands. Means **640** transmits log-off commands to agent **400** for deactivation of established network communicability.

Referring to FIG. **7**, a network **7** operating in accordance with an alternative embodiment of the present invention is shown. In the alternative embodiment, an enhanced authentication method is conducted before network communicability is granted. Network **7** includes intelligent edge devices **710**, **715** and a network management station **720** interconnected over a backbone network **730** by means similar to those described in relation to network **1**. Bridges **710**, **715** are associated with end systems **740**, **750**, **760** and **745**, **755**, **765**, respectively, which utilize LAN communication media, such as Ethernet or Token Ring. Network **7** also includes enhanced authentication server **770** interconnected over backbone network **730**. It will be appreciated that, as in the previous preferred embodiment, a network operating in accordance with the alternative embodiment may include one or more edge devices having common operational capabilities and associated with one or more end systems. In network **7**, devices **710**, **715** station **720** and systems **740**, **750**, **760** and **745**, **755**, **765** have operational capabilities common to their counterparts in network **1**, plus additional operational capabilities hereafter described.

Turning to FIG. **8**, a functional diagram of a basic authentication server **800** preferably operable on station **720** is shown. Server **800** is preferably interoperative with devices **710**, **715** and systems **740**, **750**, **760** and **745**, **755**, **765** and associated modules, agents and clients to perform the functionality of server **320** described above, including RSRC AUTH means **510**, CNCT EST means **520**, ID VER means **530**, ID STOR means **540** and NET MNTR means **550**.

Server **800** also includes ENH CNCT EST means **810**. Means **810** serves to establish and maintain a secure connection with enhanced authentication server **770**. A TCP/IP based flow is contemplated. Server **800** also includes ENH RSRC AUTH means **820**. Means **820** serves to enable network administrators to define, on an individualized basis, an enhanced authentication method for each prospective user of network **7**. Means **820** enables a network administrator to enter user-specific entries which additionally include enhanced authentication method information. Enhanced authentication method information includes information sufficient to enable basic server **800** to identify a device, station, or system within network **7** which will conduct the enhanced authentication session, if any, the prospective user must successfully complete to become authenticated. Preferably, enhanced authentication method information includes an IP address of enhanced authentication server **770**. Enhanced authentication methods may include one of various security methods implemented on enhanced authentication server **770**. Authentication methods marketed under the trade names Secure ID™ by Security Dynamics, Inc. and methods that comply with Internet Engineering Task Force (IETF) RFC **2058** Remote Authentication Dial-in User Service (RADIUS) are referenced herein by way of example.

Server **800** also includes ENH ID VER means **830**. Means **830** serves, upon verifying log-in responses received from a user and that the user is authorized to use the network **7** at the time of the log-in attempt, to initiate an enhanced authentication method, if indicated. Means **830**, upon determining that the log-in response matches user identification information associated with a user-specific entry in user records, and upon determining that the user is time-authorized if time restrictions are indicated, checks whether there is an enhanced authentication method associated with the matching user-specific entry. If an enhanced authentication method is indicated, means **820**, before transmitting authorized communicability information and user status information to the agent on the appropriate one of devices **710**, **715**, transmits a request to enhanced authentication server **770** to conduct an enhanced authentication session with the user. The enhanced authentication session is preferably conducted between enhanced server **770** and the user transparently to basic server **800**. Enhanced server **770** instructs basic server **800** of the results of the enhanced authentication session. If the user was successfully authenticated, means **830** transmits to the agent authorized communicability information and user status information, preferably in the form of a log-in valid message. If the user was not successfully authenticated, means **830** transmits user status information, preferably a log-in invalid message, but no authorized communicability information. If an enhanced authentication method is not indicated when the check for an enhanced authentication method is performed, means **830** transmits to the agent authorized communicability information and user status information, in the form of a log-in valid message, without engaging server **770**. If a matching entry for user identification information is not found in user records, or if the user is not time-authorized, means **830** transmits to the agent user status information, in

the form of a log-in invalid message, without transmitting authorized communicability information.

Referring now to FIG. **9**, a flow diagram illustrates a preferred method for implementing the invention within network **1**. When device **10** is initialized (**905**), agent **400** attempts to establish a secure connection with server **320** using the known address of server **320**. Once a TCP session is successfully established, agent **400** and server **320** authenticate one another by exchanging authentication keys.

When a user boots-up device **40** (**910**), client **360** activates. Client **360** sends an authentication request to agent **400** using a known address of agent **400**. Authentication requests are transmitted to agent **400** periodically until agent **400** responds. When agent **400** receives a request, agent **400** responds by transmitting a log-in prompt to client **360**.

The user enters a log-in response and the response is transmitted to agent **400** (**915**). Agent **400** transmits authentication information to server **320**. Authentication information preferably includes an address of device **10**, an identifier of authentication module **240** associated with system **40**, and the log-in response.

Server **320** determines whether the log-in response is recognized on station **20** (**920**). Server **320** checks user records **330** for a user-specific entry having user identification information matching the log-in response. If a matching entry is found, server **320** checks any time restrictions associated with the entry to determine if the user is authorized to use the network resources at the particular time (**925**). If the prospective user is time-authorized, server **320** retrieves the list of authorized network resources and any time restrictions associated with the matching user identification information. The information is transmitted to agent **400** (**930**) along with user status information, preferably a log-in valid message. If no matching entry is found (**935**), or if the user is not time-authorized (**940**), user status information, preferably a log-in invalid message, is returned to the user via agent **400**. Agent **400** also in that instance determines if user has made the configurable number of failed log-in attempts (**945**). If the configurable number of failed log-in attempts has been reached (**950**), agent **400** terminates the authentication session with client **360**. The user is denied network access until such time as the user reboots system **40**. If the configurable number of failed log-in attempts has not been reached (**955**), agent **400** presents the user with another log-in prompt.

Turning to FIG. **10**, a flow diagram illustrates a preferred method for implementing the invention within network **7**. The method proceeds generally as in FIG. **9**, except that an enhanced authentication method is performed, if indicated. Accordingly, once a determination is made that the user is time-authorized (**1005**), basic server **800** checks whether there is an enhanced authentication method associated with the matching entry (**1010**). If an enhanced authentication method is indicated, server **800** transmits a request to enhanced authentication server **770** to conduct an enhanced authentication session with the user (**1015**). Enhanced server **770** informs basic server **800** of the results of the enhanced authentication session. If the session was successfully completed (**1020**), basic server **800** transmits authorized communicability information and user status information, in the form of a log-in valid message, to the agent (**1030**). If enhanced session was not successfully completed (**1025**), basic server **800** transmits a log-in invalid message to user and does not transmit authorized communicability information to agent. Agent also in that instance determines if user has made a configurable number of failed log-in attempts. The authentication session either continues or terminates as discussed depending on the outcome of that inquiry. If an enhanced authentication method is not indicated when the check for an enhanced authentication method is performed (**1010**), server **800** transmits authorized communicability information and user status information, in the form of a log-in valid message, without requesting server **770** to conduct an enhanced authentication session.

It will be appreciated by those of ordinary skill in the art that the invention can be embodied in other specific forms without departing from the spirit or essential character hereof. The present description is therefore considered in all respects to be illustrative and not restrictive. The scope of the invention is indicated by the appended claims, and all changes that come within the meaning and range of equivalents thereof are intended to be embraced therein.

We claim:

1. A user authentication method for a communication network having a plurality of nodes, the method comprising:

entering on a first node first user identification information;

transmitting to a second node the first user identification information, the second node having second user identification information;

comparing for a match on the second node the first user identification information with the second user identification information; and

authorizing communication between the first node and a group of nodes on the communication network in response to a match, wherein the group of nodes is represented by a virtual local area network identifier.

2. A user authentication method for a communication network having a plurality of nodes, the method comprising:

entering on a first node first user identification information;

transmitting to a second node the first user identification information, the second node having second user identification information;

comparing for a match on the second node the first user identification information with the second user identification information; and

establishing communicability between the first node and a group of nodes associated with the second user identification information in response to a match, wherein the group of nodes is represented by a virtual local area network identifier.

3. The method of claim **2**, wherein the first, second and group of nodes include devices selected from the group consisting of computers, workstations, and servers.

4. The user authentication method according to claim **2**, wherein the communicability is established for an access period associated with the second user identification information.

5. The user authentication method of claim **2**, wherein the first node includes an authentication client and the second node includes an authentication server.

6. A user authentication method for a communication network having a plurality of nodes, the method comprising:

associating a user of the network with a group of nodes represented by a virtual local area network based on a unique user key;

verifying the unique user key in a log-in sequence; and

authorizing communication between the user and the group of nodes upon verifying the unique user key.

7. The user authentication method according to claim **6**, wherein the group of nodes is represented in the association by a virtual local area network identifier.

8. The user authentication method according to claim 6, wherein the unique user key comprises a password.

9. A user authentication method for a communication network having a plurality of nodes, the method comprising:

associating a user of the network with a group of nodes and an access period based on a unique user key;

verifying the unique user key in a log-in sequence; and authorizing communication between the user and the group of nodes for the access period upon verifying the unique user key, wherein the group of nodes is represented by a virtual local area network.

10. The user authentication method according to claim 8, wherein the group of nodes is represented in the association by a virtual local area network identifier.

11. The user authentication method according to claim 8, wherein the unique user key comprises a password.

12. A user authentication method for a communication network having a plurality of nodes, the method comprising:

associating based on a unique user key each of a plurality of users of the network with a group of nodes represented by a virtual local area network selected for the user; and

verifying in a log-in sequence for each of the plurality of users the user's unique user key prior to establishing communicability between the user and the group of nodes selected for the user.

13. The user authentication method according to claim 12, wherein each group of nodes is represented in the association by a virtual local area network identifier.

14. The user authentication method according to claim 12, wherein each unique user key comprises a password.

15. A user authentication method for a communication network having a plurality of nodes, the method comprising:

entering on a first node first user identification information;

transmitting to a second node the first user identification information, the second node having a database with pairs of user identification information and network resources;

searching the database for paired user identification information matching the first user identification information; and authorizing communication between the first node and the network resources paired with matching user identification information, wherein the network resources are represented by a virtual local area network.

16. A user authentication method for a communication network having a plurality of nodes, the method comprising:

entering on a first node a first user identification information;

transmitting to a second node the first user identification information, the second node having second user identification information;

comparing for a match on the second node the first user identification information with the second user identification information; and

initiating upon a match an enhanced authentication for the user, whereby more information is solicited from the user and compared with information on a third node prior to establishing communicability between the user and a group of nodes represented by a virtual local area network identifier with which the user is authorized to communicate.

17. A user authentication method for a communication network having a plurality of nodes, the method comprising:

entering on a first node first user identification information;

transmitting to an authentication agent on a second node communicating with the first node over a LAN link the first user identification information;

relaying from the authentication agent to an authentication server the first user identification information;

comparing on the authentication server the first user identification information with user identification information in a database of user identification information; and

transmitting from the authentication server to the authentication agent, if the first user identification information matches user identification information in the database of user identification information, information notifying the authentication agent that a user on the first node has been authenticated whereupon the authentication agent authorizes transmission on the second node of packets in data flows involving the first node.

18. The user authentication method according to claim 17, wherein the first node and second node are co-located in a local area network.

19. The user authentication method according to claim 17, wherein the authentication server resides on the second node.

20. The user authentication method according to claim 17, wherein the authentication server resides on a third node.

21. The user authentication method according to claim 17, wherein the authorization includes data flows for which the first node is the source.

22. The user authentication method according to claim 17, wherein the authorization includes data flows for which the first node is the destination.

23. A user authentication method for a communication network having a plurality of nodes, the method comprising:

transmitting a log-in response from an end system being used by a user to an authentication agent;

relaying the log-in response to an authentication server;

reviewing the log-in response at the authentication server to determine if the user is authorized; and

transmitting to the authentication agent a list of network resources for which the user is authorized, along with any time restrictions whereupon the authentication agent applies the authorized list of network resources and time restrictions to establish network connectivity rules for the user, wherein the authentication agent is located on a node having a LAN link to the end system.

24. A user authentication system for a communication network comprising:

a first node for entering user identification information;

a second node for receiving the user identification information from the first node and comparing for a match the user identification information with user identification information in a database of user identification information; and

a port on the second node that is authenticated upon a match for allowing communication between the first node and a group of nodes associated with the user identification information, and is not authenticated upon a mismatch, thereby failing to establish communication between the first node and other nodes, wherein the group of nodes is associated with a virtual local area network.

25. The system according to claim 24, wherein the database resides on the second node.

26. The system according to claim 24, wherein the database resides on a third node.

27. The authentication system of claim 24, wherein the node is selected from the group consisting of a computer, a workstation, and a server.

28. A user authentication system for a communication network comprising:

a node interconnected to an edge device over a LAN, the edge device managing the packet flow from the node to a backbone network; and

the backbone network coupled to a network management station, wherein the edge device comprises:

an authentication module interfacing with the node, performing LAN media translations so that the edge device supports nodes operating using disparate LAN media;

a backbone module for interfacing the authentication module to the backbone network;

a switching link for switching packets from the authentication module to the backbone module, thereby allowing packets from authenticated users to flow between the node and the backbone network; and

a management processor module for managing the switching link.

29. The authentication module of claim 28, wherein the authentication module filters and forwards packets to and from the node.

30. The authentication module of claim 28, wherein the authentication module interprets and modifies packets to and from the node.

31. The authentication system of claim 28, wherein the network management station comprises:

a database of user records; and

an authentication server that compares user identity information with the user records in the database, and upon a match, the authentication server sends to the edge device, a list of network resources that a user on the first node is authorized to use, and upon a mismatch, the authentication server sends to the edge device an indication of non-authorization.

32. A user authentication system for a communication network, comprising:

a first node being used by a user; and

a second node communicating with the first node over a LAN link, the second node providing the sole interface between the first node and a LAN backbone, wherein the second node denies the first node access to the LAN backbone prior to the user becoming authenticated, except for conducting a user authentication protocol exchange.

33. The user authentication system according to claim 32, wherein the second node permits the first node access to the LAN backbone for other than the user authentication protocol exchange after the user becomes authenticated.

34. The user authentication system according to claim 32, wherein the second node permits the first node access to the LAN backbone for data exchange after the user becomes authenticated.

35. A user authentication system for a communication network, comprising:

a first node being used by a user; and

a second node communicating with the first node over a LAN link, the second node providing an exclusive point of access for the first node to the network, wherein the network is an institutional communication network and wherein prior to the user becoming authenticated the second node permits the first node access to the network solely for conducting an authentication protocol exchange with the user.

36. The user authentication system according to claim 35, wherein after the user becomes authenticated the second node permits the first node access to the network for data exchange.

37. A user authentication method for a communication network having a plurality of nodes, the method comprising:

entering on a first node first user identification information;

transmitting to an authentication agent on a second node communicating with the first node over a LAN link the first user identification information;

relaying from the authentication agent to an authentication server the first user identification information;

comparing on the authentication server the first user identification information with user identification information in a database of user identification information;

transmitting from the authentication server to the authentication agent, the result of the comparison;

transmitting from the authentication server to the authentication agent a list of network resources for which the user is authorized if the result is a match; and

associating a list of network resources with the first node if the result is a match.

38. The user authentication method of claim 37 further comprising filtering and forwarding packets between the first node and the network resources of the list according to the association if the result is a match.

39. The user authentication method of claim 38 further comprising dropping packets between the first node and other nodes if the result is a mismatch.

40. A user authentication method for a communication network having a plurality of nodes, the method comprising:

entering on a first node first user identification information;

transmitting to an authentication agent on a second node the first user identification information;

relaying from the authentication agent to an authentication server the first user identification information;

comparing on the authentication server the first user identification information with user identification information in a database of user identification information;

transmitting from the authentication server to the authentication agent, the result of the comparison;

transmitting from the authentication server to the authentication agent a list of network resources for which the user is authorized if the result is a match;

associating a list of network resources with the first node if the result is a match;

forwarding packets between the first node and a destination node if the result is a match and the nodes share a common VLAN;

dropping packets between the first node and a destination node if the result is not a match; and

dropping packets between the first node and a destination node if the nodes do not share a common VLAN.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
Certificate

Patent No. 6,339,830 Patented: January 15, 2002

On petition requesting issuance of a certificate for correction of inventorship pursuant to 35 U.S.C. 256, it has been found that the above identified patent, through error and without any deceptive intent, improperly sets forth the inventorship.

Accordingly, it is hereby certified that the correct inventorship of this patent is: Michael E. See, Chapel Hill, NC; John W. Bailey, Agoura Hills, CA; Charles L. Panza, Park City, UT; Yuri Pikover, Malibu, CA; Geoffrey C. Stone, Malibu, CA; Michelle Wright Goodwin, Calabasas, CA.

Signed and Sealed this Eleventh Day of March 2003.

ROBERT W. BEAUSOLIEL, JR.
Supervisory Patent Examiner
Art Unit 2184