IN THE UNITED STATES DISTRICT COURT
FOR THE DISTRICT OF DELAWARE

REMBRANDT TECHNOLOGIES, LP,	)	
Plaintiff,	)	
v.	)	C.A. No. _____
CBS CORPORATION,	)	
Defendant.	)	

COMPLAINT FOR PATENT INFRINGEMENT
AND DEMAND FOR JURY TRIAL

Rembrandt Technologies, LP ("Rembrandt"), for its complaint against CBS Corporation ("CBS" or "Defendant"), alleges as follows:

PARTIES

1. Rembrandt is a limited partnership organized under the laws of the State of New Jersey, having its principal place of business at 401 City Avenue, Suite 815, Bala Cynwyd, PA 19004.

2. CBS is a corporation organized under the laws of the State of Delaware, having its principal place of business at 51 West 52nd Street, 35th Floor, New York, NY 10019.

JURISDICTION AND VENUE

3. This is an action arising under the patent laws of the United States, Title 35, United States Code. This Court has subject matter jurisdiction over this case under 28 U.S.C. §§ 1331 and 1338(a).

4. This Court has personal jurisdiction over CBS. Defendant is incorporated in the State of Delaware, and has conducted and does conduct business within the State of Delaware. Defendant, directly or through subsidiaries or intermediaries, offers for sale, sells, advertises, and markets products and services that infringe the patent-in-suit, as described more specifically below. Therefore, because Defendant has committed acts of patent infringement in this district, or is otherwise present or doing business in this district, this Court has personal jurisdiction over Defendant.

5. Venue is proper in this judicial district under 28 U.S.C. §§ 1391(b), (c), and 1400(b).

INFRINGEMENT OF U.S. PATENT NO. 5,243,627

6. Rembrandt realleges and incorporates herein by reference the allegations stated in paragraphs 1-5 of this Complaint.

7. United States Patent No. 5,243,627 entitled "Signal Point Interleaving Technique" ("the '627 patent") was duly and legally issued by the United States Patent & Trademark Office on September 7, 1993. A copy of the '627 patent is annexed hereto as Exhibit A.

8. Rembrandt is the owner of all right, title and interest in the '627 patent, with the right to sue, enforce and recover damages for infringement.

9. CBS operates television systems and provides television services throughout the United States.

10. Defendant has directly or indirectly infringed the '627 patent, and is continuing to do so, by practicing the inventions claimed therein, and/or by inducing or contributing to the practice by others of the inventions claimed therein, in this judicial district. For example, Defendant has infringed, and continues to infringe, the '627 patent by its transmission, or receipt and retransmission, over its television systems, of digital terrestrial broadcast signals that comply with the ATSC Digital Television Standard.

11. Rembrandt has been damaged by Defendant's infringement and will suffer additional and irreparable damage unless this Court enjoins Defendant from continuing its infringement under 35 U.S.C. § 283.

12. Upon information and belief, such infringement has been, and will continue to be, willful and deliberate, entitling Rembrandt to increased damages under 35 U.S.C. § 284 and making this an exceptional case entitling Rembrandt to an award of reasonable attorneys' fees pursuant to 35 U.S.C. § 285.

PRAYER FOR RELIEF

WHEREFORE, Rembrandt respectfully requests the following relief:

(1) the entry of judgment in favor of Rembrandt, and against Defendant, that Defendant has infringed the '627 patent;

(2) a permanent injunction enjoining and restraining Defendant and its officers, agents, servants, employees, affiliates, divisions, units and subsidiaries, and those in association therewith, from further acts of infringement of the '627 patent;

(3) an award of damages;

(4) an award of increased damages pursuant to 35 U.S.C. § 284;


(5) an award of all costs and expenses of this action, including reasonable attorneys' fees, pre-judgment interest, and post-judgment interest; and

(6) such other and further relief, at law and in equity, as the Court deems just and proper.

JURY DEMAND

Rembrandt hereby respectfully requests a jury trial on all issues so triable.

ASHBY & GEDDES



Steven J. Balick (I.D. #2114)
John G. Day (I.D. #2403)
Lauren E. Maguire (I.D. #4261)
222 Delaware Avenue, 17th Floor
P.O. Box 1150
Wilmington, DE 19899
(302) 654-1888
sbalick@ashby-geddes.com
jday@ashby-geddes.com
lmaguire@ashby-geddes.com

Attorneys for Plaintiff

Of Counsel:

John F. Sweeney
Joseph A. DeGirolamo
Michael O. Cummings
MORGAN & FINNEGAN, LLP
3 World Financial Center
New York, NY 10281-2101
Telephone: (212) 415-8700
jsweeney@morganfinnegan.com
jdegirolamo@ morganfinnegan.com
mcummings@morganfinnegan.com

Dated: December 1, 2006
175613.1

EXHIBIT A

US005243627A

United States Patent [19]

Betts et al.

[11] Patent Number: 5,243,627

[45] Date of Patent: Sep. 7, 1993

[54] SIGNAL POINT INTERLEAVING TECHNIQUE

[75] Inventors: William L. Betts, St. Petersburg; Edward S. Zuranski, Largo, both of Fla.

[73] Assignee: AT&T Bell Laboratories, Murray Hill, N.J.

[21] Appl. No.: 748,594

[22] Filed: Aug. 22, 1991

[51] Int. Cl.[5] H04L 5/12

[52] U.S. Cl. 375/39; 375/60; 375/99; 371/43

[58] Field of Search 375/39, 58, 60, 99; 371/43, 37.5, 2.1, 45; 341/81

[56] References Cited

U.S. PATENT DOCUMENTS

3,988,677	10/1976	Fletcher et al.	371/45 X
4,677,624	6/1987	Betts et al.	375/39
4,945,549	7/1990	Simon et al.	375/53
5,029,185	7/1991	Wei	375/39 X

Primary Examiner—Curtis Kuntz
Assistant Examiner—Tesfaldet Bocure
Attorney, Agent, or Firm—Ronald D. Slusky; Gerard A. deBlasi

[57] ABSTRACT

Viterbi decoder performance in a data communication system using 2N-dimensional channel symbols N>1 can be further enhanced by an interleaving technique which uses a distributed trellis encoder in combination with a signal point interleaver.

24 Claims, 4 Drawing Sheets




FIG. 1

PRIOR ART




FIG. 2





FIG. 3


DTE
RANDOMIZER
S/P
MODULUS CONVERTER
4D QAM ENCODER
DELAY
SIGNAL POINT INTERLEAVER
MODULATOR
TO CHANNEL
SWITCHING CIRCUIT
4D TRELLIS ENCODER
SYMBOL CLOCK
INDEX VALUES
UNCODED BITS
TRELLIS BITS



FROM CHANNEL
DEMODULATOR/ EQUALIZER
PHASE TRACKING LOOP
SIGNAL POINT DEINTERLEAVER
SWITCHING CIRCUIT
SWITCHING CIRCUIT
SWITCHING CIRCUIT
4D VITERBI DECODER
4D VITERBI DECODER
4D VITERBI DECODER
SYMBOL CLOCK
MODULUS DECONVERTER
DELAY
DERANDOMIZER
DTE
UNCODED BITS
INDEX VALUES
DECODED TRELLIS BITS

FIG. 4

FIG. 5

		4D SYMBOL	4D SYMBOL	4D SYMBOL	4D SYMBOL	4D SYMBOL	4D SYMBOL
I	NOT INTERLEAVED ONE TRELLIS STAGE	$X_0^\alpha\ X_1^\alpha$	$X_2^\alpha\ X_3^\alpha$	$X_4^\alpha\ X_5^\alpha$	$X_6^\alpha\ X_7^\alpha$	$X_8^\alpha\ X_9^\alpha$	X_{10}^α ...
II	NOT INTERLEAVED THREE TRELLIS STAGES	$X_0^\alpha\ X_1^\alpha\ X_2^\beta\ X_3^\beta\ X_4^\gamma\ X_5^\gamma$	$X_6^\alpha\ X_7^\alpha\ X_8^\beta\ X_9^\beta\ X_{10}^\gamma$ ...				
III	INTERLEAVED ONE TRELLIS STAGE	$X_0^\alpha\ X_{-1}^\alpha\ X_2^\alpha\ X_1^\alpha\ X_4^\alpha\ X_3^\alpha$	$X_6^\alpha\ X_5^\alpha\ X_8^\alpha\ X_7^\alpha\ X_{10}^\alpha$ ...				
IV	INTERLEAVED TWO TRELLIS STAGES	$X_0^\alpha\ X_{-1}^\beta\ X_2^\beta\ X_1^\alpha\ X_4^\alpha\ X_3^\beta$	$X_6^\beta\ X_5^\alpha\ X_8^\alpha\ X_7^\beta\ X_{10}^\beta$ ...				
V	INTERLEAVED THREE TRELLIS STAGES	$X_0^\alpha\ X_{-1}^\gamma\ X_2^\beta\ X_1^\alpha\ X_4^\gamma\ X_3^\beta$	$X_6^\alpha\ X_5^\gamma\ X_8^\beta\ X_7^\alpha\ X_{10}^\gamma$ ...				

FIG. 6





FIG. 7



SIGNAL POINT INTERLEAVING TECHNIQUE

BACKGROUND OF THE INVENTION

The present invention relates to the transmission of digital data over band-limited channels.

Over the years, the requirements of modern-day digital data transmission over band-limited channels—such as voiceband telephone channels—have resulted in a push for higher and higher bit rates. This push has led to the development and introduction of such innovations as adaptive equalization, multi-dimensional signal constellations, echo cancellation (for two-wire applications), and trellis coding. Today, the data rates achieved using these and other techniques are beginning to approach the theoretical limits of the channel.

It has been found that various channel impairments, whose effects on the achievable bit rate were relatively minor compared to, say, additive white Gaussian noise and linear distortion, have now become of greater concern. These include such impairments as nonlinear distortion and residual (i.e., uncompensated-for) phase jitter. Such impairments are particularly irksome in systems which use trellis coding. Indeed, it has been found that the theoretical improvement in Gaussian noise immunity promised by at least some trellis codes is not realized in real-world applications where these impairments are manifest. The principal reason this is so appears to be that the noise components introduced into the received signal samples are such as to worsen the effectiveness of the Viterbi decoder used in the receiver to recover the transmitted data.

U.S. Pat. No. 4,677,625, issued Jun. 30, 1987 to Betts et al, teaches a method and arrangement in which, through the use of a distributed trellis encoder/Viterbi decoder, the effects of many of these impairments can be reduced. The invention in the Betts et al patent recognizes that a part of the reason that the performance of the Viterbi decoder is degraded by these impairments is the fact that the noise components of channel symbols which closely follow one another in the transmission channel are highly correlated for many types of impairments. And it is that correlation which worsens the effect that these impairments have on the Viterbi decoder. Among the impairments whose noise is correlated in this way are impulse noise, phase "hits" and gain "hits." All of these typically extend over a number of adjacent channel symbols in the channel, and thus all result in channel symbol noise components which are highly correlated. The well-known noise enhancement characteristics of linear equalizers also induce correlated noise in adjacent channel symbols, as does uncompensated-for phase jitter. Also, the occurrence of one of the relatively high power points of the signal constellation can, in pulse code modulation (PCM) systems, for example, give rise to noise on adjacent channel symbols which, again, is correlated.

The Betts et al patent addresses this issue by distributing the outgoing data to a plurality of trellis encoders in round-robin fashion and interleaving the trellis encoder outputs on the transmission channel. In the receiver, the stream of received interleaved channel symbols is correspondingly distributed to a plurality of trellis decoders. Since the successive pairs of channel symbols applied to a particular trellis decoder are separated from one another as they traverse the channel, the correlation of the noise components of these channel symbol pairs is reduced from what it would have otherwise been.

SUMMARY OF THE INVENTION

In accordance with the present invention, it has been realized that the Viterbi decoder performance in a data communication system using 2N-dimensional channel symbols can be further enhanced by an interleaving technique which uses, in combination, a) the aforementioned distributed trellis encoder/Viterbi decoder technique and b) a signal point interleaving technique which causes the constituent signal points of the channel symbols to be non-adjacent as they traverse the channel.

In preferred embodiments of the invention, the interleaving is carried out in such a way that every N^{th} signal point in the signal point stream traversing the channel is the N^{th} signal point of a respective one of the channel symbols. This criterion enhances the accuracy with which the phase tracking loop in the receiver performs its function.

Also in preferred embodiments, we have found that the use of three parallel trellis encoders in conjunction with a signal point interleaving regime in which the signal points of each channel symbol are separated from one another by three signaling intervals (bauds) provides an optimum or near-optimum tradeoff between signal point/channel symbol separation and the decoding delay that is caused by the interleaving.

BRIEF DESCRIPTION OF THE DRAWING

In the drawing,

FIG. 1 is a block diagram of the transmitter section of a prior art modem;

FIG. 2 is shows a signal constellation used by the transmitter of FIG. 1;

FIG. 3 is a block diagram of the transmitter section of a modem employing four-dimensional channel symbols and embodying the principles of the invention;

FIG. 4 is a block diagram of the receiver section of a modem embodying the principles of the invention which processes the received four-dimensional channel symbols generated by the transmitter of FIG. 3;

FIG. 5 is a signal point timing/sequencing chart helpful in explaining the principles of the present invention;

FIG. 6 is a signal point interleaver which can be used in the transmitter of FIG. 3 to interleave the signal points of eight-dimensional channel symbols; and

FIG. 7 is a signal point deinterleaver which can be used in the receiver of FIG. 4 to deinterleave the signal points of eight-dimensional channel symbols.

DETAILED DESCRIPTION

FIG. 1 depicts the transmitter section of a prior art modem employing a 2N-dimensional signaling scheme, $N \geq 1$. The modem receives input information in the form of a serial bit stream from data terminal equipment (DTE) **111**—illustratively a host computer. That bit stream is then scrambled, or randomized, by randomizer **113** whose output bits are provided in serial form to serial-to-parallel (S/P) converter **115**.

Serial-to-parallel converter **115**, in turn, provides, during each of a succession of symbol intervals (comprised of N baud intervals), some predetermined number of parallel bits on lead **109** and some number of parallel bits on lead **108**. (It will be appreciated that whenever bits are provided in parallel in the modem, separate leads are required to carry each of the bits.) The bits on lead **109** are applied to trellis encoder **119**a,

and are referred to as the "trellis bits." The bits on lead **108** are applied to modulus converter **116**, and are referred to as the "uncoded bits."

To better understand how trellis encoder **119**α and modulus converter **116** work, reference is made to FIG. **2**, which shows the two-dimensional signal constellation that forms the basis of the 2N-dimensional signaling scheme illustratively used by the modem. This constellation is comprised of 32 signal points, which are divided into four subsets, A through D, each comprised of eight signal points. The eight points of subset A are explicitly labeled as A_0 through A_7. It may be noted that subsets C, B and D can be arrived at by clockwise rotation of subset A by 90, 180 and 270 degrees, respectively. (Conventional differential encoding circuitry within trellis encoder **119**α exploits this symmetry.) For reference, a single signal point of each of those subsets is also shown on FIG. **2**.

Consider, first, the case of N=1, i.e., a two-dimensional signaling scheme. In this case, one trellis bit on lead **109** would be expanded to two bits by trellis encoder **119**α on lead **121**. The four possible values of those three bits **00**, **01**, **10**, and **11** identify subsets A, B, C and D, respectively. The successive 2-bit words on lead **121** are represented as α_n, n=0,1,2. . . , where n is an index that advances at the baud rate. At the same time, three parallel bits would be provided on lead **108**. These are converted by modulus converter **116** into an index having a value within the range (decimal) 0 to 7. The index value, represented in binary form on lead **117**, selects a particular signal point from the subset identified on lead **121**. Thus if lead **121** carries the two bits **00** while lead **117** carries the three bits **001**, then signal point A_1 of the FIG. **2** constellation has been selected. The words on leads **117** and **121** are applied to QAM encoder **124** which generates, on lead **125**, values representing the I (in-phase) and Q (quadrature-phase) components of signal point A_1. The signal point generated on lead **125** in the n^{th} baud interval is denoted X_n^{α}, which is passed on to modulator **128** to generate a passband line signal which is applied to the communication channel. The superscript, α, indicates that the trellis encoder that was used to identify the subset for any particular signal point was trellis encoder **119**α. That is, of course, a trivial notation as far as FIG. **1** goes inasmuch as trellis encoder **119**α is the only trellis encoder in the modem. However, it is useful to introduce this notation because more than one trellis encoder stage is used in preferred embodiments of modems incorporating the principles of the present invention as shown in later FIGS.

In the case of N>1, the operation is similar. Now, however, the words on lead **109** are used by trellis encoder **119**α to sequentially identify on lead **121**N subsets, while the words on lead **108** are used to generate N corresponding index values on lead **117**. The N signal points identified in this way are the component signal points of a 2N-dimensional channel symbol, the first such symbol being comprised of the signal points X_0^{α}, . . . $X_{(N-1)}^{\alpha}$. For example, a modem in which the transmitter of FIG. **1** could be used may be a 14,400 bit per second modem using four-dimensional coding (i.e., N=2) and a baud rate of 3200. In this case, nine bits from S/P converter **115** are used for each four-dimensional symbol. Specifically, three parallel bits on lead **109** are expanded into four bits on lead **121** to identify a pair of subsets while six bits on lead **108** are used to select particular signal points from those two subsets. Those two signal points are thereupon communicated over the channel by QAM encoder **124** and modulator **128** as described above.

Note that, implementationally, the 2N-dimensional channel symbol is generated by having the trellis encoder identify, interdependently, N subsets of the two-dimensional constellation of FIG. **2**, then select a two-dimensional signal point from each of the subsets thus identified. The concatenation of the N two-dimensional signal points thus selected is the desired 2N-dimensional channel symbol. This process, however, can be understood as involving the direct selection of a 2N-dimensional channel symbol. Viewed in this context, the set of all possible combinations of N of the two-dimensional subsets identified by N successive trellis encoder outputs can be understood to be a set of 2N-dimensional subsets of a 2N-dimensional constellation, the latter being comprised of all possible combinations of N of the signal points of the two-dimensional constellation. A succession of N outputs from the trellis encoder identifies a particular one of the 2N-dimensional subsets and a succession of N outputs from the modulus converter selects a particular 2N-dimensional signal point from the identified 2N-dimensional subset.

Modulus converter **116** is illustratively of the type disclosed in co-pending, commonly-assigned U.S. patent application Ser. No. 588,658 filed Sep. 26, 1990 and allowed on May 21, 1991, hereby incorporated by reference. Modulus converter **116** provides the modem with the ability to support data transmission at various different bit rates. Assume, for example, that the rate at which bits are provided by DTE **111** decreases. The serial-to-parallel converter will continue to provide its outputs on leads **108** and **109** at the same baud rate as before. However, the upper limit of the range of index values that are provided by modulus converter **116** on lead **117** will be reduced, so that, effectively, each of the four subsets A through D, instead of having eight signal points, will have some smaller number. Conversely if the rate at which bits are provided by DTE **111** should increase over that originally assumed, the upper limit of the range of index values, and thus the number of parallel bits, that appear on lead **117** will be increased beyond eight and the constellation itself will be expanded to accommodate the larger number of signal points thus being selected. As an alternative to using a modulus converter, fractional bit rates can be supported using, for example, the technique disclosed in L. Wei, "Trellis-Coded Modulation with Multidimensional Constellations," *IEEE Trans. on Communication Theory*, Vol. IT-33, No. 4, July 1987, pp. 483–501.

Turning now to FIG. **3**, the transmitter portion of a modem embodying the principles of the invention is shown. This embodiment illustratively uses the aforementioned four-dimensional, i.e., N=2, signaling scheme. Many of the components are similar to those shown in FIG. **1**. Thus, in particular, the transmitter of FIG. **3**—which receives its input information in the form of a stream of input bits from DTE **311**—includes randomizer **313**, which supplies its output, on lead **314**, to S/P converter **315**. The latter outputs uncoded bits to modulus converter **316**. The transmitter further includes four-dimensional QAM encoder **324** and modulator **328**. The trellis bits, on lead **309**, are provided not to a standard single trellis encoder, but to a distributed trellis encoder comprised of three trellis encoder stages: trellis encoder stage **319**α, trellis encoder stage **319**β, and trellis encoder stage **319**γ.

Such a distributed trellis encoder, which is described in the aforementioned Betts et al patent, generates a plurality of streams of trellis encoded channel symbols in response to respective portions of the input information. Specifically, a three-bit word on lead **309** is supplied to trellis encoder stage **319**α. The next three-bit word on lead **309** is supplied to trellis encoder stage **319**β. The next three-bit word is supplied to trellis encoder stage **319**γ, and then back to trellis encoder stage **319**α. This distribution of the trellis bits to the various trellis encoder stages is performed by switching circuit **331** operating under the control of symbol clock **325**. The initial data word outputs of the trellis encoders are subset identifiers α_0 and α_1 for encoder stage **319**α, β_2 and β_3 for encoder stage **319**β, and γ_4 and γ_5 for encoder stage **319**γ, followed by α_6 and α_7 for encoder stage **319**α, and so forth. These are supplied to four-dimensional QAM encoder **324** by switching circuit **337**—also operating under the control of symbol clock **325**—on lead **338** through a one-symbol delay **364** and lead **363**, in order to compensate for a one-symbol delay caused by modulus converter **316**. Thus, the stream of subset identifiers on lead **338** is $\alpha_0, \alpha_1, \beta_2, \beta_3, \gamma_4, \gamma_5, \alpha_6 \ldots$. Using the notation introduced above, then, the output of encoder **324** on lead **325** is the stream of signal points $X_0^\alpha, X_1^\alpha, X_2^\beta, X_3^\beta, X_4^\gamma, X_5^\gamma, X_6^\alpha \ldots$, which is comprised of three interleaved streams of trellis encoded channel symbols, these streams being $X_0^\alpha, X_1^\alpha, X_6^\alpha, X_7^\alpha, X_{12}^\alpha \ldots$; $X_2^\beta, X_3^\beta, X_8^\beta, X_9^\beta, X_{14}^\beta \ldots$; and $X_4^\gamma, X_5^\gamma, X_{10}^\gamma, X_{11}^\gamma, X_{16}^\gamma \ldots$. These, in turn, are supplied, in accordance with the invention, to signal point interleaver **341** which applies alternate ones of the signal points applied thereto to lead **3412**—which signal points appear immediately at the interleaver output on lead **342**—and to one-symbol (Z^{-1}) delay element **3411**, which appear on lead **342** after being delayed therein by one symbol interval. The resulting interleaved stream of trellis encoded signal points is $X_0^\alpha, X_{-1}^\gamma, X_2^\beta, X_1^\alpha, X_4^\gamma, X_3^\beta, X_6^\alpha, X_5^\gamma, X_8^\beta, X_7^\alpha, X_{10}^\gamma, X_9^\beta \ldots$ (the signal point X_{-1}^γ being, of course, the signal point applied to interleaver **341** just ahead of signal point X_0^α).

A discussion and explanation of how the interleaving just described is advantageous is set forth hereinbelow. In order to fully set the stage for that explanation, however, it will be first useful to consider the receiver section of a modem which receives the interleaved signal point stream.

Thus referring to FIG. **4**, the line signal transmitted by the transmitter of FIG. **3** is received from the channel and applied to demodulator/equalizer **455** which, in conventional fashion—including an input from phase tracking loop **457**—generates a stream of outputs on lead **456** representing the demodulator/equalizer's best approximation of the values of the I and Q components of the signal points of the transmitted interleaved signal point stream. These outputs are referred to herein as the "received signal points." (Due to distortion and other channel impairments that the demodulator/equalizer is not able to compensate for, the I and Q components of the received signal points, instead of having exact integer values, can have any value. Thus a transmitted signal point having coordinates (3, −5) may be output by the demodulator/equalizer as the received signal point (2.945, −5.001).) The stream of received signal points on lead **456** is denoted $\overline{X}_0^\alpha, \overline{X}_{-1}^\gamma, \overline{X}_2^\beta, \overline{X}_1^\alpha, \overline{X}_4^\gamma, \overline{X}_3^\beta, \overline{X}_6^\alpha, \overline{X}_5^\gamma, \overline{X}_8^\beta, \overline{X}_7^\alpha, \overline{X}_{10}^\gamma, \overline{X}_9^\beta \ldots$.

The successive received signal points are deinterleaved in signal point deinterleaver **441**, which provides the opposite function to interleaver **341** in the transmitter. The output of deinterleaver **441** on lead **442** is thus $\overline{X}_0^\alpha, \overline{X}_1^\alpha, \overline{X}_2^\beta, \overline{X}_3^\beta, \overline{X}_4^\gamma, \overline{X}_5^\gamma, \overline{X}_6^\alpha, \ldots$, etc. (Although not explicitly shown in the drawing, the same well-known techniques used in modems of this general kind to identify within the stream of received signal points the boundaries between successive symbols is used to synchronize the operation of signal point deinterleaver **441** to ensure that received signal points $\overline{X}_0^\alpha, \overline{X}_2^\beta, \overline{X}_4^\gamma \ldots$ are applied to delay element **4411** while received signal points $\overline{X}_1^\alpha, \overline{X}_3^\beta, \overline{X}_5^\gamma \ldots$ are applied to lead **4412**.)

The received signal points on lead **442** are then distributed by switching circuit **431** under the control of symbol clock **425** to a distributed Viterbi decoder comprised of 4D Viterbi decoder stages **419**α, **419**β and **419**γ. Specifically, received signal points $\overline{X}_0^\alpha$ and $\overline{X}_1^\alpha$ are applied to decoder stage **419**α; received signal points $\overline{X}_2^\beta$ and $\overline{X}_3^\beta$ are applied to decoder stage **419**β; and received signal points $\overline{X}_4^\gamma$ and $\overline{X}_5^\gamma$ are applied to decoder stage **419**γ. The outputs of the three decoder stages are then combined into a serial stream on lead **438** by switching circuit **437**, also operating under the control of symbol clock **425**. Those outputs, representing decisions as to the values of the transmitted signal points, are denoted $\hat{X}_0, \hat{X}_1, \hat{X}_2, \hat{X}_3, \hat{X}_4, \hat{X}_5, \hat{X}_6, \ldots$, the α, β and γ superscripts no longer being needed.

In conventional fashion, the bits that represent each of the decisions on lead **438** can be divided into bits that represent a) the trellis bits that appeared on transmitter lead **309** and b) the index values that appeared on transmitter lead **317**. Those two groups of bits are provided in the receiver on leads **461** and **462**, respectively. The latter group of bits are deconverted by modulus deconverter **416** (also disclosed in the aforementioned '658 patent application) back to uncoded bit values on lead **414**. The operation of the modulus deconverter imparts a one-symbol delay to the bits on lead **414**. Accordingly, the bits on lead **461** are caused to be delayed by one symbol by delay element **464**. The resulting combined bits on lead **415** thus represent the stream of bits that appeared at the output of randomizer **313** in the transmitter. These are derandomized in the receiver by derandomizer **413** and the resulting derandomized bit stream is applied to DTE **411** which may be, for example, a computer terminal.

Referring to FIG. **5**, one can see the improvement that is achieved by the present invention.

Line I shows the stream of output signal points generated and launched into the channel using one stage of trellis encoding and no signal point interleaving. This is, of course, the prior art arrangement shown in FIG. **1**. Line II shows the effect of providing a three-stage distributed trellis encoder but still no signal point interleaving. This is the arrangement shown in the aforementioned Betts et al patent. Note that the signal points of each channel symbol operated on by a particular trellis encoder stage are adjacent in the output signal point stream. For example, the second signal point of the symbol $X_0^\alpha X_1^\alpha$—namely signal point X_1^α—is separated by five baud intervals from the first (closer) signal point of the symbol $X_6^\alpha X_7^\alpha$—namely signal point X_6^α. As noted earlier, such separation is advantageous because the channel symbols which are processed one after the other in a particular Viterbi decoder stage have noise components which are not highly correlated.

Note, however, that the individual signal points of each channel symbol, e.g., X_0^α and X_1^α, are adjacent to

one another as they pass through the channel; and since all the signal points of a channel symbol must be processed serially in the same Viterbi decoder stage, this means that the Viterbi decoder must process adjacent signal points that have highly correlated noise components.

It is to this end that signal point interleaver **341** is included within the transmitter in accordance with the invention. Firstly, it may be noted from Line III that using the signal point interleaver without the distributed trellis encoder—an arrangement not depicted in the drawing—will, advantageously, cause the signal points from the same channel symbol to be non-adjacent. Moreover, there is further advantage in that a pair of channel symbols processed serially by Viterbi decoder stage **419**α traverses the channel separated by five baud intervals rather than three, thereby providing greater decorrelation of the noise components thereof. Compare, for example, the span of baud intervals occupied by signal points X_0^{α} and X_1^{α}, X_2^{α} and X_3^{α} in Line I and the span of baud intervals occupied by the same signal points in Line III. Disadvantageously, however, the use of a single trellis encoding stage brings back the problem that the distributed trellis encoder solves, as described above. Thus, for example, although signal points X_0^{α} and X_1^{α}, which are from the same channel symbol, are separated from one another when traversing the channel, we find that, disadvantageously, signal points X_2^{α} and X_1^{α}, which are signal points from two different channel symbols which will be processed serially by the Viterbi decoder, traverse the channel adjacent to one another.

Line IV shows that using the signal point interleaver with a two-stage trellis encoder—also an arrangement not depicted in the drawing—provides some improvement. Firstly, it may be noted that, as in Line III, signal points from the same channel symbol remain separated by three baud intervals. Additionally, pairs of channel symbols processed sequentially by a given Viterbi decoder stage—such as the channel symbols comprised of signal points X_0^{α} and X_1^{α}, X_4^{α} and X_5^{α}—are still non-adjacent and, indeed, are now separated by seven baud intervals, which is even greater than the separation of five baud intervals provided in Line III. Moreover, certain signal points that traverse the channel adjacent to one another and which are from channel symbols which would have been decoded sequentially in the one-trellis-encoding-stage case are, in the two-trellis-encoding-stage case of Line IV, processed by different Viterbi decoding stages. Signal points X_2^{β} and X_1^{α} are such a pair of signal points. Note, however, that, disadvantageously, signal points X_1^{α} and X_4^{α} traverse the channel serially, and are from channel symbols which are serially processed by the "α" Viterbi decoder stage.

Referring, however, to Line V, which depicts the stream of signal points output by the transmitter of FIG. **3**, it will be seen that, in accordance with the invention, there is still a non-adjacency—indeed, a separation of at least three baud intervals—between a) the signal points which belong to any particular channel symbol (and which, therefore, are processed serially by a particular Viterbi decoder stage) and b) the signal points which belong to channel symbols which are processed serially by a Viterbi decoder stage. Thus, for example, signal points X_1^{α} and X_4^{γ} are now processed by different Viterbi decoder stages. Moreover, pairs of channel symbols processed sequentially by a given Viterbi decoder stage—such as the channel symbols comprised of signal points X_0^{α} and X_1^{α}, X_6^{α} and X_7^{α}—are now separated by none baud intervals.

Using more than three trellis encoder stages in the distributed trellis encoder and/or a signal point interleaver that separates signal points from the same channel symbol by more than three baud intervals would provide even greater separation and could, therefore, potentially provide even greater improvement in Viterbi decoding. However, such improvement comes at a price—that price being increased decoding delay—particularly as the number of trellis encoders is increased beyond three. An engineering trade-off can be made, as suits any particular application.

Moreover, it is desirable for the signal point interleaver to provide a sequence in which every N^{th} signal point in the interleaved signal point stream is the N^{th} signal point of a channel symbol. (The reason this is desirable is described in detail hereinbelow.) In the case of an N=2, four-dimensional signaling scheme, this means that every second, that is "every other," signal point in the interleaved stream is the second signal point of the channel symbol from which it comes. In the case of an N=4, eight-dimensional signaling scheme, this means that every fourth signal point in the interleaved stream is the fourth signal point of the channel symbol from which it comes. Indeed, this criterion is in fact satisfied in the embodiment of FIG. **3**. Note that each one of signal points X_0^{α}, X_2^{β}, X_4^{γ}, X_6^{α}, . . . , which appear as every other signal point in the interleaved stream, is the second signal point of one of the four-dimensional channel symbols. Note that not all rearrangements of the signal points will, in fact, satisfy this criterion, such as, if the two signal points of a channel symbol are separated by two, rather than three, baud intervals.

Satisfying the above criterion is advantageous because it enhances the accuracy with which phase tracking loop **457** performs its function. This is so because the arrival of an N^{th} signal point of a given symbol means that all the signal points comprising that channel symbol have arrived. This, in turn, makes it possible to form a decision as to the identity of that channel symbol by using the minimum accumulated path metric in the Viterbi decoder stages. (Those decisions are fed back to the tracking loop by decoder stages **419**α, **419**β **419**γ on leads **494**, **495** and **496**, respectively, via switching circuit **456**.) Without having received all of the signal points of a channel symbol, one cannot take advantage of the accumulated path metric information but, rather, must rely on the so-called raw sliced values, which is less accurate. By having every N^{th} signal point in the interleaved stream be the N^{th} signal point of a channel symbol, we are guaranteed that the time between adjacent such path metric "decisions" supplied to the phase tracking loop is, advantageously, never more than N baud intervals.

The foregoing merely illustrates the principles of the invention. Thus although the illustrative embodiment utilizes a four-dimensional signaling scheme, the invention can be used with signaling schemes of any dimensionality. In the general, 2N-dimensional, case each stage of the distributed trellis encoder would provide N two-dimensional subset identifiers to switching circuit **337** before the latter moves on to the next stage. And, of course, each stage of the distributed Viterbi decoder would receive N successive received signal points. The distributed trellis encoder and distributed Viterbi decoder can, however, continue to include three trellis

encoders and still maintain, independent of the value of N, a separation of three baud intervals in the channel between signal points that are from channel symbols that are adjacent in the trellis encoder. If a greater separation of such signal points is desired, more stages can be added to the distributed trellis encoder/Viterbi decoder, just as was noted above for the four-dimensional case. However, when dealing with 2N-dimensional signaling where N>2, it is necessary to add additional delay elements to the signal point interleaver/deinterleaver in order to maintain a three-baud-interval separation among the signal points from any given channel symbol.

Consider, for example, the case of N=4, i.e., an eight-dimensional case. Looking again at FIG. 3, the three (8D) stages of the distributed trellis encoder would generate the three streams of subset identifiers $\alpha_0\,\alpha_1\,\alpha_2\,\alpha_3\,\alpha_{12}\ldots$, $\beta_4\,\beta_5\,\beta_6\,\beta_7\,\beta_{16}\ldots$, and $\gamma_8\,\gamma_9\,\gamma_{10}\,\gamma_{11}\,\gamma_{20}\ldots$, respectively. This would lead to the following stream of signal points of eight-dimensional trellis encoded channel symbols at the output of the QAM encoder on lead 325: $X_0^{\alpha}\,X_1^{\alpha}\,X_2^{\alpha}\,X_3^{\alpha}\,X_4^{\beta}\,X_5^{\beta}\,X_6^{\beta}\,X_7^{\beta}\,X_8^{\gamma}\,X_9^{\gamma}X_{10}^{\gamma}\,X_{11}^{\gamma}\,X_{12}^{\alpha}\ldots$ Signal point interleaving could be carried out by substituting signal point interleaver 641 of FIG. 6 for interleaver 341. Interleaver 641, in addition to direct connection 6414, includes one-, two-, and three-symbol delay elements 6413, 6412 and 6411, respectively.

The signal points on lead 325, after passing through interleaver 641, would appear on lead 342 in the following order: $X_0^{\alpha}\,X_{-3}^{\gamma}\,X_{-6}^{\beta}\,X_{-9}^{\alpha}\,X_4^{\beta}\,X_1^{\alpha}\,X_{-2}^{\gamma}\,X_{-5}^{\beta}\,X_8^{\gamma}\,X_5^{\beta}\,X_2^{\alpha}\,X_{-1}^{\gamma}\,X_{12}^{\alpha}\,X_9^{\gamma}\,X_6^{\beta}\,X_3^{\alpha}\,X_{16}^{\beta}\,X_{13}^{\alpha}\,X_{10}^{\gamma}\,X_7^{\beta}\ldots$ where signal points with negative subscripts are, of course, signal points that arrived before signal point X_0^{α} and were already stored in the delay elements 6411, 6412 and 6413. Examination of this signal point stream will reveal that there is either a three- or five-baud separation between signal points of channel symbols that are processed sequentially by the same trellis encoder stage, e.g., X_3^{α} and X_{12}^{α}; that adjacent signal points of any one channel symbol, e.g., X_0^{α} and X_1^{α}, are separated by five baud intervals; and that the four signal points comprising any particular one channel symbol are separated by fifteen baud intervals.

FIG. 7 shows the structure of a deinterleaver 741 that could be used in the receiver of FIG. 4 in place of deinterleaver 441 in order to restore the signal points of the eight-dimensional channel symbols to their original order. This structure, which is the inverse of interleaver 641, includes delay stages 7411, 7412 and 7413, as well as direct connection 7414.

It will be appreciated that, although various components of the modem transmitter and receiver are disclosed herein for pedagogic clarity as discrete functional elements and indeed—in the case of the various switching circuits—as mechanical elements, those skilled in the art will recognize that the function of any one or more of those elements could be implemented with any appropriate available technology, including one or more appropriately programmed processors, digital signal processing (DSP) chips, etc. For example, multiple trellis encoders and decoders can be realized using a single program routine which, through the mechanism of indirect addressing of multiple arrays within memory, serves to provide the function of each of the multiple devices.

It will thus be appreciated that those skilled in the art will be able to devise numerous arrangements which, although not explicitly shown or described herein, embody the principles of the invention and are within its spirit and scope.

We claim:

1. Apparatus for forming a stream of trellis encoded signal points in response to input information, said apparatus comprising

means for generating a plurality of streams of trellis encoded channel symbols in response to respective portions of said input information, each of said channel symbols being comprised of a plurality of signal points, and

means for interleaving the signal points of said generated channel symbols to form said stream of trellis encoded signal points, said interleaving being carried out in such a way that the signal points of each channel symbol are non-adjacent in said stream of trellis encoded signal points and such that the signal points of adjacent symbols in any one of said channel symbol streams are non-adjacent in said stream of trellis encoded signal points.

2. The apparatus of claim 1 wherein said means for generating generates three of said streams of trellis encoded channel symbols, and wherein said means for interleaving causes there to be interleaved between each of the signal points of each channel symbol at least two signal points from other channel symbols of said streams of trellis encoded channel symbols.

3. The apparatus of claim 1 wherein said channel symbols are 2N-dimensional channel symbols, N>1, and wherein said means for interleaving causes every N^{th} signal point in said interleaved signal point stream to be the N^{th} signal point of a respective one of said channel symbols.

4. The apparatus of claim 2 wherein said channel symbols are 2N-dimensional channel symbols, N>1, and wherein said means for interleaving causes every N^{th} signal point in said interleaved signal point stream to be the N^{th} signal point of a respective one of said channel symbols.

5. A modem comprising

means for receiving a stream of input bits,

means for dividing said stream of input bits into a stream of uncoded bits and a plurality of streams of trellis bits,

means for independently trellis encoding each of said plurality of streams of trellis bits to generate respective streams of data words each identifying one of a plurality of predetermined subsets of the channel symbols of a predetermined 2N-dimensional constellation, N being an integer greater than unity, each of said channel symbols being comprised of a plurality of signal points,

means for selecting an individual channel symbol from each identified subset in response to said stream of uncoded bits to form a stream of channel symbols, and

means for generating a stream of output signal points, said signal point stream being comprised of the signal points of the selected channel symbols, the signal points of said signal point stream being sequenced in such a way that signal points that are either a) part of the same channel symbol, or b) part of channel symbols that are adjacent to one another in said channel symbol stream, are separated in said output stream by at least one other signal point.

6. The apparatus of claim 5 wherein said trellis encoding means includes a plurality of trellis encoder stage

means for trellis encoding respective ones of said streams of trellis bits.

7. The apparatus of claim 5 wherein said means for selecting includes means for modulus converting said stream of uncoded bits.

8. The apparatus of claim 5 wherein said channel symbols are 2N-dimensional channel symbols, N>1, and wherein said means for generating causes every N^{th} signal point in said stream of output signal points to be the N^{th} signal point of a respective one of said channel symbols.

9. Receiver apparatus for recovering information from a received stream of trellis encoded signal points, said signal points having been transmitted to said receiver apparatus by transmitter apparatus which generates said signal points by generating a plurality of streams of trellis encoded channel symbols in response to respective portions of said information, each of said channel symbols being comprised of a plurality of signal points, and by interleaving the signal points of said generated channel symbols to form said stream of trellis encoded signal points, said interleaving being carried out in such a way that the signal points of each channel symbol are non-adjacent in said stream of trellis encoded signal points and such that the signal points of adjacent symbols in any one of said channel symbol streams are non-adjacent in said stream of trellis encoded signal points,

said receiver apparatus comprising

means for deinterleaving the interleaved signal points to recover said plurality of streams of trellis encoded channel symbols, and

a distributed Viterbi decoder for recovering said information from the deinterleaved signal points.

10. The apparatus of claim 9 further comprising

a phase tracking loop, and

means for adapting the operation of said phase tracking loop in response to minimum accumulated path metrics in said distributed Viterbi decoder.

11. A method for forming a stream of trellis encoded signal points in response to input information, said method comprising the steps of

generating a plurality of streams of trellis encoded channel symbols in response to respective portions of said input information, each of said channel symbols being comprised of a plurality of signal points, and

interleaving the signal points of said generated channel symbols to form said stream of trellis encoded signal points, said interleaving being carried out in such a way that the signal points of each channel symbol are non-adjacent in said stream of trellis encoded signal points and such that the signal points of adjacent symbols in any one of said channel symbol streams are non-adjacent in said stream of trellis encoded signal points.

12. The method of claim 11 wherein said generating step generates three of said streams of trellis encoded channel symbols, and wherein said interleaving step causes there to be interleaved between each of the signal points of each channel symbol at least two signal points from other channel symbols of said streams of trellis encoded channel symbols.

13. The method of claim 11 wherein said channel symbols are 2N-dimensional channel symbols, N>1, and wherein said interleaving step causes every N^{th} signal point in said interleaved signal point stream to be the N^{th} signal point of a respective one of said channel symbols.

14. The method of claim 12 wherein said channel symbols are 2N-dimensional channel symbols, N>1, and wherein said interleaving step causes every N^{th} signal point in said interleaved signal point stream to be the N^{th} signal point of a respective one of said channel symbols.

15. A method for use in a modem, said method comprising the steps of

receiving a stream of input bits,

dividing said stream of input bits into a stream of uncoded bits and a plurality of streams of trellis bits,

independently trellis encoding each of said plurality of streams of trellis bits to generate respective streams of data words each identifying one of a plurality of predetermined subsets of the channel symbols of a predetermined 2N-dimensional constellation, N being an integer greater than unity, each of said channel symbols being comprised of a plurality of signal points,

selecting an individual channel symbol from each identified subset in response to said stream of uncoded bits to form a stream of channel symbols, and

generating a stream of output signal points, said signal point stream being comprised of the signal points of the selected channel symbols, the signal points of said signal point stream being sequenced in such a way that signal points that are either a) part of the same channel symbol, or b) part of channel symbols that are adjacent to one another in said channel symbol stream, are separated in said output stream by at least one other signal point.

16. The method of claim 15 wherein in said trellis encoding step a plurality of trellis encoder stages trellis encode respective ones of said streams of trellis bits.

17. The method of claim 15 wherein said selecting step includes the step of modulus converting said stream of uncoded bits.

18. The method of claim 15 wherein said channel symbols are 2N-dimensional channel symbols, N>1, and wherein said generating step causes every N^{th} signal point in said stream of output signal points to be the N^{th} signal point of a respective one of said channel symbols.

19. A method for use in a receiver to recover information from a received stream of trellis encoded signal points, said signal points having been transmitted to said receiver apparatus by a method which includes the steps of

generating a plurality of streams of trellis encoded channel symbols in response to respective portions of said information, each of said channel symbols being comprised of a plurality of signal points, and

interleaving the signal points of said generated channel symbols to form said stream of trellis encoded signal points, said interleaving being carried out in such a way that the signal points of each channel symbol are non-adjacent in said stream of trellis encoded signal points and such that the signal points of adjacent symbols in any one of said channel symbol streams are non-adjacent in said stream of trellis encoded signal points,

said method comprising the steps of

deinterleaving the interleaved signal points to recover said plurality of streams of trellis encoded channel symbols, and

using a distributed Viterbi decoder to recover said information from the deinterleaved signal points.

20. The method of claim 19 wherein said receiver includes a phase tracking loop and wherein said method comprises the further step of adapting the operation of said phase tracking loop in response to minimum accumulated path metrics in said distributed Viterbi decoder.

21. Data communication apparatus comprising

means for receiving input information,

means for generating a plurality of streams of trellis encoded channel symbols in response to respective portions of said input information, each of said channel symbols being comprised of a plurality of signal points,

means for interleaving the signal points of said generated channel symbols to form a stream of trellis encoded signal points, said interleaving being carried out in such a way that the signal points of each channel symbol are non-adjacent in said stream of trellis encoded signal points and such that the signal points of adjacent symbols in any one of said channel symbol streams are non-adjacent in said stream of trellis encoded signal points,

means for applying the stream of trellis encoded signal points to a transmission channel,

means for receiving the stream of trellis encoded signal points from the channel,

means for deinterleaving the interleaved signal points to recover said plurality of streams of trellis encoded channel symbols, and

a distributed Viterbi decoder for recovering said information from the deinterleaved signal points.

22. The apparatus of claim 21 wherein said means for generating generates three of said streams of trellis encoded channel symbols, and wherein said means for interleaving causes there to be interleaved between each of the signal points of each channel symbol at least two signal points from other channel symbols of said streams of trellis encoded channel symbols.

23. The apparatus of claim 21 wherein said channel symbols are 2N-dimensional channel symbols, $N>1$, and wherein said means for interleaving causes every N^{th} signal point in said interleaved signal point stream to be the N^{th} signal point of a respective one of said channel symbols.

24. The apparatus of claim 22 wherein said channel symbols are 2N-dimensional channel symbols, $N>1$, and wherein said means for interleaving causes every N^{th} signal point in said interleaved signal point stream to be the N^{th} signal point of a respective one of said channel symbols.

* * * * *

JS 44 (Rev. 3/99)

CIVIL COVER SHEET

The JS-44 civil cover sheet and the information contained herein neither replace nor supplement the filing and service of pleadings or other papers as required by law, except as provided by local rules of court. This form, approved by the Judicial Conference of the United States in September 1974, is required for the use of the Clerk of Court for the purpose of initiating the civil docket sheet. (SEE INSTRUCTIONS ON THE REVERSE OF THE FORM.)

I. (a) PLAINTIFFS

REMBRANDT TECHNOLOGIES, LP

(b) County of Residence of First Listed Plaintiff * (EXCEPT IN U.S. PLAINTIFF CASES)

*Plaintiff is a New Jersey limited partnership

DEFENDANTS

CBS CORPORATION

County of Residence of First Listed _____ (IN U.S. PLAINTIFF CASES ONLY)

NOTE: IN LAND CONDEMNATION CASES, USE THE LOCATION OF THE LAND INVOLVED.

(c) Attorney's (Firm Name, Address, and Telephone Number)

Steven J. Balick
Ashby & Geddes
222 Delaware Avenue, 17th Floor
Wilmington, DE 19801

Attorneys (If Known)

Unknown

II. BASIS OF JURISDICTION (Place an "X" in One Box Only)

- ☐ 1 U.S. Government Plaintiff
- ☒ 3 Federal Question (U.S. Government Not a Party)
- ☐ 2 U.S. Government Defendant
- ☐ 4 Diversity (Indicate Citizenship of Parties in Item III)

III. CITIZENSHIP OF PRINCIPAL PARTIES (Place an "X" in One Box for Plaintiff and One Box for Defendant) (For Diversity Cases Only)

		DEF			DEF
Citizen of This State	☐ 1	☐ 1	Incorporated *or* Principal Place of Business In This State	☐ 4	☐ 4
Citizen of Another State	☐ 2	☐ 2	Incorporated *and* Principal Place of Business In Another State	☐ 5	☐ 5
Citizen or Subject of a Foreign Country	☐ 3	☐ 3	Foreign Nation	☐ 6	☐ 6

IV. NATURE OF SUIT (Place an "X" in One Box Only)

CONTRACT
- ☐ 110 Insurance
- ☐ 120 Marine
- ☐ 130 Miller Act
- ☐ 140 Negotiable Instrument
- ☐ 150 Recovery of Overpayment & Enforcement of Judgment
- ☐ 151 Medicare Act
- ☐ 152 Recovery of Defaulted Student Loans (Excl. Veterans)
- ☐ 153 Recovery of Overpayment of Veteran's Benefits
- ☐ 160 Stockholders' Suits
- ☐ 190 Other Contract
- ☐ 195 Contract Product Liability

TORTS

PERSONAL INJURY
- ☐ 310 Airplane
- ☐ 315 Airplane Product Liability
- ☐ 320 Assault, Libel & Slander
- ☐ 330 Federal Employers' Liability
- ☐ 340 Marine
- ☐ 345 Marine Product Liability
- ☐ 350 Motor Vehicle
- ☐ 355 Motor Vehicle Product Liability
- ☐ 360 Other Personal Injury

PERSONAL INJURY
- ☐ 362 Personal Injury—Med. Malpractice
- ☐ 365 Personal Injury—Product Liability
- ☐ 368 Asbestos Personal Injury Product Liability

PERSONAL PROPERTY
- ☐ 370 Other Fraud
- ☐ 371 Truth in Lending
- ☐ 380 Other Personal Property Damage
- ☐ 385 Property Damage Product Liability

FORFEITURE/PENALTY
- ☐ 610 Agriculture
- ☐ 620 Other Food & Drug
- ☐ 625 Drug Related Seizure of Property 21 USC
- ☐ 630 Liquor Laws
- ☐ 640 R.R. & Truck
- ☐ 650 Airline Regs.
- ☐ 660 Occupational Safety/Health
- ☐ 690 Other

BANKRUPTCY
- ☐ 422 Appeal 28 USC 158
- ☐ 423 Withdrawal 28 USC 157

OTHER STATUTES
- ☐ 400 State Reapportionment
- ☐ 410 Antitrust
- ☐ 430 Banks and Banking
- ☐ 450 Commerce/ICC Rates/etc.
- ☐ 460 Deportation
- ☐ 470 Racketeer Influenced and Corrupt Organizations
- ☐ 810 Selective Service
- ☐ 850 Securities/Commodities/ Exchange
- ☐ 875 Customer Challenge 12 USC 3410
- ☐ 891 Agricultural Acts
- ☐ 892 Economic Stabilization Act
- ☐ 893 Environmental Matters
- ☐ 894 Energy Allocation Act
- ☐ 895 Freedom of Information Act
- ☐ 900 Appeal of Fee Determination Under Equal Access to Justice
- ☐ 950 Constitutionality of State Statutes
- ☐ 890 Other Statutory Actions

REAL PROPERTY
- ☐ 210 Land Condemnation
- ☐ 220 Foreclosure
- ☐ 230 Rent Lease & Ejectment
- ☐ 240 Torts to Land
- ☐ 245 Tort Product Liability
- ☐ 290 All Other Real Property

CIVIL RIGHTS
- ☐ 441 Voting
- ☐ 442 Employment
- ☐ 443 Housing/ Accommodations
- ☐ 444 Welfare
- ☐ 440 Other Civil Rights

PRISONER PETITIONS
- ☐ 510 Motions to Vacate Sentence
- Habeas Corpus:
- ☐ 530 General
- ☐ 535 Death Penalty
- ☐ 540 Mandamus & Other
- ☐ 550 Civil Rights
- ☐ 555 Prison Condition

LABOR
- ☐ 710 Fair Labor Standards Act
- ☐ 720 Labor/Mgmt. Relations
- ☐ 730 Labor/Mgmt.Reporting & Disclosure Act
- ☐ 740 Railway Labor Act
- ☐ 790 Other Labor Litigation
- ☐ 791 Empl. Ret. Inc. Security Act

PROPERTY RIGHTS
- ☐ 820 Copyrights
- ☒ 830 Patent
- ☐ 840 Trademark

SOCIAL SECURITY
- ☐ 861 HIA (1395ff)
- ☐ 862 Black Lung (923)
- ☐ 863 DIWC/DIWW (405(g))
- ☐ 864 SSID Title XVI
- ☐ 865 RSI (405(g))

FEDERAL TAX SUITS
- ☐ 870 Taxes (U.S. Plaintiff or Defendant)
- ☐ 871 IRS—Third Party 26 USC 7609

V. ORIGIN (PLACE AN "X" IN ONE BOX ONLY)

☒ 1 Original Proceeding ☐ 2 Removed from State Court ☐ 3 Remanded from Appellate Court ☐ 4 Reinstated or Reopened ☐ 5 Transferred from another district (specify) ☐ 6 Multidistrict Litigation ☐ 7 Appeal to District Judge from Magistrate Judgment

VI. CAUSE OF ACTION (Cite the U.S. Civil Statute under which you are filing and write brief statement of cause. Do not cite jurisdictional statutes unless diversity.)

Title 35 U.S. Code. This is an action arising under the patent laws of the United States.

VII. REQUESTED IN COMPLAINT: ☐ CHECK IF THIS IS A CLASS ACTION UNDER F.R.C.P. 23 **DEMAND $** CHECK YES only if demanded in complaint: **JURY DEMAND:** ☒ Yes ☐ No

VIII. RELATED CASE(S) IF ANY (See instructions): JUDGE Sleet DOCKET NUMBER 06-635-GMS

DATE December 1, 2006 SIGNATURE OF ATTORNEY OF RECORD Steven J. Balick

FOR OFFICE USE ONLY

RECEIPT # _____ AMOUNT _____ APPLYING IFP _____ JUDGE _____ MAG. JUDGE _____

JS 44 Reverse (Rev. 12/96)

INSTRUCTIONS FOR ATTORNEYS COMPLETING CIVIL COVER SHEET FORM JS-44

Authority For Civil Cover Sheet

The JS-44 civil cover sheet and the information contained herein neither replaces nor supplements the filings and service of pleading or other papers as required by law, except as provided by local rules of court. This form, approved by the Judicial Conference of the United States in September 1974, is required for the use of the Clerk of Court for the purpose of initiating the civil docket sheet. Consequently, a civil cover sheet is submitted to the Clerk of Court for each civil complaint filed. The attorney filing a case should complete the form as follows:

I. (a) Plaintiffs-Defendants. Enter names (last, first, middle initial) of plaintiff and defendant. If the plaintiff or defendant is a government agency, use only the full name or standard abbreviations. If the plaintiff or defendant is an official within a government agency, identify first the agency and then the official, giving both name and title.

(b.) County of Residence. For each civil case filed, except U.S. plaintiff cases, enter the name of the county where the first listed plaintiff resides at the time of filing. In U.S. plaintiff cases, enter the name of the county in which the first listed defendant resides at the time of filing. (NOTE: In land condemnation cases, the county of residence of the "defendant" is the location of the tract of land involved.)

(c) Attorneys. Enter the firm name, address, telephone number, and attorney of record. If there are several attorneys, list them on an attachment, noting in this section "(see attachment)".

II. Jurisdiction. The basis of jurisdiction is set forth under Rule 8(a), F.R.C.P., which requires that jurisdictions be shown in pleadings. Place an "X" in one of the boxes. If there is more than one basis of jurisdiction, precedence is given in the order shown below.

United States plaintiff. (1) Jurisdiction based on 28 U.S.C. 1345 and 1348. Suits by agencies and officers of the United States, are included here.

United States defendant. (2) When the plaintiff is suing the United States, its officers or agencies, place an "X" in this box.

Federal question. (3) This refers to suits under 28 U.S.C. 1331, where jurisdiction arises under the Constitution of the United States, an amendment to the Constitution, an act of Congress or a treaty of the United States. In cases where the U.S. is a party, the U.S. plaintiff or defendant code takes precedence, and box 1 or 2 should be marked.

Diversity of citizenship. (4) This refers to suits under 28 U.S.C. 1332, where parties are citizens of different states. When Box 4 is checked, the citizenship of the different parties must be checked. (See Section III below; federal question actions take precedence over diversity cases.)

III. Residence (citizenship) of Principal Parties. This section of the JS-44 is to be completed if diversity of citizenship was indicated above. Mark this section for each principal party.

IV. Nature of Suit. Place an "X" in the appropriate box. If the nature of suit cannot be determined, be sure the cause of action, in Section IV below, is sufficient to enable the deputy clerk or the statistical clerks in the Administrative Office to determine the nature of suit. If the cause fits more than one nature of suit, select the most definitive.

V. Origin. Place an "X" in one of the seven boxes.

Original Proceedings. (1) Cases which originate in the United States district courts.

Removed from State Court. (2) Proceedings initiated in state courts may be removed to the district courts under Title 28 U.S.C., Section 1441. When the petition for removal is granted, check this box.

Remanded from Appellate Court. (3) Check this box for cases remanded to the district court for further action. Use the date of remand as the filing date.

Reinstated or Reopened. (4) Check this box for cases reinstated or reopened in the district court. Use the reopening date as the filing date.

Transferred from Another District. (5) For cases transferred under Title 28 U.S.C. Section 1404(a) Do not use this for within district transfers or multidistrict litigation transfers.

Multidistrict Litigation. (6) Check this box when a multidistrict case is transferred into the district under authority of Title 28 U.S.C. Section 1407. When this box is checked, do not check (5) above.

Appeal to District Judge from Magistrate Judgment. (7) Check this box for an appeal from a magistrate judge's decision.

VI. Cause of Action. Report the civil statute directly related to the cause of action and give a brief description of the cause.

VII. Requested in Complaint. Class Action. Place an "X" in this box if you are filing a class action under Rule 23, F.R.Cv.P.

Demand. In this space enter the dollar amount (in thousands of dollars) being demanded or indicate other demand such as a preliminary injunction.

Jury Demand. Check the appropriate box to indicate whether or not a jury is being demanded.

VIII. Related Cases. This section of the JS-44 is used to reference related pending cases if any. If there are related pending cases, insert the docket numbers and the corresponding judge names for such cases.

Date and Attorney Signature. Date and sign the civil cover sheet.

AO FORM 85 RECEIPT (REV. 9/04)

United States District Court for the District of Delaware

Civil Action No. 06-727

ACKNOWLEDGMENT OF RECEIPT FOR AO FORM 85

NOTICE OF AVAILABILITY OF A UNITED STATES MAGISTRATE JUDGE TO EXERCISE JURISDICTION

I HEREBY ACKNOWLEDGE RECEIPT OF 3 COPIES OF AO FORM 85.

DEC 01 2006
(Date forms issued)

(Signature of Party or their Representative)

Jason Sparkle
(Printed name of Party or their Representative)

Note: Completed receipt will be filed in the Civil Action